

HC-M-PN3-4,00-ST


Order No.: 1663501

The illustration shows versions, pneumatic male, female and female with valve

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663501>




Pneumatics pin, for HC-M-PN3 module, cross section of hose 4.0 mm

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  4 017918 123314 |
| sales group | D044 |
| Pack | 10 pcs. |
| Customs tariff | 85369010 |
| Catalog page information | Page 551 (PC-2011) |

Product notes

WEEE/RoHS-compliant since:
03/27/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|---|-------------------|
| Electrical characteristics | |
| Ambient temperature (operation) | -40 °C ... 125 °C |
| Mechanical characteristics | |
| Operating pressure, vacuum | 6.00 bar |
| Internal diameter of pressure hose connection | 4 mm |
| Insertion/withdrawal cycles | ≥ 500 |
| General characteristics | |
| Color | black |

Material data

| | |
|------------------|---------------|
| Contact material | Delrin acetal |
|------------------|---------------|

Certificates / Approvals



Certification

GOST, UL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;