

## HC-M-PN2-6,00-ST


Order No.: 1676750

The illustration shows versions, pneumatic male, female and female with valve

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1676750>



Pneumatics male connector, for HC-M-PN2 module, cross section of hose 6.0 mm

Commercial data	
GTIN (EAN)	
sales group	D044
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 551 (PC-2011)

### Product notes

WEEE/RoHS-compliant since:  
03/27/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Electrical characteristics</b>	
Ambient temperature (operation)	-40 °C ... 125 °C
<b>Mechanical characteristics</b>	
Operating pressure, vacuum	6.00 bar
Internal diameter of pressure hose connection	6 mm
Insertion/withdrawal cycles	≥ 500
<b>General characteristics</b>	
Color	black

**Material data**

Contact material	Delrin acetal
------------------	---------------

**Certificates / Approvals**



Certification

GOST, UL

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;