



- NOTES:
1. METALSHELLS: STEEL; min. 320µ" TIN
 2. INSULATORS: PBT GF UL 94 V-0, GREEN
 3. HIGH POWER CONTACTS 20A: COPPER ALLOY
PLATING: 30µ" HARD GOLD OVER min. 50µ" NICKEL
 4. METAL BRACKET: STEEL; min. 320µ" TIN over 80µ" NICKEL
 5. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
 6. PCB-SNAP: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
PCB-HOLE: Ø3.1±0.1; PCB THICKNESS 1.6mm
 7. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
 8. CONNECTOR IS PART MARKED: PART-NO. CONEC Y/WW
 9. = CHECK DIMENSION

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY, WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GMBH
DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name

tolerance	dim. in mm	scale:	2:1 (5:1)
		material:	SEE NOTES
2003	date	name	title:
drawn	20.10.	Lehmenkühler	D-SUB COMBINATION FEMALE 90° 8W8S with threaded insert, metal bracket and clip
appd.	20.10.	MMickenbecker	
norm			dwg no:
d-old			AutoCAD 2000
CONEC			DIN-A
			3
			sh:1/1
			part no: 3008W8SXX56N40X