




[Home](#)
[About Us](#)
[Products](#)
[Applications](#)
[Sales Support](#)
[Contact Us](#)
 Search  

[Industrial Products](#) > 
 [Jacks and Plugs](#) > 
 [DC Power Jack and Plug Series](#) > 
 [DC Power Jacks](#) > 
 [Straight DC Power Jacks](#)

## Straight DC Power Jacks



Straight versions of our DC power jacks. These versions have threaded bushings to allow use of both standard and locking power plugs. The L versions of the power jacks have a longer bushing (0.319") to accommodate thicker panel mount applications. Available in pin diameters of 0.050", 0.080", and 0.100".

[enlarge](#)

Products

Specifications

User Guide

Need more info? Contact Switchcraft customer service

[Printer friendly version](#)

### MATERIALS:

**Housing:** Thermoplastic

**Bushing:** Plated copper alloy

**Terminals:** Plated copper alloy

**Insulators:** Rigid Plastic

**Hardware:** Supplied with one P2439 nickel plated copper alloy hex nut, and one P2441 nickel plated steel flat washer

### ELECTRICAL:

**Current Rating:** 5A, 12V DC resistive

**Contact Resistance:** 0.01 Ohms max. (initial),

0.02 Ohms max. (after humidity, durability exposure),

0.10 Ohms max. (after salt spray)

**Insulation Resistance:** 10,000 Mohms min. (initial),

1,000 Mohms min. (after humidity, durability exposure)

**Dielectric Withstanding Voltage:** 500 VAC max.

### MECHANICAL:

**Lifecycles:** 10,000 cycles min.

5555 N Elston Ave • Chicago • Illinois • 60630 • USA • 1.773.792.2700

[Home](#)
[About Us](#)
[Sales](#)
[Contact Us](#)
[Login](#)



