



## Product Detail



<b>Product Line:</b>	<a href="#">Johnson</a> (Click for customer service)
<b>Part Number:</b>	105-0301-001
<b>Description:</b>	Tip Plug - Insulated: Solderless Type
<b>Product Family:</b>	TIP PLUG
<b>Body Material:</b>	Nylon 6/6 per ASTM D4066
<b>Breakdown Voltage:</b>	3500 Vrms min.
<b>Color / Finish:</b>	White
<b>Contact Material:</b>	Brass
<b>Contact Finish:</b>	Nickel
<b>Contact Termination:</b>	Solderless
<b>Current:</b>	10 amps
<b>Description:</b>	Insulated Solderless
<b>For Use With:</b>	.080 (2.00) Tip Jack

20070523-1523

# Tip Plug

## Insulated: Solderless Type

**JOHNSON**  
Components™  
INCHES (MILLIMETERS)  
CUSTOMER DRAWINGS AVAILABLE UPON REQUEST

### SPECIFICATIONS

**Contact:** Brass per QQ-B-626D

**Finish:** Nickel

**Insulated Handle:** Nylon 6/6 per ASTM D4066

### RATINGS

**Current:** 10 amps

**Breakdown Voltage:** 3500 Vrms minimum =

**Contact Resistance:** 0.010 ohms maximum

<b>NICKEL PLATING</b>
105-0301-001 White

**For Standard Tip Jack: .080 (2.00) Diameter**

### FEATURES:

- Recessed head to reduce shock hazard
- Accepts wire sizes up to 16 gauge
- Nylon UL approved for self extinguishing

