

AVX Wire-to-Board Connectors



Version 10.10

AVX
A KYOCERA GROUP COMPANY

Table of Contents



INSULATION DISPLACEMENT CONNECTORS (IDC) WIRE TO BOARD (WTB)

| | |
|-----------------------------------------------------------------------------|--------------|
| DISCRETE WIRE IDC – SERIES 9175 | 2-6 |
| 26-28 AWG 2 Way IDC Connector | 3 |
| 26-28 AWG 3 Way IDC Connector | 4 |
| Hand Insertion Tooling / Clearance Area on PCB for Hand Tooling | 5 |
| Insertion Tooling Requires Hand Press with Flat Rock Plates | 6 |
| DISCRETE WIRE IDC – SERIES 9176 | 7-14 |
| 18-24 AWG 1 Way IDC Connector | 8 |
| 18-24 AWG 2 Way IDC Connector | 9 |
| 18-24 AWG 3 Way IDC Connector | 10 |
| Accessory Cap - Through Wire | 11 |
| Accessory Cap - Wire Stop | 12 |
| Hand Insertion Tooling for Single 18/24 Gauge Wire | 13 |
| Insertion Tooling Requires Hand Press with Flat Rock Plates | 14 |
| DISCRETE WIRE IDC CONTACT AND CAP – SERIES 9176-400 | 15-19 |
| Contact Details | 16 |
| 22-24 AWG IDC Wire to Board Connector Single Contact | 17 |
| Assembly Tooling Cap Not Used – Wire onto Contact | 18 |
| Cap Details | 19 |
| DISCRETE WIRE IDC CONTACT AND CAP – SERIES 9176-500 | 20-24 |
| Contact Details | 21 |
| 18-24 AWG IDC Wire to Board Connector Single Contact | 22 |
| Assembly Tooling Cap Used/Assembly Tooling Cap Not Used – Wire onto Contact | 23 |
| Cap Details | 24 |
| DISCRETE WIRE IDC – SERIES 9177 | 25-29 |
| 14-20 AWG 1 Way IDC Connector | 26 |
| 14-20 AWG 2 Way IDC Connector | 27 |
| 14-20 AWG 3 Way IDC Connector | 28 |
| Insertion Tooling Requires Hand Press with Flat Rock Plates | 29 |
| Insertion Tooling PCB Restricted Areas for Assembly Tooling | 29 |

POKE-HOME WIRED TO BOARD (WTB)

| | |
|------------------------------------------------------|--------------|
| DISCRETE WIRE-TO-BOARD; POKE HOME SERIES 9276 | 30-37 |
| 1 Way Wire to Board Connector | 31 |
| 2 Way Wire to Board Connector | 32 |
| 3 Way Wire to Board Connector | 33 |
| 4 Way Wire to Board Connector | 34 |
| 6 Way Wire to Board Connector | 35 |
| 8 Way Wire to Board Connector | 36 |
| Wire Assembly/Wire Extraction | 37 |

INPUT/OUTPUT CONNECTORS

| | |
|-------------------------------------|--------------|
| I/O CONNECTORS – SERIES 9157 | 38-43 |
| Standard I/O, 15 Position | 38-41 |
| Standard I/O, 19 Position | 42-43 |
| I/O CONNECTORS – SERIES 9257 | 44-50 |
| Reduced Size I/O | 44-46 |
| Mini I/O | 47-50 |

NOTICE: Specifications are subject to change without notice. Contact your nearest AVX Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all applications.



SSL - Discrete Wire IDC



Series 9175



The 917X series of surface mount Insulation Displacement Connectors (IDC) were developed to meet the harsh automotive and industrial market applications for connecting individual wires directly to a PCB ranging from 14 AWG to 28 AWG. This industry proven contact system has been tested to automotive levels of shock, vibration, and temperature cycling to prove their reliability and robustness. The simplicity of inserting a wire into the connector with a small tool allows a wide range of devices to be connected to the PCB without soldering. In SSL applications specifically, these connectors are used to bring power and signal onto the PCB or are used to daisy chain multiple boards together in a long string. While the IDC contact provides a gas-tight connection to conductor of the wire, the housing has been designed to grab the insulation of the wire to provide a positive strain relief even in the harshest conditions. In case of repair, the wires can be removed and replace up to three times.

The 9175 series accepts 26 AWG to 28 AWG wires with an insulation diameter ranging from 0.7mm to 1.0mm. These single contact connectors support a 1 amp current rating and have a split SMT tail design to provide maximum stability on the PCB. Available in a 2p and 3p configuration, these connectors can be end stackable for higher pin counts.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application Notes: refer to 201-01-124

FEATURES AND BENEFITS

- IDC contact provides a gas-tight connection to the PCB for long term reliability
- Connector housing captures the wire insulation for positive strain relief
- Tested to automotive levels on shock, vibration and temperature cycling for reliability
- Low and high volume assembly tools to match production volumes
- Reduced total applied cost versus solder or crimp processes
- High temperature insulator capable to 260 degrees C reflow soldering processes

ELECTRICAL

- Current Rating: 1 Amp / Contact
- Voltage Rating: 125 VAC

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Nylon 46: UL94V0
- Contact Material: Phosphor Bronze
- Plating: Tin over Nickel
- Durability: 3 Cycles

HOW TO ORDER

00
Prefix

9175
Series

00X
Number of Ways

| Code | No of Ways | Details |
|------|------------|---------|
| 002 | 2 | Page 3 |
| 003 | 3 | Page 4 |

001
Wire Gauge Size

| Code | Accepted Wire Gauge | Wire Insulation |
|------|----------------------------------------------------------|--------------------------|
| 001 | 28 Gauge Solid or Stranded 26 Gauge Solid or Stranded | Min Ø 0.70 Max Ø 1.00 |

X
Insulator Color

| Code | Color | Application |
|------|-------|-------------|
| 0 | Black | Industrial |
| 1 | White | Lighting |

06
Plating Option
06 = Pure Tin all over


Certification: UL File #E320991

SSL - Discrete Wire IDC



Series 9175



26-28 AWG 2 WAY IDC CONNECTOR





- NOTES:
1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
 2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 2.
 3. CONNECTOR DESIGNED TO ACCEPT 26 AND 28 GAUGE SOLID OR STRANDED WIRE.
 4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
 5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-100.





SMT PCB LAYOUT

PURE TIN PADS



PACKING DETAILS

| | |
|------------|-------|
| REEL QTY | 2000 |
| LEADER | 500MM |
| TRAILER | 500MM |
| REEL / BOX | 7 |
| PACK QTY | 14000 |




SSL - Discrete Wire IDC

Series 9175





26-28 AWG 3 WAY IDC CONNECTOR




NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 2.
3. CONNECTOR DESIGNED TO ACCEPT 26 AND 28 GAUGE SOLID OR STRANDED WIRE.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-100.





SMT PCB LAYOUT

PURE TIN PADS



PACKING DETAILS

| | |
|------------|-------|
| REEL QTY | 2000 |
| LEADER | 500MM |
| TRAILER | 500MM |
| REEL / BOX | 7 |
| PACK QTY | 14000 |




SSL - Discrete Wire IDC




Series 9175

HAND INSERTION TOOLING SINGLE WIRE INSERTION TOOL FOR 26/28 GAUGE WIRE



UNIVERSAL HANDLE

| Details | Tool Part Number |
|-------------------------|---------------------|
| 6.35 A/F HEX BIT HOLDER | 06 7000 7730 01 000 |



ALL METAL

HIGH PRODUCTION Metal

| Max Insulation Dia | Tool Part Number |
|--------------------|---------------------|
| Ø 1.00 | 06 9175 7017 01 000 |




METAL SHANK

PLASTIC

MED PRODUCTION Metal/Plastic

| Max Insulation Dia | Tool Part Number |
|--------------------|---------------------|
| Ø 1.00 | 06 9175 7016 01 000 |




ALL PLASTIC

LOW PRODUCTION Plastic

| Max Insulation Dia | Tool Part Number |
|--------------------|---------------------|
| Ø 1.00 | 06 9175 7004 01 000 |


CLEARANCE AREA ON PCB FOR HAND TOOLING

2 WAY



AREA TO BE KEPT CLEAR FOR TOOLING

3 WAY



AREA TO BE KEPT CLEAR FOR TOOLING




INSERTION TOOLING REQUIRES HAND PRESS WITH FLAT ROCK PLATES

2 WAY TOOL

TOOL NUMBER 06-9175-7017-01-002

SKETCH SHOWS PCB RESTRICTED AREAS FOR ASSEMBLY TOOLING




NOTES:

1. DIMENSIONS SHOWN ARE REFERENCE DIMENSIONS.
2. MAXIMUM COMPONENT HEIGHT 0.80MM IN THIS AREA.
3. MAXIMUM COMPONENT HEIGHT 4.00MM IN THIS AREA.
4. THE SAME RESTRICTIONS APPLY TO ALL WIRE INSULATION DIAMETERS.

3 WAY TOOL

TOOL NUMBER 06-9175-7017-01-003


SKETCH SHOWS PCB RESTRICTED AREAS FOR ASSEMBLY TOOLING



SSL - Discrete Wire IDC



Series 9176



The 917X series of surface mount Insulation Displacement Connectors (IDC) were developed to meet the harsh automotive and industrial market applications for connecting individual wires directly to a PCB ranging from 14 AWG to 28 AWG. This industry proven contact system has been tested to automotive levels of shock, vibration, and temperature cycling to prove their reliability and robustness. The simplicity of inserting a wire into the connector with a small tool allows a wide range of devices to be connected to the PCB without soldering. In SSL applications specifically, these connectors are used to bring power and signal onto the PCB or are used to daisy chain multiple boards together in a long string. While the IDC contact provides a gas-tight connection to conductor of the wire, the housing has been designed to grab the insulation of the wire to provide a positive strain relief even in the harshest conditions. In case of repair, the wires can be removed and replace up to three times.

The 9176 series accepts 18 AWG to 24 AWG wires with an insulation diameter ranging from 1.1mm to 2.1mm. These dual contact connectors support a 10 amp current rating with two large SMT solder tails per wire to provide maximum stability on the PCB. Available in 1p-3p configuration, these connectors can be end stackable for higher pin counts. The 9176 series also comes with optional locking strain relief caps that act as the termination tool for severe vibration applications.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application Notes: refer to 201-01-124

FEATURES AND BENEFITS

- IDC contact provides a gas-tight connection to the PCB for long term reliability
- Connector housing captures the wire insulation for positive strain relief
- Tested to automotive levels on shock, vibration and temperature cycling for reliability
- Low and high volume assembly tools to match production volumes
- Reduced total applied cost versus solder or crimp processes
- Optional thru and end caps lock in place to provide maximum strain relief
- High temperature insulator capable to 260°C reflow soldering processes

ELECTRICAL

- Current Rating: 10 Amp / Contact
- Voltage Rating: 250 VAC

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Nylon 46: UL94V0
- Contact Material: Phosphor Bronze
- Plating: Tin over Nickel
- Durability: 3 Cycles

HOW TO ORDER

| 00 | 9176 | 00X |
|--------|------------|----------------|
| Prefix | Series | Number of Ways |
| | | |
| Code | No of Ways | Details |
| 001 | 1 | Page 8 |
| 002 | 2 | Page 9 |
| 003 | 3 | Page 10 |

00X

Wire Gauge Size

| Code | Accepted Wire Gauge | Wire Insulation | Cap Code Pages 11-12 |
|------|---------------------|-----------------|----------------------|
| 001 | 18 Gauge Stranded | Ø 1.6-2.1 | 021 |
| 011 | 20 Gauge Stranded | Ø 1.6-2.1 | 021 |
| 022 | 22 Gauge Stranded | Ø 1.1-1.6 | 016 |
| 032 | 24 Gauge Stranded | Ø 1.1-1.6 | 016 |

X
↓
Insulator Color

| Code | Color | Application |
|------|-------|-------------|
| 0 | Black | Industrial |
| 1 | White | Lighting |

| 06 |
|------------------------|
| Plating Option |
| 06 = Pure Tin all over |

Certification: UL File #E320991




SSL - Discrete Wire IDC





Series 9176

18-24 AWG 1 WAY IDC CONNECTOR




- NOTES:
1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
 2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 7.
 3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 24 AND 18 GAUGE STRANDED WIRE.
 4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
 5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
 6. FOR PCB SPACE RESTRICTED BY WIRE ASSEMBLY TOOLING REFER TO PAGE 11.
 7. FOR HAND WIRE ASSEMBLY TOOLING REFER TO PAGE 13.



| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|-----|
| 001 | 18 Gauge Stranded | 0.72 | Ø 1.6-2.1 | 2.1 |
| 011 | 20 Gauge Stranded | 0.60 | Ø 1.6-2.1 | 2.1 |
| 022 | 22 Gauge Stranded | 0.47 | Ø 1.1-1.6 | 1.6 |
| 032 | 24 Gauge Stranded | 0.37 | Ø 1.1-1.6 | 1.6 |



SMT PCB LAYOUT

PURE TIN PADS



PACKING DETAILS

| | |
|----------|-------|
| REEL QTY | 1000 |
| LEADER | 480MM |
| TRAILER | 120MM |




SSL - Discrete Wire IDC

Series 9176




18-24 AWG 2 WAY IDC CONNECTOR





PICK UP AREA 1.9 x 5.00mm MIN

NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 7.
3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 24 AND 18 GAUGE STRANDED WIRE.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
6. FOR PCB SPACE RESTRICTED BY WIRE ASSEMBLY TOOLING REFER TO PAGE 11.
7. FOR HAND WIRE ASSEMBLY TOOLING REFER TO PAGE 13
8. FOR PRESS WIRE ASSEMBLY TOOLING REFER TO PAGE 14.
9. FOR ACCESSORY CAPS REFER TO PAGES 11 AND 12.




ALL TAILS TO BE WITHIN 0.10mm COPLANARITY.



| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|-----|
| 001 | 18 Gauge Stranded | 0.72 | Ø 1.6-2.1 | 2.1 |
| 011 | 20 Gauge Stranded | 0.60 | Ø 1.6-2.1 | 2.1 |
| 022 | 22 Gauge Stranded | 0.47 | Ø 1.1-1.6 | 1.6 |
| 032 | 24 Gauge Stranded | 0.37 | Ø 1.1-1.6 | 1.6 |



SMT PCB LAYOUT

PURE TIN PADS




PACKING DETAILS

| | |
|----------|-------|
| REEL QTY | 1000 |
| LEADER | 480MM |
| TRAILER | 120MM |





18-24 AWG 3 WAY IDC CONNECTOR




NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 7.
3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 24 AND 18 GAUGE STRANDED WIRE.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
6. FOR PCB SPACE RESTRICTED BY WIRE ASSEMBLY TOOLING REFER TO PAGE 11.
7. FOR HAND WIRE ASSEMBLY TOOLING REFER TO PAGE 13
8. FOR PRESS WIRE ASSEMBLY TOOLING REFER TO PAGE 14.
9. FOR ACCESSORY CAPS REFER TO PAGES 11 AND 12.




| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|-----|
| 001 | 18 Gauge Stranded | 0.72 | Ø 1.6-2.1 | 2.1 |
| 011 | 20 Gauge Stranded | 0.60 | Ø 1.6-2.1 | 2.1 |
| 022 | 22 Gauge Stranded | 0.47 | Ø 1.1-1.6 | 1.6 |
| 032 | 24 Gauge Stranded | 0.37 | Ø 1.1-1.6 | 1.6 |





SMT PCB LAYOUT

PURE TIN PADS





PACKING DETAILS


| | |
|----------|-------|
| REEL QTY | 1000 |
| LEADER | 480MM |
| TRAILER | 120MM |




60-9176-00X-0XX-X00 ACCESSORY CAP – THROUGH WIRE




60-9176-002-016-X00



60-9176-003-016-X00



60-9176-002-021-X00



60-9176-003-021-X00



NOTES:

1. CAP FOR IDC WIRE TO BOARD CONNECTION, 2 AND 3 WAY, THROUGH WIRE.
2. FOR USE WITH STANDARD 9176 IDC CONNECTORS, SEE PAGE 7 FOR THE CORRECT PART CODE TO MATCH WIRE.
3. CAP MATERIAL: GLASS FILLED NYLON 46, FOR COLORS SEE TABLE BELOW.
4. DIMENSIONS A, B AND TEXT, SEE TABLE BELOW.
5. CAPS DESIGNED TO ACCOMMODATE WIRE INSULATION DIAMETERS 1.1MM TO 1.6MM AND 1.6MM TO 2.1MM.
6. ALL DIMENSIONS SHOWN ARE REFERENCE DIMENSIONS.
7. PACKED IN BAGS, 1000 PIECES PER BAG.


| Code | Slot A (AWG) | Diameter B | Text |
|------|--------------|------------|-----------|
| 016 | 1.60 (22-24) | 1.00 | 9176 Ø1.6 |
| 021 | 2.10 (18-20) | 1.50 | 9176 Ø2.1 |

| Color | X00 |
|-------|-----|
| Black | 000 |
| White | 100 |


60-9176-00X-0XX-X99 ACCESSORY CAP - WIRE STOP




60-9176-002-016-X99



60-9176-003-016-X99



60-9176-002-021-X99



60-9176-003-021-X99

NOTES:

1. CAP FOR IDC WIRE TO BOARD CONNECTION, 2 AND 3 WAY, WITH WIRE STOP.
2. FOR USE WITH STANDARD 9176 IDC CONNECTORS, SEE PAGE 7 FOR THE CORRECT PART CODE TO MATCH WIRE.
3. CAP MATERIAL: GLASS FILLED NYLON 46, FOR COLORS SEE TABLE BELOW.
4. DIMENSIONS A, B AND TEXT, SEE TABLE BELOW.
5. CAPS DESIGNED TO ACCOMMODATE WIRE INSULATION DIAMETERS 1.1MM TO 1.6MM AND 1.6MM TO 2.1MM.
6. ALL DIMENSIONS SHOWN ARE REFERENCE DIMENSIONS.
7. PACKED IN BAGS, 1000 PIECES PER BAG.

| Code | Slot A (AWG) | Diameter B | Text |
|------|--------------|------------|-----------|
| 016 | 1.60 (22-24) | 1.00 | 9176 Ø1.6 |
| 021 | 2.10 (18-20) | 1.50 | 9176 Ø2.1 |


| Color | X99 |
|-------|-----|
| Black | 099 |
| White | 199 |

SSL - Discrete Wire IDC




Series 9176

HAND INSERTION TOOLING FOR SINGLE 18/24 GAUGE WIRE




UNIVERSAL HANDLE

| Details | Tool Part Number |
|-------------------------|---------------------|
| 6.35 A/F HEX BIT HOLDER | 06 7000 7730 01 000 |



HIGH PRODUCTION Metal

| Max Insulation Dia (AWG) | Tool Part Number |
|--------------------------|---------------------|
| 2.10 (18-20) | 06 9176 7017 01 000 |
| 1.60 (22-24) | 06 9176 7017 02 000 |




MED PRODUCTION Metal/Plastic

| Max Insulation Dia (AWG) | Tool Part Number |
|--------------------------|---------------------|
| 2.10 (18-20) | 06 9176 7016 01 000 |
| 1.60 (22-24) | 06 9176 7016 02 000 |


CLEARANCE AREA ON PCB FOR HAND TOOLING

1 WAY




AREA TO BE KEPT CLEAR FOR TOOLING

2 WAY



AREA TO BE KEPT CLEAR FOR TOOLING

3 WAY



AREA TO BE KEPT CLEAR FOR TOOLING




SSL - Discrete Wire IDC




Series 9176

INSERTION TOOLING REQUIRES HAND PRESS WITH FLAT ROCK PLATES

2 WAY






3 WAY






HIGH PRODUCTION Metal

| No. of Ways | Max Insulation Dia (AWG) | Tool Part Number |
|-------------|--------------------------|---------------------|
| 2 | 2.10 (18-20) | 06 9176 7017 01 002 |
| | 1.60 (22-24) | 06 9176 7017 02 002 |
| 3 | 2.10 (18-20) | 06 9176 7017 01 003 |
| | 1.60 (22-24) | 06 9176 7017 02 003 |

2 WAY



3 WAY



- NOTES:
1. DIMENSIONS SHOWN ARE REFERENCE DIMENSIONS.
 2. MAXIMUM COMPONENT HEIGHT 1.00MM IN THIS AREA.
 3. MAXIMUM COMPONENT HEIGHT 6.00MM IN THIS AREA.
 4. THE SAME RESTRICTIONS APPLY TO ALL WIRE INSULATION DIAMETERS
 5. 2 AND 3 WAY TOOLS ONLY, FOR USE UNDER HAND PRESS WITH FLAT PLATES.
 6. FOR HAND TOOLING REFER TO PAGE 13.



SSL - Discrete Wire IDC Contact & Cap

Series 9176-400



The 917X series of surface mount Insulation Displacement Connectors (IDC) were developed to meet the harsh automotive and industrial market applications for connecting individual wires directly to a PCB ranging from 14 AWG to 28 AWG. This industry proven contact system has been tested to automotive levels of shock, vibration, and temperature cycling to prove their reliability and robustness. This new single contact was developed as a standalone component to enhance the application uses with the IDC technology. The simplicity of inserting a wire into an SMT contact with a small tool or optional retention / termination cap allows a wide range of devices to be connected to the PCB without soldering. In SSL applications specifically, these contacts are used to bring power and signal onto the PCB or are used to daisy chain multiple boards together in a long string. While the IDC contact provides a gas-tight connection to conductor of the wire, the optional cap provides a positive strain relief even in the harshest conditions. In case of repair, the wires can be removed and replace up to three times.

The single 9176-400 series contact and cap accepts 22 AWG to 24 AWG wires with an insulation diameter ranging from 1.0mm to 1.5mm. These dual beam contacts support a 6 amp current rating with a large SMT solder base to provide maximum stability on the PCB. The optional locking strain relief cap acts as the termination tool for severe vibration applications.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application notes: refer to 201-01-124

FEATURES AND BENEFITS

- IDC contact is supplied in T&R pockets for standard SMT placement
- IDC contact provides a gas-tight connection to the PCB for long term reliability
- Optional termination cap provides additional strain relief for severe environments
- Tested to automotive levels on shock, vibration and temperature cycling for reliability
- Reduced total applied cost versus solder or crimp processes
- Individual contacts can be located anywhere on the PCB based on specific application

ELECTRICAL

- Current Rating: 6 Amps/Contact
- Voltage Rating: Dependant on component proximity

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Nylon 46: UL94V0
- Contact Material: Phosphor Bronze
- Plating: Tin over Nickel
- Durability: 3 Cycles

HOW TO ORDER – CONTACT OPTIONS

70

Prefix

70 = Contact

9176

Series

001

Number of Ways

| Code | No of Ways | Details |
|------|------------|---------|
| 001 | 1 | Page 17 |

4XX

Wire Gauge Size

| Code | Accepted Wire Gauge |
|------|---------------------|
| 422 | 22 Gauge Stranded |
| 432 | 24 Gauge Stranded |

006

Plating Option

06 = Pure Tin all over

HOW TO ORDER – CAP OPTIONS

60

Prefix

60 = Cap

9176

Series

001

Number of Ways

| Code | No of Ways | Details |
|------|------------|---------|
| 001 | 1 | Page 19 |

4XX

Wire Gauge Size

| Code | Wire Insulation |
|------|-----------------|
| 415 | Ø 1.0-1.5 |

X00

Insulator Color

| Code | Color | Application |
|------|-------|-------------|
| 000 | Black | Industrial |
| 100 | White | Lighting |




SSL - Discrete Wire IDC Contact & Cap



Series 9176-400


CONTACT DETAILS




NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
3. CONTACT PLATING: PURE TIN.
4. CONNECTOR DESIGNED TO ACCEPT BETWEEN 22 AND 24 GAUGE STRANDED WIRE. SEE TABLE.
5. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
6. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
7. SMT PCB LAYOUT, REFER TO PAGE 17.
8. PACKING IN TAPE AND REEL, QUANTITY 2000 PER REEL.
9. WHEN REQUIRED, MATCHING CAP DETAILS ON DRAWING 60-9176-001-4XX-X06S.
10. ASSEMBLY TOOLING ON PAGE 18 FOR WIRE INTO CONTACT.

PACKING DETAILS



| | |
|----------|-------|
| REEL QTY | 1000 |
| LEADER | 480MM |
| TRAILER | 120MM |





SSL - Discrete Wire IDC Contact & Cap **AVXX**

Series 9176-400

22-24 AWG IDC WIRE TO BOARD CONNECTOR SINGLE CONTACT



SMT PCB LAYOUT

PURE TIN PADS



ORIENTATION OF CONTACT ON PAD

ASSEMBLED/INSTALLED PRODUCTS




NOTES:

1. CONNECTOR CAN BE USED WITH CONTACT ONLY OR WITH OPTIONAL CAP.
2. OUTLINE OF CAP WHEN USED.
3. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
4. DIMENSIONS SHOWN ARE REFERENCED DIMENSIONS.
5. ASSEMBLY TOOLING FOR WIRE INTO CONTACT SEE PAGE 18.

SSL - Discrete Wire IDC Contact & Cap **AVX**

Series 9176-400

ASSEMBLY TOOLING – CAP NOT USED WIRE ONTO CONTACT




NOTES:

1. ASSEMBLY TOOLING FOR CONTACT ONLY, NO CAP USED.
2. MINIMUM AREA OF PCB TO BE KEPT CLEAR OF COMPONENTS, TACKS PERMISSIBLE.
3. REFER TO APPLICATION NOTE 201-01-124 FOR FURTHER INFORMATION.
4. INSERT CORRECT TOOL INTO HANDLE, MAGNETIC RETENTION .


METAL TOOL – HIGH VOLUME

06-9176-7021-01-000




PLASTIC TOOL – LOW/MEDIUM VOLUME

06-9176-7022-01-000



UNIVERSAL HANDLE


06 7000 7730 01 000



SSL - Discrete Wire IDC Contact & Cap **AVXX**

Series 9176-400

CAP DETAILS



NOTES:

1. CAP FOR IDC WIRE TO BOARD CONNECTION.
2. CAP MATERIAL: GLASS FILLED NYLON 46, COLOR SEE PAGE 15.
3. CAPS DESIGNED TO ACCOMMODATE WIRE INSULATION DIAMETERS 1.0MM TO 1.5MM.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106, APPLICATION NOTES 201-01-124.
6. PACKING IN BAGS, QUANTITY 2000 PER BAG.
7. FOR INSTALATION DETAILS REFER TO DRAWING 70-9176-001-4XX-006S.

SSL - Discrete Wire IDC Contact & Cap **AVX**

Series 9176-500



The 917X series of surface mount Insulation Displacement Connectors (IDC) were developed to meet the harsh automotive and industrial market applications for connecting individual wires directly to a PCB ranging from 14 AWG to 28 AWG. This industry proven contact system has been tested to automotive levels of shock, vibration, and temperature cycling to prove their reliability and robustness. This new single contact was developed as a standalone component to enhance the application uses with the IDC technology. The simplicity of inserting a wire into an SMT contact with a small tool or optional retention / termination cap allows a wide range of devices to be connected to the PCB without soldering. In SSL applications specifically, these contacts are used to bring power and signal onto the PCB or are used to daisy chain multiple boards together in a long string. While the IDC contact provides a gas-tight connection to conductor of the wire, the optional cap provides a positive strain relief even in the harshest conditions. In case of repair, the wires can be removed and replace up to three times.

The single 9176 series contact and cap accepts 18 AWG to 24 AWG wires with an insulation diameter ranging from 1.1mm to 2.1mm. These dual beam contacts support a 10 amp current rating with a large SMT solder base to provide maximum stability on the PCB. The optional locking strain relief cap acts as the termination tool for severe vibration applications.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application notes: refer to 201-01-124

FEATURES AND BENEFITS

- IDC contact is supplied in T&R pockets for standard SMT placement
- IDC contact provides a gas-tight connection to the PCB for long term reliability
- Optional termination cap provides additional strain relief for severe environments
- Tested to automotive levels on shock, vibration and temperature cycling for reliability
- Reduced total applied cost versus solder or crimp processes
- Individual contacts can be located anywhere on the PCB based on specific application

ELECTRICAL

- Current Rating: 10 Amps/Contact
- Voltage Rating: Dependant on component proximity

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Nylon 46: UL94V0
- Contact Material: Phosphor Bronze
- Plating: Tin over Nickel
- Durability: 3 Cycles

HOW TO ORDER – CONTACT OPTIONS

| 70 | 9176 | 001 | 5XX | 006 | | | | | | | | | | | | | | | | |
|---------------|---------------------|-------------------------------------------------------------------------------------------------------------------------|------------------------|---------------------------|---------|-----|---|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|---------------------|-----|-------------------|-----|-------------------|-----|-------------------|-----|-------------------|--|
| Prefix | Series | Number of Ways | Wire Gauge Size | Plating Option | | | | | | | | | | | | | | | | |
| 70 = Contact | | | | 06 = Pure Tin all over | | | | | | | | | | | | | | | | |
| | | <table><tr><th>Code</th><th>No of Ways</th><th>Details</th></tr><tr><td>001</td><td>1</td><td>Page 22</td></tr></table> | Code | No of Ways | Details | 001 | 1 | Page 22 | <table><tr><th>Code</th><th>Accepted Wire Gauge</th></tr><tr><td>501</td><td>18 Gauge Stranded</td></tr><tr><td>511</td><td>20 Gauge Stranded</td></tr><tr><td>522</td><td>22 Gauge Stranded</td></tr><tr><td>532</td><td>24 Gauge Stranded</td></tr></table> | Code | Accepted Wire Gauge | 501 | 18 Gauge Stranded | 511 | 20 Gauge Stranded | 522 | 22 Gauge Stranded | 532 | 24 Gauge Stranded | |
| Code | No of Ways | Details | | | | | | | | | | | | | | | | | | |
| 001 | 1 | Page 22 | | | | | | | | | | | | | | | | | | |
| Code | Accepted Wire Gauge | | | | | | | | | | | | | | | | | | | |
| 501 | 18 Gauge Stranded | | | | | | | | | | | | | | | | | | | |
| 511 | 20 Gauge Stranded | | | | | | | | | | | | | | | | | | | |
| 522 | 22 Gauge Stranded | | | | | | | | | | | | | | | | | | | |
| 532 | 24 Gauge Stranded | | | | | | | | | | | | | | | | | | | |

HOW TO ORDER – CAP OPTIONS




| 60 | 9176 | 001 | 5XX | X00 | | | | | | | | | | | | | | | | | | | | | |
|-----------|-----------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|---------|-----|---|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------|-----|-----------------|-----|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|-------------|---|-------|------------|---|-------|----------|
| Prefix | Series | Number of Ways | Wire Gauge Size | Insulator Color | | | | | | | | | | | | | | | | | | | | | |
| 60 = Cap | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><th>Code</th><th>No of Ways</th><th>Details</th></tr><tr><td>001</td><td>1</td><td>Page 24</td></tr></table> | Code | No of Ways | Details | 001 | 1 | Page 24 | <table><tr><th>Code</th><th>Wire Insulation (AWG)</th></tr><tr><td>516</td><td>1.1-1.6 (22-24)</td></tr><tr><td>521</td><td>1.6-2.1 (18-20)</td></tr></table> | Code | Wire Insulation (AWG) | 516 | 1.1-1.6 (22-24) | 521 | 1.6-2.1 (18-20) | <table><tr><th>Code</th><th>Color</th><th>Application</th></tr><tr><td>0</td><td>Black</td><td>Industrial</td></tr><tr><td>1</td><td>White</td><td>Lighting</td></tr></table> | Code | Color | Application | 0 | Black | Industrial | 1 | White | Lighting |
| Code | No of Ways | Details | | | | | | | | | | | | | | | | | | | | | | | |
| 001 | 1 | Page 24 | | | | | | | | | | | | | | | | | | | | | | | |
| Code | Wire Insulation (AWG) | | | | | | | | | | | | | | | | | | | | | | | | |
| 516 | 1.1-1.6 (22-24) | | | | | | | | | | | | | | | | | | | | | | | | |
| 521 | 1.6-2.1 (18-20) | | | | | | | | | | | | | | | | | | | | | | | | |
| Code | Color | Application | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | Black | Industrial | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | White | Lighting | | | | | | | | | | | | | | | | | | | | | | | |

SSL - Discrete Wire IDC Contact & Cap




Series 9176-500

CONTACT DETAILS




| Code | Accepted Wire Gauge | A |
|------|---------------------|------|
| 501 | 18 Gauge Stranded | 0.72 |
| 511 | 20 Gauge Stranded | 0.60 |
| 522 | 22 Gauge Stranded | 0.47 |
| 532 | 24 Gauge Stranded | 0.37 |

AREA AVAILABLE FOR
PICK & PLACE 2.00mm SQUARE




- NOTES:
1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
 2. CONTACT MATERIAL: PHOSPHORE BRONZE.
 3. CONTACT PLATING: PURE TIN.
 4. CONNECTOR DESIGNED TO ACCEPT BETWEEN 18 AND 24 GAUGE STRANDED WIRE. SEE TABLE.
 5. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
 6. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND APPLICATION NOTES 201-01-124.
 7. SMT PCB LAYOUT, REFER TO PAGE 22.
 8. PACKING IN TAPE AND REEL, QUANTITY 1000 PER REEL.
 9. WHEN REQUIRED, MATCHING CAP DETAILS ON DRAWING 60-9176-001-5XX-X00S.
 10. ASSEMBLY TOOLING ON PAGE 23 (WITH CAP AND WITHOUT CAP).

PACKING DETAILS



| | |
|----------|-------|
| REEL QTY | 1000 |
| LEADER | 480MM |
| TRAILER | 120MM |





SSL - Discrete Wire IDC Contact & Cap **AVXX**

Series 9176-500

18-24 AWG IDC WIRE TO BOARD CONNECTOR SINGLE CONTACT


SMT PCB LAYOUT

PURE TIN PADS



ORIENTATION OF CONTACT ON PAD

ASSEMBLED/INSTALLED PRODUCTS



NOTES:


1. CONNECTOR CAN BE USED WITH CONTACT ONLY OR WITH OPTIONAL CAP.
2. OUTLINE OF CAP WHEN USED.
3. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106 AND 201-01-124.
4. DIMENSIONS SHOWN ARE REFERENCED DIMENSIONS.
5. ASSEMBLY TOOLING ON PAGE 23 (WITH CAP AND WITHOUT CAP).

SSL - Discrete Wire IDC Contact & Cap




Series 9176-500

ASSEMBLY TOOLING – CAP USED




CAP APPLICATION TOOL

06-9176-7018-01-000



UNIVERSAL HANDLE


06 7000 7730 01 000



NOTES:


1. ASSEMBLY TOOLING FOR CAP.
2. AREA OF PCB TO BE KEPT CLEAR OF COMPONENTS, TACKS PERMISSIBLE.
3. WIRE AND CAP INSERTED IN ONE OPERATION.
4. REFER TO APPLICATION NOTE 201-01-124 FOR FURTHER INFORMATION.
5. REFER BELOW WHEN CONTACT USED WITHOUT CAP.

ASSEMBLY TOOLING – CAP NOT USED WIRE ONTO CONTACT




2.1 WIRE (18-20 AWG)

06-9176-7019-01-000
06-9176-7020-01-000




1.6 WIRE (22-24 AWG)

06-9176-7019-02-000
06-9176-7020-02-000



UNIVERSAL HANDLE

06 7000 7730 01 000



NOTES:

1. ASSEMBLY TOOLING FOR CONTACT ONLY, NO CAP USED.
2. MINIMUM AREA OF PCB TO BE KEPT CLEAR OF COMPONENTS, TRACK PERMISSIBLE.
3. REFER TO TABLE FOR CORRECT TOOL/WIRE COMBINATION.
4. REFER TO APPLICATION NOTE 201-01-124 FOR FURTHER INFORMATION.

| Wire Gauge | Wire Insulation ø | Metal Tool High Volume | Plastic Tool Small to Medium Volume | Handle |
|------------|-------------------|------------------------|-------------------------------------|---------------------|
| 22-24 AWG | 1.10 to 1.60 | 06-9176-7019-02-000 | 06-9176-7020-02-000 | 06-7000-7730-01-000 |
| 18-20 AWG | 1.60 to 2.10 | 06-9176-7019-01-000 | 06-9176-7020-01-000 | 06-9176-7730-01-000 |








SSL - Discrete Wire IDC Contact & Cap



Series 9176-500

CAP DETAILS




| Code | Insulator Diameter (AWG) | B | Text C |
|------|--------------------------|------|--------|
| 516 | 1.1 to 1.6 (22-24) | 1.00 | Ø 1.6 |
| 521 | 1.6 to 2.1 (18-20) | 1.50 | Ø 2.1 |

- NOTES:
1. CAP FOR IDC WIRE TO BOARD CONNECTION.
 2. CAP MATERIAL: GLASS FILLED NYLON 46, COLOR SEE PAGE 20.
 3. CAPS DESIGNED TO ACCOMMODATE WIRE INSULATION DIAMETERS 1.1MM TO 2.1MM.
 4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
 5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-106, APPLICATION NOTES 201-01-124.
 6. PACKING IN BAGS, QUANTITY 1000 PER BAG.
 7. FOR INSTALATION DETAILS REFER TO DRAWING 70-9176-001-XX-006S.

SSL - Discrete Wire IDC



Series 9177



The 917X series of surface mount Insulation Displacement Connectors (IDC) were developed to meet the harsh automotive and industrial market applications for connecting individual wires directly to a PCB ranging from 14 AWG to 28 AWG. This industry proven contact system has been tested to automotive levels of shock, vibration, and temperature cycling to prove their reliability and robustness. The simplicity of inserting a wire into the connector with a small tool allows a wide range of devices to be connected to the PCB without soldering. In SSL applications specifically, these connectors are used to bring power and signal onto the PCB or are used to daisy chain multiple boards together in a long string. While the IDC contact provides a gas-tight connection to conductor of the wire, the housing has been designed to grab the insulation of the wire to provide a positive strain relief even in the harshest conditions. In case of repair, the wires can be removed and replace up to three times.

The 9177 series accepts 14 AWG to 20 AWG wires with an insulation diameter ranging from 2.75mm to 4.25mm. These dual contact connectors support a 15 amp current rating with two large SMT solder tails per wire to provide maximum stability on the PCB. Available in 1p-3p configuration, these connectors can be end stackable for higher pin counts.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application Notes: refer to 201-01-124

FEATURES AND BENEFITS

- IDC contact provides a gas-tight connection to the PCB for long term reliability
- Connector housing captures the wire insulation for positive strain relief
- Tested to automotive levels on shock, vibration and temperature cycling for reliability
- Low and high volume assembly tools to match production volumes
- Reduced total applied cost versus solder or crimp processes
- High temperature insulator capable to 260°C reflow soldering processes

ELECTRICAL

- Current Rating: 15 Amp / Contact
- Voltage Rating: 600 VAC

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Nylon 46: UL94V0
- Contact Material: Phosphor Bronze
- Plating: Tin over Nickel
- Durability: 3 Cycles

HOW TO ORDER

| 00 | 9177 | 00X |
|--------|------------|----------------|
| Prefix | Series | Number of Ways |
| Code | No of Ways | Details |
| 001 | 1 | Page 26 |
| 002 | 2 | Page 27 |
| 003 | 3 | Page 28 |

00X

Wire Gauge Size

| Code | Accepted Wire Gauge | Wire Insulation |
|------|---------------------|-----------------|
| 001 | 14 AWG | Ø 4.25 |
| 012 | 16 AWG | Ø 3.50 |
| 022 | 18 AWG | Ø 3.50 |
| 033 | 20 AWG | Ø 2.75 |

X

T

Insulator Color


| Code | Color | Application |
|------|-------|-------------|
| 0 | Black | Industrial |
| 1 | White | Lighting |

| 06 |
|------------------------|
| Plating Option |
| 06 = Pure Tin all over |




Certification: UL File #E320991



14-20 AWG 1 WAY IDC CONNECTOR




- NOTES:
1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
 2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 25.
 3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 14 AND 20 GAUGE STRANDED WIRE.
 4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
 5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-109.
 6. FOR PCB SPACE RESTRICTED BY ASSEMBLY TOOLING REFER TO PAGE 29.



| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|------|
| 001 | 14 Gauge Stranded | 1.10 | Ø 4.25 max | 4.25 |
| 012 | 16 Gauge Stranded | 0.82 | Ø 3.50 max | 3.50 |
| 022 | 18 Gauge Stranded | 0.72 | Ø 3.50 max | 3.50 |
| 033 | 20 Gauge Stranded | 0.60 | Ø 2.75 max | 2.75 |



SMT PCB LAYOUT

PURE TIN PADS



PACKING DETAILS

| | |
|----------|-------|
| REEL QTY | 400 |
| LEADER | 500MM |
| TRAILER | 400MM |
| REEL/BOX | 4 |
| PACK QTY | 1600 |




SSL - Discrete Wire IDC





Series 9177

14-20 AWG 2 WAY IDC CONNECTOR




NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 25.
3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 14 AND 20 GAUGE STRANDED WIRE.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-109.
6. FOR PCB SPACE RESTRICTED BY ASSEMBLY TOOLING REFER TO PAGE 29.




| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|------|
| 001 | 14 Gauge Stranded | 1.10 | Ø 4.25 max | 4.25 |
| 012 | 16 Gauge Stranded | 0.82 | Ø 3.50 max | 3.50 |
| 022 | 18 Gauge Stranded | 0.72 | Ø 3.50 max | 3.50 |
| 033 | 20 Gauge Stranded | 0.60 | Ø 2.75 max | 2.75 |





SMT PCB LAYOUT

PURE TIN PADS



PACKING DETAILS

| | |
|----------|-------|
| REEL QTY | 400 |
| LEADER | 500MM |
| TRAILER | 400MM |
| REEL/BOX | 4 |
| PACK QTY | 1600 |




SSL - Discrete Wire IDC

Series 9177




14-20 AWG 3 WAY IDC CONNECTOR





NOTES:

1. CONNECTOR FOR IDC WIRE TO BOARD CONNECTION.
2. CONTACT MATERIAL: PHOSPHORE BRONZE.
INSULATION MATERIAL: HIGH TEMPERATURE NYLON 46.
COLOR REFER TO PAGE 25.
3. CONNECTOR DESIGNED TO ACCEPT BETWEEN 14 AND 20 GAUGE STRANDED WIRE.
4. ALL DIMENSIONS FOR REFERENCE UNLESS OTHERWISE STATED.
5. FOR FULL PRODUCT SPECIFICATION REFER TO ELCO SPEC 201-01-109.
6. FOR PCB SPACE RESTRICTED BY ASSEMBLY TOOLING REFER TO PAGE 29.




| Code | Accepted Wire Gauge | A | Wire Insulation | B |
|------|---------------------|------|-----------------|------|
| 001 | 14 Gauge Stranded | 1.10 | Ø 4.25 max | 4.25 |
| 012 | 16 Gauge Stranded | 0.82 | Ø 3.50 max | 3.50 |
| 022 | 18 Gauge Stranded | 0.72 | Ø 3.50 max | 3.50 |
| 033 | 20 Gauge Stranded | 0.60 | Ø 2.75 max | 2.75 |





SMT PCB LAYOUT

PURE TIN PADS




PACKING DETAILS

| | |
|----------|-------|
| REEL QTY | 400 |
| LEADER | 500MM |
| TRAILER | 400MM |
| REEL/BOX | 4 |
| PACK QTY | 1600 |




INSERTION TOOLING – REQUIRES HAND PRESS WITH FLAT ROCK PLATES


1 WAY



2 WAY



3 WAY



HIGH PRODUCTION Metal

| No. of Ways | Max Insulation Dia (AWG) | Tool Part Number |
|-------------|--------------------------|---------------------|
| 1 | 4.25 (14) | 06 9177 7017 01 001 |
| | 3.50 (16-18) | 06 9177 7017 03 001 |
| | 2.75 (20) | 06 9177 7017 03 001 |
| 2 | 4.25 (14) | 06 9177 7017 01 002 |
| | 3.50 (16-18) | 06 9177 7017 02 002 |
| | 2.75 (20) | 06 9177 7017 03 002 |
| 3 | 4.25 (14) | 06 9177 7017 01 003 |
| | 3.50 (16-18) | 06 9177 7017 02 003 |
| | 2.75 (20) | 06 9177 7017 03 003 |


MED PRODUCTION Plastic

| No. of Ways | Max Insulation Dia (AWG) | Tool Part Number |
|-------------|--------------------------|---------------------|
| 1 | 4.25 (14) | 06 9177 7016 01 001 |
| | 3.50 (16-18) | 06 9177 7016 02 001 |
| | 2.75 (20) | 06 9177 7016 03 001 |
| 2 | 4.25 (14) | 06 9177 7016 01 002 |
| | 3.50 (16-18) | 06 9177 7016 02 002 |
| | 2.75 (20) | 06 9177 7016 03 002 |
| 3 | 4.25 (14) | 06 9177 7016 01 003 |
| | 3.50 (16-18) | 06 9177 7016 02 003 |
| | 2.75 (20) | 06 9177 7016 03 003 |




The assembly tooling restricts the available space/component heights on the PCB.
For details see below.

- NOTES:
1. ALL DIMENSIONS FOR REFERENCE DIMENSIONS.
 2. MAXIMUM COMPONENT HEIGHT 0.80MM IN THIS AREA.
 3. MAXIMUM COMPONENT HEIGHT 11.00 MM IN THIS AREA.
 4. THE SAME RESTRICTIONS APPLY TO ALL WIRE INSULATION DIAMETERS.




INSERTION TOOLING – PCB RESTRICTED AREAS FOR ASSEMBLY TOOLING





1 WAY



2 WAY



3 WAY



Discrete Wire-to-Board; Poke-Home



Series 9276



The new 9276 series connector provides a quick and reliable wire-to-board termination in a sleek 2.5mm pitch SMT package for a broad range of industrial and commercial markets. With almost every product on the market today having to deal with a small number of discrete wires to connect components to a board, the 9276 series connectors meets this challenge by simply stripping the wire and inserting them into the connector. This makes the connector very termination friendly within the factory as well as in the field by electrical installers. Developed for harsh industrial and Solid State Lighting (SSL) applications, the connector was designed with a high spring force Beryllium Copper upper spring contact to accept a wide range (18-24 AWG solid or stranded) of wire to meet multiple applications with a single connector. By incorporating a dual-contact design we were able to maximize current rating (6 Amps) and minimize PCB space. For example, the 4p connector has a footprint of 90 sq-mm while competing products are 160 sq-mm. The dual-contact design also provides two solder points for each wire eliminating the need for external anchor tabs. AVX provides a small insertion / extraction tool which will allow the wires to easily be replaced up to 5 times.

APPLICATIONS

- Connecting discrete wire components directly to the PCB
- Bringing power and signals onto a PCB
- Daisy chaining PCB's together to create a continuous string of boards
- Application notes; refer to 201-01-127

FEATURES AND BENEFITS

- Simple strip, insert and removal design
- SMT RoHS termination to the PCB with minimal footprint
- Accepts 18-24AWG Solid and Stranded wires
- Expanded size offering to maximize application potential; 1, 2, 3, 4, 6 & 8 positions
- High spring force top contact provides a lance type retention to capture and retain the wire
- Available in standard white and optional black color

ELECTRICAL

- Current Rating: 6 Amps / Contact
- Voltage Rating: 250v AC

ENVIRONMENTAL

- Operating Temperature: -40°C to +125°C

MECHANICAL

- Insulator Material: Glass-Filled Nylon 46; UL94V0
- Contact Material: Beryllium Copper / Phosphor Bronze
- Plating: Tin over Nickel
- Replacibility: 5 Cycles

HOW TO ORDER

00

Wire to Board Connector

9276

Series

00X

Number of Ways

| Code | No of Ways | Details |
|------|------------|---------|
| 001 | 2 | Page 31 |
| 002 | 3 | Page 32 |
| 003 | 4 | Page 33 |
| 004 | 5 | Page 34 |
| 006 | 6 | Page 35 |
| 008 | 8 | Page 36 |

0

Horizontal Mounting

21

Wire Size

| Code | Wire Gauge | Max Conductor | Max Insulation |
|------|-------------|-----------------|-----------------|
| 21 | 18 - 24 AWG | 1.20mm Diameter | 2.10mm Diameter |

X

Insulator Color


| Code | Color | Application |
|------|-------|-------------|
| 0 | Black | Industrial |
| 1 | White | Lighting |

06


Plating Option

Tin all over

1 WAY WIRE TO BOARD CONNECTOR




SECTION ON A-A




NOTES:

1. 9276 ONE WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.




PACKING DETAILS






1 WAY PCB BOARD LAYOUT



2 WAY WIRE TO BOARD CONNECTOR



SECTION ON A-A




SECTION ON A-A WITH WIRE


NOTES:

1. 9276 TWO WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.


2 WAY PCB BOARD LAYOUT



PACKING DETAILS




3 WAY WIRE TO BOARD CONNECTOR




NOTES:

1. 9276 THREE WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.


3 WAY PCB BOARD LAYOUT



PACKING DETAILS




4 WAY WIRE TO BOARD CONNECTOR




NOTES:

1. 9276 FOUR WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.


4 WAY PCB BOARD LAYOUT




PACKING DETAILS



6 WAY WIRE TO BOARD CONNECTOR



SECTION ON A-A




SECTION ON A-A
WITH WIRE


NOTES:

1. 9276 SIX WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.


6 WAY PCB BOARD LAYOUT



PACKING DETAILS




8 WAY WIRE TO BOARD CONNECTOR




NOTES:

1. 9276 EIGHT WAY CONNECTOR, REFER TO ELCO SPECIFICATION 201-01-125 AND APPLICATION NOTES 201-01-127 FOR FURTHER DETAILS
2. INSULATOR MATERIAL: NYLON 46, GLASS FILLED, UL94 V-0, COLOR REFER TO PAGE 30.
3. CONTACT MATERIAL: COPPER ALLOY, 0.20MM THICK, TIN PLATED.
4. OUTLINE OF CONNECTOR.
5. WIRE ASSEMBLY / EXTRACTION, REFER TO PAGE 37.
6. FRONT FACE OF CONNECTOR CAN BE IN LINE WITH EDGE OF PCB.
7. PACKING TAPE AND REEL, QUANTITY 1000 PER REEL.

8 WAY PCB BOARD LAYOUT




PACKING DETAILS




WIRE ASSEMBLY


FOR FURTHER DETAILS REFER TO APPLICATION NOTES 201-01-127



TRIM INSULATION.
DO NOT CRUSH CENTER OF WIRE.
STRANDED WIRES TWISTED TOGETHER BEFORE INSETION.
CHECK ALL STANDS OF WIRE ARE CORRECTLY ALIGNED
ATER THE INSULATION IS REMOVED.




PUSH WIRE INTO HOLE IN FRONT OF CONNECTOR
DO NOT BEND CONNECTOR



CONTINUED TO PUSH WIRE UNTIL STOP IS REACHED.

WIRE EXTRACTION



PUSH BLADE (NOT SHARP) INTO SLOT ABOVE WIRE.
WHEN WIRE IS FREE, PULL TO EXTRACT.



GENERAL DESCRIPTION

The 9157 series was specifically designed for portable equipment.

AVX now offers this two-part system as a standard product. The fixed SMT socket is designed to be housed within the confined dimensional constraints of the portable device.

The plug/cover connector has sprung contacts and is designed for termination to accessory equipment. The connector is designed to house fifteen signal contacts on a 1mm pitch rated at 1.5A. There is the option to include a switching RF coax.

A cradle SMT plug connector for docking applications is also available as standard and has the option of including a SMT RF coax.

Whatever your requirements, the 9157 series can also be customized to suit your application.

APPLICATIONS

Suitable applications include:


- Mobile Phones
- PDA
- Medical
- Docking/Charging for any portable device

KEY FEATURES AND BENEFITS


- Patented 20° angled face on the socket gives self-cleaning face when mated with plug.
- Metal Latching area integral to socket which saves PCB real estate.
- Integral to socket is a mechanical 50Ω switching coax for SMT termination.
- Single sprung plug contact design gives ten thousand mating cycles and cleaning/wiping action.
- Customer has option to terminate own RF coax using AVX custom tooling: 06-9157-7116-01-000.
- SMT plug has unique location pyramids that give positive alignment to portable device, and assist blind mating.
- RoHS Compliant.




Plug Wire with Coax





Plug Wire without Coax




SMT Plug with Coax



SMT Plug without Coax




SUGGESTED PCB LAYOUT




SUGGESTED PCB LAYOUT



SMT Socket with Coax




SMT Socket without Coax



SMT PAD LAYOUT



Cover Kit



HOW TO ORDER

Plug Options – Example

| | | | | |
|--------------------------------------------|---------------|-------------------------------|-----------------------------------------------------------------|-------------------------------------------------------|
| <u>10</u> | <u>9157</u> | <u>015</u> | <u>000</u> | <u>006</u> |
| Prefix 10 = Plug 58 = Special | Series | No of Ways 15 = 015 | RF Coax Option 000 = No RF Coax 001 = With RF Coax | Contact Type 006 = Solder Wire 007 = SMT |

Socket Options – Example

| | | | | |
|----------------------------------------------|---------------|-------------------------------|-----------------------------------------------------------------|----------------------------------|
| <u>20</u> | <u>9157</u> | <u>015</u> | <u>000</u> | <u>006</u> |
| Prefix 20 = Socket 58 = Special | Series | No of Ways 15 = 015 | RF Coax Option 000 = No RF Coax 001 = With RF Coax | Contact Type 006 = SMT |

Cover Options – Example * Parts supplied in kit form

| | | | | |
|----------------------------------------------------|---------------|--------------------------------------------------------|-----------------|--------------------------------------------------------------------------------------------------------------------|
| <u>30</u> | <u>9157</u> | <u>9700</u> | <u>00</u> | <u>000</u> |
| Prefix 30 = Sub Assembly 58 = Special | Series | Cover Version 9700 = Screw/Press-fit Version | Standard | Grommet Variation 000 = No Grommet 035 = to suit $\phi 3.50$ cable 050 = to suit $\phi 5.00$ cable |

Patent: 2276285
5540599

Note: Application tooling to terminate coax cable 06-9157-7116-01-000.

9157 MOBO® 19 Way I/O Connector



GENERAL DESCRIPTION

Based on our standard 15 way 9157 I/O family, AVX has now released a family 19 way devices. This range includes a SMT 90 degree plug, a wire socket version that is used with the standard 9157 cover and a SMT socket for charging applications.

Options with the 90 degree SMT socket include the sealing of the connector contacts and the connector to the housing up to IP67. There is also an option to have an EMLB (early mate, late break) on pins 1 and 19.


To achieve the seal to the device housing, it may be necessary to customize the device housing design.

On the SMT 90 degree version, we also have the capability of an integrated DC jack, enabling both the DC jack and the 19 way cover to be plugged in at the same time.


AVAILABLE DEVICES:

| | |
|----------------------|---------------------------|
| 10 9157 019 000 006 | Plug wire version |
| 10 9157 019 000 007 | SMT charging version |
| 20 9157 019 000 006 | 90 degree SMT socket |
| 30 9157 97 XX 00 000 | Cover options see page 41 |

Cover Kit




PLUG 10-9157-019-XXX-006




9157 MOBO® 19 Way I/O Connector




Plug Wire




SMT Plug




SMT Socket



SMT Plug (Suggested PCB Layout)



SMT Socket (Suggested PCB Layout)





GENERAL DESCRIPTION

An I/O interconnect system designed for portable equipment.

AVX offers this plug and socket reduced size system as a standard product. The fixed SMT socket is designed to be mounted on a PCB and housed within a portable device. The plug is designed for cable termination with options of single and double sided contacts and customizing the overmold cover or parts can be supplied as connector only for sub contract termination. The socket connector houses 16 contacts in two rows on 1.25mm pitch with a rating of 1 amp per contact. Both connectors are RoHS compliant.

APPLICATIONS

Suitable applications include:

- Cellular Phones
- Handheld Devices
- Industrial Modules
- Medical Electronics

KEY FEATURES AND BENEFITS

- No latching is required due to the click design of the contacts.
- Optional customization of the overmold cover.
- Options of single row (8 way) or dual row (16 way) plug connector.
- Compact size to optimize PCB real estate.
- Metal outer cover provides integrated PCB location and solder tab.
- Positive alignment and orientation of the plug and socket.
- 5K mating cycles and 1 amp rated.





9257 Reduced Size I/O Connector




Single Sided 8 Way I/O Plug Connector

Dual Sided 16 Way I/O Plug Connector



Suggested Overmolding for Plug Connector



HOW TO ORDER

10
Prefix
10 = Plug Connector

9257
Series

016
No of Ways
016 = 16 way dual sided
008 = 8 way single sided

001
Contact
001 = Solder Bucket

003
Plating Option
003 = 0.8µm Selective Gold,
Tin Tail


Notes:
1. All dimensions are for reference only unless toleranced.
2. For full product specification refer to AVX spec 201-01-089.
3. Parts packed in tube with 50 parts per tube.




9257 Reduced Size I/O Connector



16 Position I/O Socket



PCB Layout




HOW TO ORDER

| | | | | | |
|-----------------------|---------------|-------------------|-----------------------|----------------------------------------|------------------------------------|
| 20 | 9257 | 016 | 001 | 01 | 3 |
| Prefix | Series | No of Ways | Contacts | Solder Bracket | Plating Option |
| 20 = Socket Connector | | 16 = 016 | 001 = SMT Termination | 01 = Solder Bracket with location pegs | 3 = 0.8µm Selective Gold, Tin Tail |

| Packing Details | |
|-----------------|------|
| Reel Qty. | 1100 |
| Pack Qty. | 5500 |

- Notes:
1. 16 Way I/O Socket.
 2. For full product specification refer to AVX spec 201-01-089.
 3. General tolerance ± 0.20 (0.008) unless otherwise stated.
 4. SMT feet within 0.13 (0.005) coplanarity.





GENERAL DESCRIPTION

AVX offers the 12 way mini I/O connector as a standard product. The fixed SMT socket is designed to be mounted on a PCB and housed within a portable device. The plug is designed for cable termination with options of single and double sided contacts. Parts can be supplied as connectors only for sub contract termination, or with a custom overmold cover. The socket connector houses 12 contacts in a single row on 0.50mm pitch.


APPLICATIONS

- Medical Electronics
- Cellular Phones
- Industrial Modules
- Hand Held Devices

KEY FEATURES AND BENEFITS

- No latching required due to the click design of the contacts.
- Optional customization of the overmold cover.
- Compact size to optimize PCB real estate.
- Metal outer cover provides integrated PCB location and solder tab.
- Positive alignment and orientation of the plug and socket.


9257 STANDARD 12 WAY MINI I/O PLUG



HOW TO ORDER


| | | | | |
|---------------------|---------------|-------------------|-------------------|-------------------------------|
| 10 | 9257 | 012 | 101 | 006 |
| Prefix | Series | No of Ways | Contacts | Plating Option |
| 10 = Plug Connector | | 12 = 012 | 101 = Solder Tail | 006 = 0.25µm Gold over Nickel |

SUGGESTED OVERMOLDING FOR PLUG CONNECTOR



DIMENSION MARKED WITH A * ARE
VARIABLE DIMENSION TO SUIT
CUSTOMER DESIGN AND APPLICATION

9257 STANDARD 12 WAY MINI I/O SOCKET



HOW TO ORDER

20

Prefix
20 = Socket Connector

9257

Series

012

No of Ways
12 = 012

101

Contacts
101 = SMT Termination

01

Solder Bracket
01 = Solder Bracket with location pegs

6

Plating Option
6 = 0.25µm Gold over Nickel

AMERICAS

AVX Myrtle Beach, SC
Tel: 843-448-9411

AVX Northwest, WA
Tel: 360-699-8746

AVX Midwest, IN
Tel: 317-861-9184

AVX Mid/Pacific, CA
Tel: 408-988-4900

AVX Northeast, MA
Tel: 617-479-0345

AVX Southwest, CA
Tel: 949-859-9509

AVX Canada
Tel: 905-238-3151

AVX South America
Tel: +55-11-4688-1960

EUROPE

AVX Limited, England
Tel: +44-1252-770000

AVX S.A.S., France
Tel: +33-1-69-18-46-00

AVX GmbH, Germany
Tel: +49-8131-9004-0

AVX SRL, Italy
Tel: +39-02-614-571

AVX Czech Republic
Tel: +420-57-57-57-521

AVX/ELCO UK
Tel: +44-1638-675000

ELCO Europe GmbH
Tel: +49-2741-299-0

AVX S.A., Spain
Tel: +34-91-63-97-197

AVX Benelux
Tel: +31-187-489-337

ASIA-PACIFIC

**AVX/Kyocera (S) Pte Ltd.,
Singapore**
Tel: +65-6286-7555

**AVX/Kyocera, Asia, Ltd.,
Hong Kong**
Tel: +852-2363-3303

**AVX/Kyocera Yuhan Hoesa,
South Korea**
Tel: +82-2785-6504

**AVX/Kyocera HK Ltd.,
Taiwan**
Tel: +886-2-2656-0258

**AVX/Kyocera (M) Sdn Bhd,
Malaysia**
Tel: +60-4228-1190

**AVX/Kyocera International
Trading Co. Ltd.,
Shanghai**
Tel: +86-21-3255 1933

**AVX/Kyocera Asia Ltd.,
Shenzen**
Tel: +86-755-3336-0615

**AVX/Kyocera International
Trading Co. Ltd.,
Beijing**
Tel: +86-10-6588-3528

**AVX/Kyocera India
Liaison Office**
Tel: +91-80-6450-0715

ASIA-KED

(KYOCERA Electronic Devices)

KED Hong Kong Ltd.
Tel: +852-2305-1080/1223

**KED Hong Kong Ltd.
Shenzen**
Tel: +86-755-3398-9600

**KED Company Ltd.
Shanghai**
Tel: +86-21-3255-1833

**KED Hong Kong Ltd.
Beijing**
Tel: +86-10-5869-4655

KED Taiwan Ltd.
Tel: +886-2-2950-0268

**KED Korea Yuhan Hoesa,
South Korea**
Tel: +82-2-783-3604/6126

**KED (S) Pte Ltd.
Singapore**
Tel: +65-6509-0328

**Kyocera Corporation
Japan**
Tel: +81-75-604-3449

Contact:



<http://www.avx.com>

S-IWTB0M1010-N