



NC3MD-S-1-B

3 pole male receptacle, D-size metal body, screw terminals accommodating wire range 0.14mm² to 0.5mm² (AWG 26 -20), black metal housing, gold contacts, UL recognized component

Features & Benefits

- Robust "D" metal shell
- Standardized D sized 24 mm panel cutout
- Screw terminals

ACCESSORIES





DL Series

Audio

NC3MD-S-1-B

There are no technical infos for this product.

Product

Connector Type	XLR
Gender	male

Electrical

Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 5 m Ω
Dielectric strength	1,5 kVdc
Insulation resistance	> 2 G Ω (initial)
Insulation resistance	> 1 G Ω (after damp heat test)
Rated current per contact	3 A
Rated voltage	50 V

Mechanical

Insertion force	< 30 N
Withdrawal force	> 10 N
Lifetime	> 1000 mating cycles
Wire size	0.14 mm ² bis 0.5 mm ²
Wire size	26 AWG - 20 AWG
Wiring	Screw terminals
Locking device	latch lock
Mounting direction	front
Chassis shape	D

Material

Environmental

Standard compliance	IEC 61076-2-103
---------------------	-----------------

Optical

Mobile Cables