www.schurter.com/pg07







### Description

- Panel Mount Screw-on from front side

- Outlet shuttered, Protection class I, Pin temperature 70 °C
- Solder terminals or quick connect terminals

## **Technical Data**

10A / 250 VAC; Hz 50
15 A / 250 VAC; 60 Hz
> 2 kVAC between L-N > 2 kVAC between L/N-PE
(1 min/50 Hz)
-25 °C to 70 °C
from front side IP 30 acc. to IEC 60529
Suitable for appliances with protection class I acc. to IEC 61140
Solder terminals or quick connect ter- minals
Screw-on: max 8mm Mounting screw torque max 0.5Nm
Thermoplastic, black, UL 94V-0
-


Length


# Dimensions

4721



49 mm





Shutter operation: shutters opened by plug insertion


Shutter operation: shutters closed when plug is removed

- E: Solder terminals 3.5 x 0.8 mm: 28.4 mm
- E: Quick connect terminals 4.8 x 0.8 mm: 31.1 mm
- E: Quick connect terminalse 6.3 x 0.8 mm: 33.2 mm

Distributor-Stock-Check | SCHURTER-Stock-Check | e-Store







- For protection class II

Weblinks

RoHS

Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check

Appliance-Inlet /-Outlet	F acc. to IEC/EN 60320-2-2,
	UL 498, CSA C22.2 no. 42 (for cold
	condition) pin-temperature 70 °C, 10A,
	Protection class I

Connectors



Variants

# www.schurter.com/pg07

Distributor-Stock-Check	SCHURTER-Stock-Check	e-Store
-------------------------	----------------------	---------

	Туре	Panel mounting	Panel Thickness s [mm]	Terminal	Order Number			
	4721	Screw-on	-	Quick connect terminals 4.8 x 0.8 mm	4721.0100			
	4721	Screw-on	-	Quick connect terminals 6.3 x 0.8 mm	4721.0000			
	4721	Screw-on	-	Solder terminals 3.8 x 0.8 mm	4721.0300			
_								

Class II product also available on request

Cord retaining clamps and insulation covers see accessories

Packaging unit 100 Pcs

# Accessory

Description





Cord retaining kits Cord retainning strain reliefe