

Honeywell Sensing and Control



Where to buy ?

- [Interactive Catalog Home](#)
- [Product Family Information](#)
- [Specification Search](#)
- [Search Help](#)



Representative photograph, actual product appearance may vary.

- [Dimensions](#)
- [Schematic](#)
- [Performance Charts](#)
- [Specifications](#)

Click here for a print friendly version of this datasheet.

SDP8105-001

SDP Series Silicon PhotoDarlington, T-1 Plastic Package

Features

- T-1 plastic package
- 20 ° (nominal) acceptance angle
- Consistent optical properties
- Mechanically and spectrally matched to SEP8505 and SEP8705 infrared emitting diodes

Description

The SDP8105 is an NPN silicon photodarlington transfer molded in a T-1 black plastic package to minimize effect of visible ambient light. Transfer molding of this device assures superior optical centerline performance compared to other molding processes. Lead lengths are staggered to provide a simple method of polarity identification.

Product Specifications	
Product Type	IR Component
Angular Response (Degree)	20
Light Current Minimum	0.5 mA
Package Style	T1
Package Components	Plastic
Package Color	Black
Rise and Fall Time	75 μs
Power Dissipation	70 mW
Operating Temperature Range	-40 °C to 85 °C [-40 °F to 185 °F]
Dark Current	250 nA
Collector-Emitter Breakdown Voltage	15 V
Emitter-Collector Breakdown Voltage	5 V
Collector-Emitter Saturation Voltage	1.1 V
Comment	The radiation source is a IRED with a peak wavelength of 935 nm.
Availability	Global
Product Name	Photodarlington

Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.