

Audio





Home

About Us

Products

Support News

Sitemap

Search

Products only

© Neutrik® AG All rights reserved Legal Notices




Print

NYS221



Jack with special designed head for guitar strap, for thick panels, 3-pole, long-threaded bushing with washer and nut, full metal



Frontplattenausschnitt Panel cut out



					Werkstoff:	Massstab:		Datum	Name
				*)Lieferant darf ohne Ruecksprache nicht		1:1	Gezeichnet	29.01.01	Battlogg
				geaendert werden		1'1	Geprueft		
				Zeichnung urheberrechtlich geschuetzt (DIN 34) (C)			Gesehen		
				Benennung: 1/4" Phone Jacks			Ersetzt durch:		Blatt
				NYS 221		Ersatz fuer:		von Blatt	
							Zeichn. Nr.	100 07	22 22
Ind.	Aenderung	Datum	Name	Zeichn. Nr. 3102 ST 22 23					





NYS Jacks

NYS221

There are no technical infos for this product.

There are no teermoor into	Tor this product.						
Product							
Electrical							
Contact resistance	$<$ 10 m Ω						
Dielectric strength	0,5 kVdc						
Rated current per contact	1 A						
Mechanical							
Cable O.D.	≤ 6 mm						
Insertion force	≤ 20 N						
Withdrawal force	> 10 N						
Lifetime	5000 mating cycles						
Panel thickness	26 mm						
Wire size	24 AWG						
Material							
Contact plating	SnCe						
Contacts	CuSn6						
Insert	PA 6+insulation board						
Shell	CuZn39Pb3 gal 2 ?m Ni plated						
Environmental							
Solderability	Complies with IEC 68-2-20						
Temperature range	-20 °C to +70 °C						
Optical							
Mobile Cables							