

# RAD-OUT-8D-REL

Order No.: 2867157




Digital extension module with 8 digital outputs



Commercial data	
EAN	4017918929657
Pack	1 pcs.
Customs tariff	85371099
Weight/Piece	0.2009 KG
Catalog page information	Page 251 (NTK-2008)

Product notes

WEEE/RoHS-compliant since:



Technical data	
<b>Digital output</b>	
Output name	Relay output
Number of outputs	8

Maximum switching voltage	30 V AC/DC (EC Declaration of Conformity)
	30 V DC (With UL approval)
	250 V AC (With UL approval)
Limiting continuous current	0.5 A (EC Declaration of Conformity)

**Supply**

Range of supply voltages	9 V DC ... 30 V DC (via bus foot)
Typical current consumption	100 mA
Max. current consumption	160 mA

**General data**

Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Degree of protection	IP20
Mounting position	Any
Assembly instructions	on TS 35 profile rail acc. to EN 60715
Housing material	Polyamide PA non-reinforced
Length	99 mm
Width	22.5 mm
Height	114.5 mm
Conformity	CE compliant
ATEX approval	Ex II 3 G Ex nAC IIC T5 X
IECEX approval	Ex nL IIC T5
UL, USA / Canada	Class I, Div. 2, Groups A, B, C, D

**Connection data**

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M3

Certificates / Approvals



Certification Ex:

CUL-EX LIS, IECEx, UL-EX LIS

Drawings

Block diagram

