


THIS DRAWING IS UNCLASSIFIED KOPPIERUNG: KEINERLEI ZUSÄTZLICHE BEZEICHNUNG	DEFERRED FOR PUBLICATION FRÜHERER BEFRAGUNGSPUNKT	DATE: 2000	DATE: 2000
BY AMP INCORPORATED, ALL RIGHTS RESERVED © COPYRIGHT 2000			

REV. NO.	DATE	BY	APP'D
1			
2			




ORDER NO. / BESTELL-NR.	INSULATION # / ISOLATIONS-NR.	COLOR / FARBE
964972-1	1.9-2.1	YELLOW / GELB
963530-1	1.4-1.9	GREY / GRAU
964971-1	1.2-1.6	RED / ROT

REV.	ORDER NO. / BESTELL-NR.	WIRE RANGE / Drahtgrößenbereich [mm²]	INSULATION # / Isolations-# [mm]	MATERIAL / Werkstoff	SURFACE / Oberfläche	LENGTH / Länge	WIRE CRIMP / Drahterimp	INSUL. CRIMP / Iso'erimp
A	4-1241732-1	B	4-1241733-1	CuNiSi	△	A = 3.0 B = 4.4 C = 6.4	E = 2.5 G = 2.7 D _w = 1.2	H = 4.3 K = 4.8 D _w = 2.7 Form C
	1241732-2	B	1241733-2	CuFe 2	△			
A	4-1241730-1	B	4-1241731-1	CuNiSi	△	A = 2.5 B = 4.4 C = 6.4	E = 2.1 G = 2.1 D _w = 0.8	H = 4.3 K = 4.8 D _w = 2.6 Form C
	1241730-2	B	1241731-2	CuFe 2	△			
A2	4-1241860-1	A	4-1241861-1	CuNiSi	△	A = 3.0 B = 4.4 C = 6.4	E = 2.5 G = 2.7 D _w = 1.2	H = 3.2 K = 3.4 D _w = 1.8 Form A
	1241860-7	A	1241861-7	CuNi12Zn24	Blank			
	1241860-2	A	1241861-2	CuFe 2	△			
A	4-1241858-1	A	4-1241859-1	CuNiSi	△	A = 2.5 B = 4.4 C = 6.4	E = 2.1 G = 2.1 D _w = 0.8	H = 2.9 K = 2.9 D _w = 1.4 Form A
	1241858-2	A	1241859-2	CuFe 2	△			
A	968052-1	A	968053-1	CuFe 2	△	A = 3.0 B = 4.6 C = 7	E = 2.5 G = 2.7 D _w = 1.2	H = 3.2 K = 3.4 D _w = 1.8 Form A
B	969022-1	A	969023-1	CuFe 2	△	A = 3.0 B = 4.6 C = 7	E = 2.5 G = 2.7 D _w = 1.2	H = 3.2 K = 3.4 D _w = 1.8 Form A
B	965914-2	A	965915-2	CuFe 2	△	A = 2.5 B = 4.6 C = 7	E = 2.1 G = 2.1 D _w = 0.8	H = 2.9 K = 2.9 D _w = 1.4 Form A
	965914-1	A	965915-1	CuFe 2	△			

FLR - CABLE / LEITUNG

NOTES / Bemerkungen

- △ BODY ELECTRO TIN PLATED OVER NICKEL 0.2 µm min.
Kontaktkörper galv. verzinkt über Nickel
- △ CONTACT AREA SELECTIV GOLD OVER NICKEL 0.8 µm min.
Kontaktzone selektiv vergoldet über Ni
- △ WIRE CRIMP AREA ELECTRO TIN PLATED OVER NICKEL 1 µm min.
Drahterimpbereich galv. verzinkt über Ni
- △ ACCORDING INSULATION # IS TO CHOOSE THE SINGLE WIRE SEAL
Entsprechend dem Isolationsdurchmesser ist die Einzel-Dichtung auszuwählen
- △ VARIANTS WITH GAP-SIZE 0.2mm
Vorlängen mit Gap-Size 0.2mm
- △ VARIANTS WITH GAP-SIZE 0.35mm
Vorlängen mit Gap-Size 0.35mm
- △ BODY ELECTRO TIN PLATED OVER NICKEL 0.2 µm min.
Kontaktkörper galv. verzinkt über Nickel
- △ CONTACT AREA SELECTIV GOLD OVER NICKEL 0.8 µm min.
Kontaktzone selektiv vergoldet über Ni
- △ WIRE CRIMP AREA ELECTRO TIN PLATED 1 µm min.
Drahterimpbereich galv. verzinkt



<p>AMP 1471-B REV 27JAN88</p> <p>13.36.13</p>	<p>12-NOV-01</p> <p>12-NOV-01</p> <p>16-NOV-01</p> <p>14-18081</p>	<p>AMP</p> <p>tyco Electronics AMP GmbH</p> <p>D - 64625 Bensheim</p>	<p>PRODUCT GROUP DRAWING FOR</p> <p>MICRO TIMER 3 CONTACT</p>	<p>RESTRICTED TO</p> <p>ALL FILES</p>
<p>DATE: 12-NOV-01</p> <p>BY: [Signature]</p> <p>APP'D: [Signature]</p>	<p>DATE: 12-NOV-01</p> <p>BY: [Signature]</p> <p>APP'D: [Signature]</p>	<p>DATE: 12-NOV-01</p> <p>BY: [Signature]</p> <p>APP'D: [Signature]</p>	<p>DATE: 12-NOV-01</p> <p>BY: [Signature]</p> <p>APP'D: [Signature]</p>	<p>DATE: 12-NOV-01</p> <p>BY: [Signature]</p> <p>APP'D: [Signature]</p>