


- Designed for Complementary Use with TIP100, TIP101 and TIP102
- 80 W at 25°C Case Temperature
- 8 A Continuous Collector Current
- Maximum  $V_{CE(sat)}$  of 2.5 V at  $I_C = 8$  A



Pin 2 is in electrical contact with the mounting base.

MDTRACA

### absolute maximum ratings at 25°C case temperature (unless otherwise noted)

RATING		SYMBOL	VALUE	UNIT
Collector-base voltage ( $I_E = 0$ )	TIP105	$V_{CBO}$	-60	V
	TIP106		-80	
	TIP107		-100	
Collector-emitter voltage ( $I_B = 0$ )	TIP105	$V_{CEO}$	-60	V
	TIP106		-80	
	TIP107		-100	
Emitter-base voltage		$V_{EBO}$	-5	V
Continuous collector current		$I_C$	-8	A
Peak collector current (see Note 1)		$I_{CM}$	-15	A
Continuous base current		$I_B$	-1	A
Continuous device dissipation at (or below) 25°C case temperature (see Note 2)		$P_{tot}$	80	W
Continuous device dissipation at (or below) 25°C free air temperature (see Note 3)		$P_{tot}$	2	W
Unclamped inductive load energy (see Note 4)		$\frac{1}{2}L_{IC}^2$	10	mJ
Operating junction temperature range		$T_j$	-65 to +150	°C
Storage temperature range		$T_{stg}$	-65 to +150	°C
Lead temperature 3.2 mm from case for 10 seconds		$T_L$	260	°C

NOTES: 1. This value applies for  $t_p \leq 0.3$  ms, duty cycle  $\leq 10\%$ .

2. Derate linearly to 150°C case temperature at the rate of 0.64 W/°C.

3. Derate linearly to 150°C free air temperature at the rate of 16 mW/°C.

4. This rating is based on the capability of the transistor to operate safely in a circuit of:  $L = 20$  mH,  $I_{B(on)} = -5$  mA,  $R_{BE} = 100$  Ω,  $V_{BE(off)} = 0$ ,  $R_S = 0.1$  Ω,  $V_{CC} = -20$  V.

### PRODUCT INFORMATION

AUGUST 1978 - REVISED SEPTEMBER 2002  
Specifications are subject to change without notice.

**electrical characteristics at 25°C case temperature**

PARAMETER	TEST CONDITIONS			MIN	TYP	MAX	UNIT
$V_{(BR)CEO}$ Collector-emitter breakdown voltage	$I_C = -30 \text{ mA}$ (see Note 5)	$I_B = 0$	TIP105 TIP106 TIP107	-60 -80 -100			V
$I_{CEO}$ Collector-emitter cut-off current	$V_{CE} = -30 \text{ V}$ $V_{CE} = -40 \text{ V}$ $V_{CE} = -50 \text{ V}$	$I_B = 0$	TIP105 TIP106 TIP107			-50 -50 -50	$\mu\text{A}$
$I_{CBO}$ Collector cut-off current	$V_{CB} = -60 \text{ V}$ $V_{CB} = -80 \text{ V}$ $V_{CB} = -100 \text{ V}$	$I_E = 0$	TIP105 TIP106 TIP107			-50 -50 -50	$\mu\text{A}$
$I_{EBO}$ Emitter cut-off current	$V_{EB} = -5 \text{ V}$	$I_C = 0$				-8	mA
$h_{FE}$ Forward current transfer ratio	$V_{CE} = -4 \text{ V}$ $V_{CE} = -4 \text{ V}$	$I_C = -3 \text{ A}$ $I_C = -8 \text{ A}$	(see Notes 5 and 6)	1000 200		20000	
$V_{CE(\text{sat})}$ Collector-emitter saturation voltage	$I_B = -6 \text{ mA}$ $I_B = -80 \text{ mA}$	$I_C = -3 \text{ A}$ $I_C = -8 \text{ A}$	(see Notes 5 and 6)			-2 -2.5	V
$V_{BE}$ Base-emitter voltage	$V_{CE} = -4 \text{ V}$	$I_C = -8 \text{ A}$	(see Notes 5 and 6)			-2.8	V
$V_{EC}$ Parallel diode forward voltage	$I_E = -8 \text{ A}$	$I_B = 0$	(see Notes 5 and 6)			-3.5	V

NOTES: 5. These parameters must be measured using pulse techniques,  $t_p = 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ .

6. These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

**thermal characteristics**

PARAMETER	MIN	TYP	MAX	UNIT
$R_{\theta JC}$ Junction to case thermal resistance			1.56	$^{\circ}\text{C}/\text{W}$
$R_{\theta JA}$ Junction to free air thermal resistance			62.5	$^{\circ}\text{C}/\text{W}$
$C_{\theta C}$ Thermal capacitance of case	0.9			J/ $^{\circ}\text{C}$

**resistive-load-switching characteristics at 25°C case temperature**

PARAMETER	TEST CONDITIONS <sup>†</sup>	MIN	TYP	MAX	UNIT
$t_d$ Delay time	$I_C = -8 \text{ A}$ $I_{B(on)} = -80 \text{ mA}$ $I_{B(off)} = 80 \text{ mA}$ $V_{BE(off)} = 5 \text{ V}$ $R_L = 5 \Omega$ $t_p = 20 \mu\text{s}$ , dc $\leq 2\%$		35		ns
$t_r$ Rise time			300		ns
$t_s$ Storage time			900		ns
$t_f$ Fall time			1.3		$\mu\text{s}$

<sup>†</sup> Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.

**PRODUCT INFORMATION**

## TYPICAL CHARACTERISTICS




Figure 1.




Figure 2.




Figure 3.

**PRODUCT INFORMATION**

AUGUST 1978 - REVISED SEPTEMBER 2002  
Specifications are subject to change without notice.

### MAXIMUM SAFE OPERATING REGIONS




Figure 4.

### THERMAL INFORMATION




Figure 5.

### PRODUCT INFORMATION