

# TIP29, A, B, C (NPN), TIP30, A, B, C (PNP)

## Complementary Silicon Plastic Power Transistors

Designed for use in general purpose amplifier and switching applications. Compact TO-220 AB package.


### Features

- Pb-Free Packages are Available\*



**ON Semiconductor®**

**1 AMPERE  
POWER TRANSISTORS  
COMPLEMENTARY SILICON  
40, 60, 80, 100 VOLTS,  
80 WATTS**



**TO-220AB  
CASE 221A  
STYLE 1**

### MARKING DIAGRAM



TIPxxx = Device Code:  
29, 29A, 29B, 29C  
30, 30A, 30B, 30C  
A = Assembly Location  
Y = Year  
WW = Work Week  
G = Pb-Free Package

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## TIP29, A, B, C (NPN), TIP30, A, B, C (PNP)

### MAXIMUM RATINGS

| Rating   | Symbol         | TIP29<br>TIP30 | TIP29A<br>TIP30A | TIP29B<br>TIP30B | TIP29C<br>TIP30C | Unit                     |
|--|----------------|----------------|------------------|------------------|------------------|--------------------------|
| Collector - Emitter Voltage  | $V_{CEO}$      | 40             | 60               | 80               | 100              | Vdc                      |
| Collector - Base Voltage   | $V_{CB}$       | 40             | 60               | 80               | 100              | Vdc                      |
| Emitter - Base Voltage   | $V_{EB}$       | 5.0            |                  |                  |                  | Vdc                      |
| Collector Current - Continuous<br>- Peak   | $I_C$          | 1.0<br>3.0     |                  |                  |                  | Adc                      |
| Base Current   | $I_B$          | 0.4            |                  |                  |                  | Adc                      |
| Total Power Dissipation<br>@ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 30<br>0.24     |                  |                  |                  | W<br>W/ $^\circ\text{C}$ |
| Total Power Dissipation<br>@ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 2.0<br>0.016   |                  |                  |                  | W<br>W/ $^\circ\text{C}$ |
| Unclamped Inductive Load Energy (Note 1)   | E              | 32             |                  |                  |                  | mJ                       |
| Operating and Storage Junction Temperature Range   | $T_J, T_{stg}$ | -65 to +150    |                  |                  |                  | $^\circ\text{C}$         |

### THERMAL CHARACTERISTICS

| Characteristic                          | Symbol          | Max   | Unit                      |
|---|-----------------|-------|---------------------------|
| Thermal Resistance, Junction-to-Ambient | $R_{\theta JA}$ | 62.5  | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance, Junction-to-Case    | $R_{\theta JC}$ | 4.167 | $^\circ\text{C}/\text{W}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. This rating based on testing with  $L_C = 20$  mH,  $R_{BE} = 100$   $\Omega$ ,  $V_{CC} = 10$  V,  $I_C = 1.8$  A, P.R.F = 10 Hz

### ORDERING INFORMATION

| Device  | Package             | Shipping        |
|---------|---------------------|-----------------|
| TIP29   | TO-220              | 50 Units / Rail |
| TIP29G  | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP29A  | TO-220              | 50 Units / Rail |
| TIP29AG | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP29B  | TO-220              | 50 Units / Rail |
| TIP29BG | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP29C  | TO-220              | 50 Units / Rail |
| TIP29CG | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP30   | TO-220              | 50 Units / Rail |
| TIP30G  | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP30A  | TO-220              | 50 Units / Rail |
| TIP30AG | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP30B  | TO-220              | 50 Units / Rail |
| TIP30BG | TO-220<br>(Pb-Free) | 50 Units / Rail |
| TIP30C  | TO-220              | 50 Units / Rail |
| TIP30CG | TO-220<br>(Pb-Free) | 50 Units / Rail |

## TIP29, A, B, C (NPN), TIP30, A, B, C (PNP)

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic  | Symbol         | Min                   | Max                      | Unit            |
|---|----------------|-----------------------|--------------------------|-----------------|
| <b>OFF CHARACTERISTICS</b>  |                |                       |                          |                 |
| Collector-Emitter Sustaining Voltage ( $I_C = 30\text{ mAdc}$ , $I_B = 0$ ) (Note 2)<br>TIP29, TIP30<br>TIP29A, TIP30A<br>TIP29B, TIP30B<br>TIP29C, TIP30C  | $V_{CEO(sus)}$ | 40<br>60<br>80<br>100 | -<br>-<br>-<br>-         | Vdc             |
| Collector Cutoff Current<br>( $V_{CE} = 30\text{ Vdc}$ , $I_B = 0$ )<br>( $V_{CE} = 60\text{ Vdc}$ , $I_B = 0$ )<br>TIP29, TIP29A, TIP30, TIP30A<br>TIP29B, TIP29C, TIP30B, TIP30C  | $I_{CEO}$      | -<br>-                | 0.3<br>0.3               | mAdc            |
| Collector Cutoff Current<br>( $V_{CE} = 40\text{ Vdc}$ , $V_{EB} = 0$ )<br>( $V_{CE} = 60\text{ Vdc}$ , $V_{EB} = 0$ )<br>( $V_{CE} = 80\text{ Vdc}$ , $V_{EB} = 0$ )<br>( $V_{CE} = 100\text{ Vdc}$ , $V_{EB} = 0$ )<br>TIP29, TIP30<br>TIP29A, TIP30A<br>TIP29B, TIP30B<br>TIP29C, TIP30C | $I_{CES}$      | -<br>-<br>-<br>-      | 200<br>200<br>200<br>200 | $\mu\text{Adc}$ |
| Emitter Cutoff Current ( $V_{BE} = 5.0\text{ Vdc}$ , $I_C = 0$ )  | $I_{EBO}$      | -                     | 1.0                      | mAdc            |
| <b>ON CHARACTERISTICS (Note 2)</b>  |                |                       |                          |                 |
| DC Current Gain ( $I_C = 0.2\text{ Adc}$ , $V_{CE} = 4.0\text{ Vdc}$ )<br>( $I_C = 1.0\text{ Adc}$ , $V_{CE} = 4.0\text{ Vdc}$ )  | $h_{FE}$       | 40<br>15              | -<br>75                  | -               |
| Collector-Emitter Saturation Voltage ( $I_C = 1.0\text{ Adc}$ , $I_B = 125\text{ mAdc}$ )   | $V_{CE(sat)}$  | -                     | 0.7                      | Vdc             |
| Base-Emitter On Voltage ( $I_C = 1.0\text{ Adc}$ , $V_{CE} = 4.0\text{ Vdc}$ )  | $V_{BE(on)}$   | -                     | 1.3                      | Vdc             |
| <b>DYNAMIC CHARACTERISTICS</b>  |                |                       |                          |                 |
| Current-Gain - Bandwidth Product (Note 3)<br>( $I_C = 200\text{ mAdc}$ , $V_{CE} = 10\text{ Vdc}$ , $f_{test} = 1.0\text{ MHz}$ )   | $f_T$          | 3.0                   | -                        | MHz             |
| Small-Signal Current Gain ( $I_C = 0.2\text{ Adc}$ , $V_{CE} = 10\text{ Vdc}$ , $f = 1.0\text{ kHz}$ )  | $h_{fe}$       | 20                    | -                        | -               |


2. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2.0\%$

3.  $f_T = |h_{fe}| \cdot f_{test}$

# TIP29, A, B, C (NPN), TIP30, A, B, C (PNP)

## PACKAGE DIMENSIONS

TO-220  
CASE 221A-09  
ISSUE AE



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.570  | 0.620 | 14.48       | 15.75 |
| B   | 0.380  | 0.405 | 9.66        | 10.28 |
| C   | 0.160  | 0.190 | 4.07        | 4.82  |
| D   | 0.025  | 0.035 | 0.64        | 0.88  |
| F   | 0.142  | 0.161 | 3.61        | 4.09  |
| G   | 0.095  | 0.105 | 2.42        | 2.66  |
| H   | 0.110  | 0.155 | 2.80        | 3.93  |
| J   | 0.014  | 0.025 | 0.36        | 0.64  |
| K   | 0.500  | 0.562 | 12.70       | 14.27 |
| L   | 0.045  | 0.060 | 1.15        | 1.52  |
| N   | 0.190  | 0.210 | 4.83        | 5.33  |
| Q   | 0.100  | 0.120 | 2.54        | 3.04  |
| R   | 0.080  | 0.110 | 2.04        | 2.79  |
| S   | 0.045  | 0.055 | 1.15        | 1.39  |
| T   | 0.235  | 0.255 | 5.97        | 6.47  |
| U   | 0.000  | 0.050 | 0.00        | 1.27  |
| V   | 0.045  | ---   | 1.15        | ---   |
| Z   | ---    | 0.080 | ---         | 2.04  |