

Cooper Bussmann Homepage About Cooper Bussmann Contact Us Privacy Legal Cooper Bussmann® Brand Site Map	al IEC Electronics Consumer/Aftermarket OEM Transportation Terminal Blocks Systems/Services/Software FNM-3 Time-Delay Supplementary Fuses, 13/32 x 1-1/2 Inches					
	Product Informat					
	Product Type:	Fuse				
	Product Family:	Electrical Power				
	Upgrade Product:	LP-CC-3		tifications		
	Brand:	Cooper Bussmann	<u>UL L</u>	isted		
	Sub-brand:	Fusetron	CSA	Certified		
	Recommended P	coducts	Electrical Propert	tion		
	Recommended Pl	ouders		lies		
	Rec. Fuse Block:	BM603 Series	Maximum AC			
				250 3		
	Rec. Fuse Block: Rec. Inline Fuse	BM603 Series	Maximum AC Voltage: Amperage Rating: AC Interrupting	250		
	Rec. Fuse Block: Rec. Inline Fuse Holder: Rec. Panel-mount	BM603 Series	Maximum AC Voltage: Amperage Rating: AC Interrupting Ratings:	250 3 • 10000 at 125V • 100 at 250V		
	Rec. Fuse Block: Rec. Inline Fuse Holder: Rec. Panel-mount Fuse Holder: Rec. Modular Fuse	BM603 Series HPS HEB Series	Maximum AC Voltage: Amperage Rating: AC Interrupting	250 3 • 10000 at 125V		
	Rec. Fuse Block: Rec. Inline Fuse Holder: Rec. Panel-mount Fuse Holder: Rec. Modular Fuse Holder:	BM603 SeriesHPSHEB SeriesOPM-NG-SM3	Maximum AC Voltage: Amperage Rating: AC Interrupting Ratings:	250 3 • 10000 at 125V • 100 at 250V		
	Rec. Fuse Block: Rec. Inline Fuse Holder: Rec. Panel-mount Fuse Holder: Rec. Modular Fuse Holder: Rec. Fuse Clips:	BM603 SeriesHPSHEB SeriesOPM-NG-SM35960 SeriesSAMI-7 Series	Maximum AC Voltage: Amperage Rating: AC Interrupting Ratings:	250 3 • 10000 at 125V • 100 at 250V		

Downloaded from **Elcodis.com** electronic components distributor

Bussmann®

Time-Delay Ferrule Fuse 13/32" x 1-1/2"

FNM



- · Fibre tube.
- · For circuits with high inrush currents.
- · Formerly designated 5AB.
- Fusetron[®] Dual-Element fuse.



Recommended fuseblocks/fuseholders for 13/32" x 1-1/2" fuses See Data Sheets listed below

- Open fuseblocks 1104, 2104
- Finger-safe fuseholders 1109, 1102, 1103, 1151
- Panel-mount fuseholders 2114, 2113, 2108, 2112, 2109, 2140
- - In-line fuseholders 2127, 2126

Catalog Symbol: FNM TIME-DELAY 1/10 TO 30A Interrupting Rating - SEE CHART BELOW UL Listed: STD. 248-14, 0-10/250Vac; 12-15/125Vac FILE #E19180, GUIDE #JDYX CSA Certified: 1-10/250Vac; CLASS 1422-01, 12-15/125Vac; FILE 53787

Electrical Ratings (Catalog Symbol and Amperes)

250Vac IR		250Vac	IR		250Vac	IR		125Vac	
FNM-1/10		FNM-1-1	/8		FNM-4			FNM-12	- 10,000
FNM-1/8		FNM-1-1	/4		FNM-4-1	/2		FNM-15	@ 125Vac
FNM-15/100		FNM-1-4	/10		FNM-5			-	
FNM-2/10		FNM-1-1	/2		FNM-5-6	/10		-	
FNM-1/4	35A@	FNM-1-6	/10	100A @	FNM-6			32Vac	
FNM-3/10	250Vac	FNM-1-8	/10		FNM-6-1	/4	200A@	FNM-20	
FNM-4/10	10,000	FNM-2		10,000	FNM-7		250Vac	FNM-25	
FNM-1/2	@	FNM-2-1	/4	@	FNM-8		10,000 @ 125Vac	FNM-30	
FNM-6/10	125Vac	FNM-2-1	/2	125Vac	FNM-9		125 Vac	-	
FNM-3/4		FNM-2-8	/10		FNM-10			_	
FNM-8/10		FNM-3			_			_	
FNM-1		FNM-3-2	/10		_			_	
-		FNM-3-1	/2		-			-	

If 250Vac is needed for 12-30A, use FNW series.

Carton Quantity and Weight

Ampere	Carton	Weight		
Ratings	Qty	Lbs.	Kg.	
0-30	10	.125	.057	

C€



Form No. FNM Page 1 of 2 Data Sheet: 2028