

<u>All Categories</u> > <u>Broadband Split / Snap-on Ferrite Cores for Round Cables</u> > <u>Broadband Solid Ferrite Cores for Round</u> <u>Cables and Wiring Harnesses</u> > <u>Multiple Turn Axial Wire Ferrite Beads / Cores</u> > <u>Chip Beads - Power Filtering</u> > <u>Axial Lead</u> <u>Beads - Power Filtering</u> > <u>Chip Beads - Low Frequency</u> > Item # 35F0121-1SR-10

Item # 35F0121-1SR-10 Chip Beads - Low Frequency





Specifications

Figure Number	2
Typical Z Ohms at 1 MHz	35
Typical Z Ohms at 5 MHz	82
Typical Z Ohms at 10 MHz	102
Typical Z Ohms at 25 MHz	90
Typical Peak Impedance	104 ohms
Peak Impedance Frequency	17 MHz
Max. DCR	0.001 ohms
Rated Current (Continuous)	10000
Dimension A	3.05 mm 0.120 in
Dimension B	2.54 mm 0.100 in
Dimension B1	0.120 in 3.05 mm
Dimension C	8.51 mm 0.335 in
Dimension C1	0.375 in 9.53 mm

Downloaded from Elcodis.com electronic components distributor

Dimension T1	0.050 in 1.27 mm
Dimension T2	0.060 in 1.52 mm
Product Type Code	Assembled Part
Part Size Code	0121
Board Mounting Style	Surface Mount
Packaging	Tape & Reel Standard SMT Package
Additional Description	Lead Free Standard Catalog Part

Print Back
