



Search This Product Catalog

[Product Catalog for Global Telecommunications OEM Site](#) > [Products for Equipment Manufacturers](#) . . . [3M™ D Sub, Socket Connector, 8300 Series](#) > [3M™ D Sub, Socket Connector, 9 Contacts, 8309 Series](#) >

 **Printer-friendly format 3M™ D Sub Connectors, D Sub Socket, 9 Contacts, 8309-6000**  
**Open Cover, Mounting Style Ø.120 [3.05]. Available Option is 3448-8D9A Strain Relief, Ordered Separately. 100/Pack**



[\[click to enlarge\]](#)

3M Id : DE-6100-0721-8  
 GTIN(UPC/EAN) : 0 00 51138 32351 6

**Additional Information**

- Available in either preassembled or two piece covers
- Available in either open or closed end cover
- Improved metal strain relief — hooks directly to metal shell
- Low profile
- Four mounting options
- RoHS compliant

For more information, refer to TS0235 (TS-0235).

**Learn More . . .**

[Packaging Data](#)

[3M™ D Sub Socket, 8300 Series, TS0235 - Data Sheet \(PDF 336.6 K\)](#)

[3M™ I/O Wire to Wire Conn., .100" Mating & Accessory Charts - Product Selection Guide \(PDF 72.6 K\)](#)

**Please Note:**

Adobe® Acrobat® Reader is required to view PDF documents.



Return to Solutions for Network Equipment Manufacturers

- Product Catalog for Global Telecommunications OEM Site
  - [Products for Business Enterprise](#)
  - [Products for Carriers](#)
  - [Products for Equipment Manufacturers](#)

Related Solution Sites

- [3M Access Network](#)
- [Enterprise Networks](#)

**Characteristics**

<b>Conductor Accommodation</b>	26 & 28 AWG Solid or Stranded
<b>Contact Material</b>	Copper Alloy
<b>Contact Termination Area Plating</b>	None
<b>Contact Underplating</b>	100 μ" [2.54 μm] Nickel
<b>Contact Wiping Area Plating</b>	30 μ" [0.76 μm] Gold
<b>Current Rating</b>	1 Ampere
<b>Insulation Color</b>	Gray
<b>Insulation Flammability Rating</b>	UL 94V-0
<b>Insulation Material</b>	Glass Filled Polyester (PBT)
<b>Insulation Resistance</b>	>1 X 10 <sup>9</sup> Ohms @ 500 Vdc
<b>Interface Grid</b>	1.11"
<b>Interface Style</b>	D Sub Socket
<b>Markings</b>	3M Logo & Contact Position Numbers
<b>Mounting Option</b>	Mounting Flanges - .120" Dia Hole
<b>Non-Operating Temperature</b>	-55 to 105 Degree Celsius
<b>Number of Contact Rows</b>	2

<b>Number of Contacts</b>	9
<b>Pitch</b>	.050 Inch
<b>Primary Trademark Name</b>	3M
<b>Separable</b>	Yes
<b>Shield</b>	Yes
<b>Termination Method</b>	Insulation Displacement
<b>Termination Style</b>	Multiple Wires
<b>Withstanding Voltage</b>	1000 Vrms at Sea Level