



Silicon PIN Diode

- Optimized for antenna switches in hand held applications
- Very low capacitance at zero volts reverse bias at frequencies above 1GHz (typ. 0.19 pF)
- Low forward resistance (typ. 0.8Ω @ $I_F = 10\text{mA}$)
- Very low signal distortion
- Pb-free (RoHS compliant) package ¹⁾
- Qualified according AEC Q101


BAR89-02LRH


Type	Package	Configuration	L_S (nH)	Marking
BAR89-02LRH	TSLP-2-7	single, leadless	0.4	R

Maximum Ratings at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	80	V
Forward current	I_F	100	mA
Total power dissipation $T_S \leq 133^\circ\text{C}$	P_{tot}	250	mW
Junction temperature	T_j	150	°C
Operating temperature range	T_{op}	-55 ... 125	
Storage temperature	T_{stg}	-55 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point ²⁾	R_{thJS}	≤ 65	K/W

¹⁾Pb-containing package may be available upon special request

²⁾For calculation of R_{thJA} please refer to Application Note Thermal Resistance

Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Breakdown voltage $I_{(BR)} = 5 \mu\text{A}$	$V_{(BR)}$	80	-	-	V
Reverse current $V_R = 60 \text{ V}$	I_R	-	-	50	nA
Forward voltage $I_F = 10 \text{ mA}$ $I_F = 100 \text{ mA}$	V_F	-	0.83 0.95	0.9 1.1	V


Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
AC Characteristics					
Diode capacitance	C_T	-	0.25	0.35	pF
$V_R = 1\text{ V}, f = 1\text{ MHz}$		-	0.25	-	
$V_R = 0\text{ V}, f = 100\text{ MHz}$		-	0.19	-	
$V_R = 0\text{ V}, f = 1\text{ GHz}$		-	0.18	-	
$V_R = 0\text{ V}, f = 1.8\text{ GHz}$		-	-	-	
Reverse parallel resistance	R_P	-	35	-	k Ω
$V_R = 0\text{ V}, f = 100\text{ MHz}$		-	5	-	
$V_R = 0\text{ V}, f = 1\text{ GHz}$		-	3.5	-	
$V_R = 0\text{ V}, f = 1.8\text{ GHz}$		-	-	-	
Forward resistance	r_f	-	3	-	Ω
$I_F = 1\text{ mA}, f = 100\text{ MHz}$		-	1.2	-	
$I_F = 5\text{ mA}, f = 100\text{ MHz}$		-	0.8	1.5	
$I_F = 10\text{ mA}, f = 100\text{ MHz}$		-	-	-	
Charge carrier life time	τ_{rr}	-	800	-	ns
$I_F = 10\text{ mA}, I_R = 6\text{ mA}$, measured at $I_R = 3\text{ mA}$, $R_L = 100\ \Omega$		-	-	-	
I-region width	W_I	-	19	-	μm
Insertion loss ¹⁾	l_L	-	0.23	-	dB
$I_F = 1\text{ mA}, f = 1.8\text{ GHz}$		-	0.1	-	
$I_F = 5\text{ mA}, f = 1.8\text{ GHz}$		-	0.08	-	
$I_F = 10\text{ mA}, f = 1.8\text{ GHz}$		-	-	-	
Isolation ¹⁾	l_{SO}	-	19	-	
$V_R = 0\text{ V}, f = 0.9\text{ GHz}$		-	14	-	
$V_R = 0\text{ V}, f = 1.8\text{ GHz}$		-	11	-	
$V_R = 0\text{ V}, f = 2.45\text{ GHz}$		-	-	-	

¹BAR89-02LRH in series configuration, $Z = 50\ \Omega$


Diode capacitance $C_T = f(V_R)$

$f =$ Parameter




Reverse parallel resistance $R_p = f(V_R)$

$f =$ Parameter




Forward resistance $r_f = f(I_F)$

$f = 100\text{MHz}$




Forward current $I_F = f(V_F)$

$T_A =$ Parameter




Forward current $I_F = f(T_S)$

BAR89-02LRH



Permissible Puls Load $R_{thJS} = f(t_p)$


BAR89-02LRH



Permissible Pulse Load

$I_{Fmax} / I_{FDC} = f(t_p)$


BAR89-02LRH



Insertion loss $I_L = -|S_{21}|^2 = f(f)$

I_F = Parameter


BAR89-02LRH in series configuration, $Z = 50\Omega$




Isolation $I_{SO} = -|S_{21}|^2 = f(f)$

V_R = Parameter

BAR89-02LRH in series configuration, $Z = 50\Omega$




Package Outline




Foot Print

For board assembly information please refer to Infineon website "Packages"




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 15.000 Pieces/Reel
 Reel ø330 mm = 50.000 Pieces/Reel (optional)



Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.