



Silicon RF Schottky Diodes

- Low barrier type for mixer applications up to 12 GHz, phase detectors and modulators
- Pb-free (RoHS compliant) package¹⁾
- Qualified according AEC Q101


BAT15-04R


ESD (Electrostatic discharge) sensitive device, observe handling precaution!

| Type | Package | Configuration | L_S (nH) | Marking |
|------------|---------|---------------------|------------|---------|
| BAT15-04R* | SOT 23 | reverse series pair | 1.5 | 4R |

*preliminary

¹Pb-containing package may be available upon special request

Maximum Ratings at $T_A = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Value | Unit |
|-----------------------------|-----------|-------------|------|
| Diode reverse voltage | V_R | 4 | V |
| Forward current | I_F | 110 | mA |
| Junction temperature | T_j | 150 | °C |
| Operating temperature range | T_{op} | -55 ... 150 | |
| Storage temperature | T_{stg} | -65 ... 150 | |


Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Values | | | Unit |
|--|--------------|--------|------|------|----------|
| | | min. | typ. | max. | |
| DC Characteristics | | | | | |
| Breakdown voltage $I_{(BR)} = 10 \mu\text{A}$ | $V_{(BR)}$ | 4 | - | - | V |
| Forward voltage $I_F = 1 \text{ mA}$ | V_F | 0.2 | 0.25 | 0.3 | |
| Forward voltage matching ¹⁾ $I_F = 1 \text{ mA}$ | ΔV_F | - | - | 10 | mV |
| AC Characteristics | | | | | |
| Diode capacitance $V_R = 0 \text{ V}, f = 1 \text{ MHz}$ | C_T | - | 0.25 | - | pF |
| Differential forward resistance $I_F = 5 \text{ mA}$ | R_F | - | - | 18 | Ω |

¹⁾ ΔV_F is the difference between lowest and highest V_F in a multiple diode component.


Diode capacitance $C_T = f(V_R)$

$f = 1\text{MHz}$




Reverse current $I_R = f(V_R)$

$T_A = \text{Parameter}$




Forward Voltage $V_F = f(T_A)$

$I_F = \text{Parameter}$




Forward current $I_F = f(V_F)$

$T_A = 25^\circ\text{C}$




Package Outline




1) Lead width can be 0.6 max. in dambar area

Foot Print




Marking Layout (Example)



Standard Packing

Reel \varnothing 180 mm = 3.000 Pieces/Reel
 Reel \varnothing 330 mm = 10.000 Pieces/Reel



Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.