



PD54003-E PD54003S-E

RF POWER transistor, LdmoST plastic family
N-channel enhancement-mode, lateral MOSFETs

Features

- Excellent thermal stability
- Common source configuration
- $P_{OUT} = 3 \text{ W}$ with 12dB gain @ 500 MHz
- New RF plastic package

Description

The device is a common source N-channel, enhancement-mode lateral field-effect RF power transistor. It is designed for high gain, broadband commercial and industrial applications. It operates at 7 V in common source mode at frequencies of up to 1 GHz. The device features the excellent gain, linearity and reliability of ST's latest LDMOS technology, the PowerSO-10RF. The superior linearity performance makes it an ideal solution for portable radios. The PowerSO-10RF is the first true surface-mount device (SMD) plastic RF power package. It is based on the highly reliable PowerSO-10, the first ST-originated, JEDEC-approved, high-power SMD package. It has been optimized specifically for RF requirements, and offers excellent RF performance as well as ease of assembly. surface-mount recommendations are available in application note AN1294 (see www.st.com/rf).




Figure 1. Pin connection




Table 1. Device summary

| Order code | Package | Packing |
|--------------|------------------------------|---------------|
| PD54003-E | PowerSO-10RF (formed lead) | Tube |
| PD54003S-E | PowerSO-10RF (straight lead) | Tube |
| PD54003TR-E | PowerSO-10RF (formed lead) | Tape and reel |
| PD54003STR-E | PowerSO-10RF (straight lead) | Tape and reel |

Contents

| | | |
|----------|-----------------------------------|-----------|
| 1 | Electrical data | 3 |
| 1.1 | Maximum ratings | 3 |
| 1.2 | Thermal data | 3 |
| 2 | Electrical characteristics | 4 |
| 2.1 | Static | 4 |
| 2.2 | Dynamic | 4 |
| 2.3 | Moisture sensitivity level | 4 |
| 3 | Impedance | 5 |
| 4 | Typical performance | 6 |
| 4.1 | PD54003-E | 7 |
| 4.2 | PD54003S-E | 9 |
| 5 | Test circuit | 11 |
| 6 | Circuit layout | 13 |
| 7 | Common source s-parameter | 14 |
| 8 | Package mechanical data | 20 |
| 9 | Revision history | 26 |

1 Electrical data

1.1 Maximum ratings

Table 2. Absolute maximum ratings ($T_{CASE} = 25^\circ\text{C}$)

| Symbol | Parameter | Value | Unit |
|---------------|---|-------------|------------------|
| $V_{(BR)DSS}$ | Drain-source voltage | 25 | V |
| V_{GS} | Gate-source voltage | ± 20 | V |
| I_D | Drain current | 4 | A |
| P_{DISS} | Power dissipation (@ $T_C = 70^\circ\text{C}$) | 52.8 | W |
| T_J | Max. operating junction temperature | 165 | $^\circ\text{C}$ |
| T_{STG} | Storage temperature | -65 to +150 | $^\circ\text{C}$ |

1.2 Thermal data

Table 3. Thermal data

| Symbol | Parameter | Value | Unit |
|------------|------------------------------------|-------|---------------------------|
| R_{thJC} | Junction - case thermal resistance | 1.8 | $^\circ\text{C}/\text{W}$ |

2 Electrical characteristics

$T_{CASE} = +25^{\circ}\text{C}$

2.1 Static

Table 4. Static

| Symbol | Test conditions | | Min. | Typ. | Max. | Unit |
|--------------|-------------------------|--------------------------|-------------------------|------|------|---------------|
| I_{DSS} | $V_{GS} = 0$ | | $V_{DS} = 25 \text{ V}$ | | 1 | μA |
| I_{GSS} | $V_{GS} = 20 \text{ V}$ | | $V_{DS} = 0$ | | 1 | μA |
| $V_{GS(Q)}$ | $V_{DS} = 10 \text{ V}$ | | $I_D = 50 \text{ mA}$ | | 2.0 | V |
| $V_{DS(ON)}$ | $V_{GS} = 10 \text{ V}$ | | $I_D = 1 \text{ A}$ | | 1.3 | V |
| g_{FS} | $V_{DS} = 10 \text{ V}$ | | $I_D = 3.2 \text{ A}$ | | 1.7 | mho |
| C_{ISS} | $V_{GS} = 0$ | $V_{DS} = 7.5 \text{ V}$ | $f = 1 \text{ MHz}$ | 59 | | pF |
| C_{OSS} | $V_{GS} = 0$ | $V_{DS} = 7.5 \text{ V}$ | $f = 1 \text{ MHz}$ | 43 | | pF |
| C_{RSS} | $V_{GS} = 0$ | $V_{DS} = 7.5 \text{ V}$ | $f = 1 \text{ MHz}$ | 4.0 | | pF |

2.2 Dynamic

Table 5. Dynamic

| Symbol | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|---|------|------|------|------|
| P_{OUT} | $V_{DD} = 7.5 \text{ V}$, $I_{DQ} = 50 \text{ mA}$ | 3 | | | W |
| G_{PS} | $V_{DD} = 7.5 \text{ V}$, $I_{DQ} = 50 \text{ mA}$, $P_{OUT} = 3 \text{ W}$, $f = 500 \text{ MHz}$ | 10 | 12 | | dB |
| n_D | $V_{DD} = 7.5 \text{ V}$, $I_{DQ} = 50 \text{ mA}$, $P_{OUT} = 3 \text{ W}$, $f = 500 \text{ MHz}$ | 50 | 55 | | % |
| Load mismatch | $V_{DD} = 9.5 \text{ V}$, $I_{DQ} = 50 \text{ mA}$, $P_{OUT} = 3 \text{ W}$, $f = 500 \text{ MHz}$ All phase angles | 20:1 | | | VSWR |

2.3 Moisture sensitivity level

Table 6. Moisture sensitivity level

| Test methodology | Rating |
|------------------|--------|
| J-STD-020B | MSL 3 |

3 Impedance

Figure 2. Current conventions




Table 7. Impedance data

| PD54003-E | | | PD54003S-E | | |
|-------------|-----------------------|-----------------------|-------------|-----------------------|-----------------------|
| Freq. (MHz) | Z_{IN} (Ω) | Z_{DL} (Ω) | Freq. (MHz) | Z_{IN} (Ω) | Z_{DL} (Ω) |
| 480 | $2.245 - j 0.077$ | $3.436 + j 1.013$ | 480 | $1.400 - j 3.986$ | $2.805 + j 2.724$ |
| 500 | $1.553 - j 1.251$ | $2.661 + j 0.139$ | 500 | $1.209 - j 2.451$ | $3.192 + j 3.147$ |
| 520 | $1.993 - j 1.098$ | $2.564 + j 0.656$ | 520 | $1.534 - j 2.104$ | $2.524 + j 2.369$ |

4 Typical performance

Figure 3. Capacitance vs. drain voltage




Figure 4. Drain current vs. gate voltage





Figure 5. Gate-source voltage vs. case temperature



4.1 PD54003-E

Figure 6. Output power vs. input power




Figure 7. Power gain vs. output power




Figure 8. Drain efficiency vs. output power




Figure 9. Return loss vs. output power









Figure 10. Output power vs. bias current**Figure 11. Drain voltage vs. bias current****Figure 12. Output power vs. supply voltage****Figure 13. Drain efficiency vs. supply voltage****Figure 14. Output power vs. gate-source voltage**

4.2 PD54003S-E

Figure 15. Output power vs. input power




Figure 16. Power gain vs. output power




Figure 17. Drain efficiency vs. output power




Figure 18. Return loss vs. output power




Figure 19. Output power vs. bias current




Figure 20. Drain efficiency vs. bias current







Figure 21. Output power vs. supply voltage**Figure 22. Drain efficiency vs. supply voltage****Figure 23. Output power vs. gate-source voltage**

5 Test circuit

Figure 24. Test circuit schematic




Table 8. Test circuit component part list

| Component | Description |
|----------------------|---|
| B1,B2 | Short ferrite bead, fair rite products (2743021446) |
| C1,C13 | 240 pF, 100 mil chip capacitor |
| C2,C3,C4,C10,C11,C12 | 0 to 20 pF trimmer capacitor |
| C5 | 130 pF, 100 mil chip capacitor |
| C6,C17 | 120 pF, 100 mil chip capacitor |
| C7,C14 | 10 μ F, 50 V electrolytic capacitor |
| C8,C15 | 1.200 pF, 100 mil chip capacitor |
| C9,C16 | 0.1 F, 100 mil chip capacitor |
| L1 | 55.5 Nh, 5 turn, Coilcraft |
| N1,N2 | Type N flange mount |
| R1 | 15 Ω , 0805 chip resistor |
| R2 | 1.0 k Ω , 1/8 W resistor |
| R3 | 15 Ω , 0805 chip resistor |
| R4 | 33 k Ω , 1/8 W resistor |
| Z1 | 0.175" X 0.080" microstrip |
| Z2 | 1.049" X 0.080" microstrip |
| Z3 | 0.289" X 0.080" microstrip |
| Z4 | 0.026" X 0.080" microstrip |
| Z5 | 0.192" X 0.223" microstrip |
| Z6,Z7 | 0.260" X 0.223" microstrip |
| Z8 | 0.064" X 0.080" microstrip |

Table 8. Test circuit component part list (continued)

| Component | Description |
|-----------|---|
| Z9 | 0.334" X 0.080" microstrip |
| Z10 | 0.985" X 0.080" microstrip |
| Z11 | 0.472" X 0.080" microstrip |
| Board | ROGER, ultra lam 2000 THK 0.030", $\epsilon_r = 2.55$ 2oz. ED cu 2 SIDES. |

6 Circuit layout

Figure 25. Test fixture component layout





Figure 26. Test circuit photomaster



7 Common source s-parameter

Table 9. S-parameter for PD54003-E ($V_{DS} = 7.5$ V, $I_{DS} = 50$ mA)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 0.729 | -127 | 10.26 | 94 | 0.058 | 5 | 0.702 | -122 |
| 100 | 0.759 | -146 | 4.91 | 72 | 0.056 | -15 | 0.706 | -141 |
| 150 | 0.807 | -154 | 3.02 | 59 | 0.050 | -28 | 0.749 | -149 |
| 200 | 0.845 | -159 | 2.06 | 48 | 0.044 | -38 | 0.802 | -154 |
| 250 | 0.844 | -162 | 1.48 | 40 | 0.039 | -45 | 0.839 | -185 |
| 300 | 0.901 | -165 | 1.12 | 33 | 0.034 | -52 | 0.875 | -162 |
| 350 | 0.921 | -168 | 0.86 | 27 | 0.030 | -57 | 0.899 | -165 |
| 400 | 0.932 | -170 | 0.69 | 22 | 0.027 | -60 | 0.915 | -168 |
| 450 | 0.944 | -172 | 0.56 | 18 | 0.023 | -64 | 0.935 | -170 |
| 500 | 0.952 | -173 | 0.47 | 14 | 0.019 | -66 | 0.943 | -172 |
| 550 | 0.957 | -175 | 0.39 | 11 | 0.017 | -68 | 0.951 | -173 |
| 600 | 0.962 | -176 | 0.33 | 8 | 0.014 | -72 | 0.954 | -175 |
| 650 | 0.967 | -177 | 0.29 | 5 | 0.012 | -70 | 0.958 | -176 |
| 700 | 0.969 | -178 | 0.25 | 3 | 0.010 | -71 | 0.958 | -178 |
| 750 | 0.970 | -180 | 0.22 | 1 | 0.009 | -69 | 0.963 | -179 |
| 800 | 0.972 | 179 | 0.20 | -1 | 0.008 | -71 | 0.963 | 179 |
| 850 | 0.972 | 179 | 0.18 | -2 | 0.007 | -78 | 0.969 | 178 |
| 900 | 0.973 | 178 | 0.16 | -4 | 0.004 | -76 | 0.972 | 177 |
| 950 | 0.972 | 177 | 0.15 | -5 | 0.002 | -46 | 0.972 | 176 |
| 1000 | 0.975 | 176 | 0.13 | -6 | 0.003 | -42 | 0.973 | 175 |
| 1050 | 0.975 | 175 | 0.12 | -7 | 0.001 | 14 | 0.968 | 174 |
| 1100 | 0.975 | 174 | 0.11 | -8 | 0.003 | 29 | 0.966 | 173 |
| 1150 | 0.970 | 173 | 0.10 | -10 | 0.003 | 51 | 0.967 | 172 |
| 1200 | 0.973 | 173 | 0.10 | -10 | 0.005 | 65 | 0.965 | 171 |
| 1250 | 0.972 | 172 | 0.09 | -12 | 0.005 | 62 | 0.966 | 170 |
| 1300 | 0.970 | 171 | 0.08 | -12 | 0.007 | 67 | 0.963 | 170 |
| 1350 | 0.970 | 170 | 0.08 | -12 | 0.007 | 67 | 0.959 | 169 |
| 1400 | 0.967 | 170 | 0.07 | -12 | 0.008 | 73 | 0.962 | 168 |
| 1450 | 0.968 | 169 | 0.07 | -12 | 0.010 | 64 | 0.953 | 167 |
| 1500 | 0.965 | 168 | 0.06 | -15 | 0.010 | 76 | 0.950 | 166 |

Table 10. S-parameter PD54003-E ($V_{DS} = 7.5$ V, $I_{DS} = 500$ mA)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 0.779 | -162 | 16.39 | 88 | 0.026 | 4 | 0.772 | -160 |
| 100 | 0.810 | -168 | 7.93 | 79 | 0.025 | -7 | 0.768 | -168 |
| 150 | 0.836 | -171 | 5.18 | 73 | 0.024 | -13 | 0.774 | -171 |
| 200 | 0.850 | -173 | 3.81 | 67 | 0.023 | -16 | 0.784 | -172 |
| 250 | 0.861 | -174 | 2.96 | 60 | 0.022 | -21 | 0.795 | -173 |
| 300 | 0.871 | -175 | 2.39 | 55 | 0.020 | -24 | 0.815 | -174 |
| 350 | 0.881 | -176 | 1.97 | 49 | 0.018 | -27 | 0.813 | -174 |
| 400 | 0.890 | -176 | 1.65 | 45 | 0.017 | -31 | 0.845 | -175 |
| 450 | 0.901 | -177 | 1.40 | 40 | 0.016 | -30 | 0.865 | -176 |
| 500 | 0.908 | -178 | 1.20 | 36 | 0.015 | -34 | 0.876 | 176 |
| 550 | 0.915 | -179 | 1.05 | 32 | 0.013 | -32 | 0.886 | -177 |
| 600 | 0.924 | -179 | 0.92 | 28 | 0.012 | -34 | 0.894 | -178 |
| 650 | 0.928 | 180 | 0.81 | 25 | 0.010 | -33 | 0.900 | -179 |
| 700 | 0.934 | 179 | 0.72 | 22 | 0.010 | -33 | 0.906 | 180 |
| 750 | 0.937 | 178 | 0.65 | 19 | 0.008 | -29 | 0.912 | 179 |
| 800 | 0.939 | 177 | 0.59 | 17 | 0.007 | -24 | 0.920 | 178 |
| 850 | 0.943 | 177 | 0.53 | 14 | 0.006 | -15 | 0.928 | 177 |
| 900 | 0.943 | 176 | 0.48 | 12 | 0.006 | -7 | 0.932 | 176 |
| 950 | 0.948 | 175 | 0.45 | 10 | 0.005 | 9 | 0.934 | 175 |
| 1000 | 0.950 | 175 | 0.41 | 7 | 0.005 | 11 | 0.938 | 174 |
| 1050 | 0.952 | 174 | 0.38 | 5 | 0.006 | 28 | 0.934 | 173 |
| 1100 | 0.955 | 173 | 0.35 | 3 | 0.006 | 33 | 0.937 | 172 |
| 1150 | 0.954 | 172 | 0.32 | 1 | 0.007 | 41 | 0.938 | 172 |
| 1200 | 0.954 | 172 | 0.30 | 0 | 0.007 | 40 | 0.938 | 171 |
| 1250 | 0.953 | 172 | 0.28 | -3 | 0.008 | 51 | 0.940 | 170 |
| 1300 | 0.952 | 170 | 0.26 | -4 | 0.008 | 53 | 0.939 | 169 |
| 1350 | 0.954 | 170 | 0.24 | -5 | 0.010 | 55 | 0.936 | 168 |
| 1400 | 0.952 | 169 | 0.23 | -6 | 0.011 | 57 | 0.943 | 167 |
| 1450 | 0.952 | 168 | 0.22 | -7 | 0.011 | 59 | 0.933 | 167 |
| 1500 | 0.950 | 168 | 0.20 | -8 | 0.010 | 70 | 0.930 | 166 |

Table 11. S-parameter for PD54003-E ($V_{DS} = 7.5$ V, $I_{DS} = 1$ A)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 0.802 | -166 | 16.70 | 88 | 0.021 | 0 | 0.793 | -164 |
| 100 | 0.831 | -170 | 8.10 | 80 | 0.021 | -6 | 0.790 | -171 |
| 150 | 0.855 | -173 | 5.32 | 75 | 0.020 | -8 | 0.793 | -173 |
| 200 | 0.867 | -175 | 3.94 | 69 | 0.019 | -13 | 0.801 | -174 |
| 250 | 0.876 | -175 | 3.08 | 64 | 0.019 | -16 | 0.807 | -175 |
| 300 | 0.883 | -177 | 2.52 | 59 | 0.018 | -19 | 0.822 | -176 |
| 350 | 0.887 | -177 | 2.09 | 53 | 0.017 | -22 | 0.834 | -176 |
| 400 | 0.864 | -178 | 1.77 | 49 | 0.015 | -24 | 0.844 | -177 |
| 450 | 0.903 | -178 | 1.52 | 44 | 0.014 | -23 | 0.864 | -177 |
| 500 | 0.911 | -179 | 1.32 | 40 | 0.013 | -26 | 0.871 | -178 |
| 550 | 0.916 | -180 | 1.15 | 36 | 0.012 | -27 | 0.880 | -179 |
| 600 | 0.922 | 179 | 1.01 | 33 | 0.010 | -25 | 0.886 | -179 |
| 650 | 0.926 | 179 | 0.90 | 30 | 0.010 | -20 | 0.989 | 180 |
| 700 | 0.931 | 178 | 0.81 | 27 | 0.009 | -23 | 0.898 | 179 |
| 750 | 0.934 | 177 | 0.73 | 24 | 0.008 | -15 | 0.903 | 178 |
| 800 | 0.938 | 177 | 0.66 | 21 | 0.007 | -16 | 0.911 | 177 |
| 850 | 0.941 | 176 | 0.60 | 18 | 0.007 | 2 | 0.919 | 176 |
| 900 | 0.944 | 175 | 0.55 | 16 | 0.007 | 3 | 0.923 | 175 |
| 950 | 0.945 | 175 | 0.51 | 13 | 0.007 | 14 | 0.927 | 175 |
| 1000 | 0.947 | 174 | 0.47 | 11 | 0.005 | 29 | 0.930 | 174 |
| 1050 | 0.950 | 173 | 0.43 | 9 | 0.007 | 24 | 0.930 | 173 |
| 1100 | 0.952 | 173 | 0.40 | 6 | 0.007 | 41 | 0.929 | 172 |
| 1150 | 0.947 | 172 | 0.37 | 4 | 0.007 | 35 | 0.932 | 171 |
| 1200 | 0.949 | 171 | 0.35 | 2 | 0.009 | 47 | 0.931 | 171 |
| 1250 | 0.951 | 171 | 0.32 | 0 | 0.009 | 52 | 0.934 | 170 |
| 1300 | 0.951 | 170 | 0.30 | -1 | 0.009 | 42 | 0.931 | 169 |
| 1350 | 0.948 | 169 | 0.28 | -2 | 0.011 | 51 | 0.931 | 168 |
| 1400 | 0.948 | 169 | 0.26 | -4 | 0.011 | 53 | 0.935 | 167 |
| 1450 | 0.948 | 168 | 0.25 | -5 | 0.011 | 55 | 0.927 | 167 |
| 1500 | 0.945 | 167 | 0.23 | -6 | 0.012 | 64 | 0.927 | 165 |

Table 12. S-parameter for PD54003S-E ($V_{DS} = 7.5$ V, $I_{DS} = 50$ mA)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 0.749 | -133 | 9.42 | 93 | 0.063 | 4 | 0.702 | -130 |
| 100 | 0.760 | -151 | 4.51 | 74 | 0.060 | -15 | 0.706 | -147 |
| 150 | 0.799 | -157 | 2.81 | 62 | 0.055 | -26 | 0.747 | -153 |
| 200 | 0.837 | -160 | 1.93 | 52 | 0.051 | -36 | 0.790 | -157 |
| 250 | 0.869 | -163 | 1.41 | 43 | 0.046 | -43 | 0.835 | -160 |
| 300 | 0.893 | -165 | 1.08 | 37 | 0.041 | -49 | | -162 |
| 350 | 0.913 | -167 | 0.84 | 31 | 0.037 | -53 | 0.885 | -165 |
| 400 | 0.932 | -169 | 0.68 | 26 | 0.033 | -58 | 0.905 | -167 |
| 450 | 0.941 | -170 | 0.55 | 21 | 0.029 | -61 | 0.918 | -169 |
| 500 | 0.949 | -172 | 0.46 | 18 | 0.026 | -66 | 0.931 | -170 |
| 550 | 0.961 | -173 | 0.39 | 14 | 0.024 | -68 | 0.943 | -172 |
| 600 | 0.965 | -174 | 0.33 | 11 | 0.021 | -69 | 0.947 | -173 |
| 650 | 0.969 | -176 | 0.29 | 9 | 0.019 | -74 | 0.954 | -174 |
| 700 | 0.970 | -177 | 0.25 | 6 | 0.017 | -73 | 0.960 | -175 |
| 750 | 0.974 | -177 | 0.22 | 4 | 0.016 | -73 | 0.962 | -177 |
| 800 | 0.977 | -178 | 0.20 | 2 | 0.014 | -77 | 0.965 | -177 |
| 850 | 0.979 | -179 | 0.18 | 1 | 0.012 | -79 | 0.965 | -178 |
| 900 | 0.977 | -180 | 0.16 | -1 | 0.011 | -82 | 0.968 | -179 |
| 950 | 0.978 | 180 | 0.15 | -3 | 0.010 | -80 | 0.971 | -180 |
| 1000 | 0.982 | 179 | 0.13 | -4 | 0.009 | -82 | 0.973 | 179 |
| 1050 | 0.983 | 178 | 0.12 | -6 | 0.007 | -88 | 0.974 | 178 |
| 1100 | 0.982 | 177 | 0.13 | -7 | 0.005 | -88 | 0.969 | 178 |
| 1150 | 0.982 | 177 | 0.10 | -8 | 0.005 | -83 | 0.975 | 177 |
| 1200 | 0.982 | 176 | 0.10 | -9 | 0.004 | -87 | 0.975 | 176 |
| 1250 | 0.984 | 176 | 0.09 | -11 | 0.000 | -90 | 0.972 | 176 |
| 1300 | 0.980 | 175 | 0.08 | -11 | 0.020 | -81 | 0.970 | 175 |
| 1350 | 0.978 | 175 | 0.08 | -12 | 0.001 | -111 | 0.974 | 175 |
| 1400 | 0.977 | 174 | 0.07 | -12 | 0.001 | -61 | 0.970 | 174 |
| 1450 | 0.979 | 174 | 0.07 | -11 | 0.001 | 19 | 0.971 | 173 |
| 1500 | 0.976 | 173 | 0.06 | -13 | 0.002 | 138 | 0.970 | 173 |

Table 13. S-parameter for PD54003S-E ($V_{DS} = 7.5$ V, $I_{DS} = 500$ mA)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|--------|-------|---------|-------|
| 50 | 0.805 | -165 | 13.88 | 88 | 0.025 | 1 | 0.806 | -164 |
| 100 | 0.838 | -170 | 6.74 | 81 | 0.003 | -6 | 0.80372 | -171 |
| 150 | 0.863 | -172 | 4.43 | 76 | 0.024 | -10 | 0.840 | -173 |
| 200 | 0.873 | -174 | 3.27 | 71 | 0.024 | -15 | 0.814 | -174 |
| 250 | 0.880 | -175 | 2.57 | 65 | 0.023 | -18 | 0.827 | -175 |
| 300 | 0.884 | -176 | 2.10 | 60 | 0.022 | -22 | 0.83481 | -175 |
| 350 | 0.891 | -176 | 1.75 | 56 | 0.022 | -27 | 0.845 | -175 |
| 400 | 0.901 | -177 | 1.49 | 51 | 0.020 | -28 | 0.857 | -176 |
| 450 | 0.906 | -177 | 1.27 | 47 | 0.018 | -33 | 0.863 | -176 |
| 500 | 0.914 | -178 | 1.10 | 43 | 0.017 | -35 | 0.877 | -177 |
| 550 | 0.923 | -178 | 0.97 | 39 | 0.017 | -37 | 0.881 | -177 |
| 600 | 0.927 | -179 | 0.85 | 36 | 0.015 | -36 | 0.892 | -177 |
| 650 | 0.931 | -179 | 0.76 | 33 | 0.014 | -39 | 0.902 | -178 |
| 700 | 0.934 | -180 | 0.68 | 30 | 0.013 | -38 | 0.908 | -78 |
| 750 | 0.941 | 180 | 0.62 | 27 | 0.012 | -40 | 0.914 | -179 |
| 800 | 0.944 | 179 | 0.56 | 25 | 0.012 | -47 | 0.918 | -180 |
| 850 | 0.948 | 179 | 0.51 | 22 | 0.010 | -47 | 0.920 | 180 |
| 900 | 0.949 | 178 | 0.46 | 19 | 0.009 | -42 | 0.927 | 179 |
| 950 | 0.951 | 178 | 0.43 | 17 | 0.008 | -46 | 0.933 | 178 |
| 1000 | 0.954 | 177 | 0.40 | 15 | 0.006 | -42 | 0.936 | 178 |
| 1050 | 0.955 | 177 | 0.37 | 13 | 0.007 | -36 | 0.937 | 177 |
| 1100 | 0.959 | 176 | 0.34 | 10 | 0.006 | -38 | 0.939 | 177 |
| 1150 | 0.960 | 176 | 0.32 | 9 | 0.004 | -42 | 0.942 | 176 |
| 1200 | 0.961 | 175 | 0.30 | 7 | 0.004 | -23 | 0.943 | 176 |
| 1250 | 0.965 | 175 | 0.28 | 5 | 0.004 | 0 | 0.942 | 175 |
| 1300 | 0.960 | 174 | 0.26 | 4 | 0.0036 | 2 | 0.941 | 175 |
| 1350 | 0.961 | 174 | 0.24 | 2 | 0.004 | 20 | 0.941 | 174 |
| 1400 | 0.959 | 173 | 0.23 | 1 | 0.004 | 30 | 0.941 | 173 |
| 1450 | 0.960 | 173 | 0.24 | 1 | 0.004 | 40 | 0.949 | 173 |
| 1500 | 0.959 | 172 | 0.20 | 0 | 0.003 | 50 | 0.948 | 172 |

Table 14. S-parameter for PD54003S-E ($V_{DS} = 7.5$ V, $I_{DS} = 1$ A)

| Freq (MHz) | IS11I | S11.F | IS21I | S21.F | IS12I | S12.F | IS22I | S22.F |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 0.879 | -164 | 14.04 | 88 | 0.021 | 0 | 0.828 | -168 |
| 100 | 0.879 | -172 | 6.82 | 82 | 0.020 | -5 | 0.826 | -174 |
| 150 | 0.885 | -174 | 4.50 | 78 | 0.020 | -9 | 0.832 | -175 |
| 200 | 0.887 | -175 | 3.34 | 73 | 0.020 | -11 | 0.831 | -176 |
| 250 | 0.890 | -176 | 2.65 | 68 | 0.019 | -16 | 0.844 | -177 |
| 300 | 0.894 | -177 | 2.18 | 64 | 0.019 | -18 | 0.847 | -176 |
| 350 | 0.898 | -177 | 1.82 | 60 | 0.018 | -21 | 0.857 | -177 |
| 400 | 0.907 | -178 | 1.57 | 55 | 0.017 | -21 | 0.864 | -177 |
| 450 | 0.910 | -178 | 1.35 | 51 | 0.016 | -25 | 0.866 | -177 |
| 500 | 0.914 | -179 | 1.18 | 47 | 0.015 | -29 | 0.877 | -178 |
| 550 | 0.922 | -179 | 1.04 | 44 | 0.014 | -30 | 0.887 | -178 |
| 600 | 0.926 | -180 | 0.93 | 41 | 0.014 | -30 | 0.888 | -179 |
| 650 | 0.930 | 180 | 0.84 | 38 | 0.130 | -33 | 0.897 | -179 |
| 700 | 0.934 | 179 | 0.75 | 35 | 0.012 | -33 | 0.905 | -180 |
| 750 | 0.938 | 179 | 0.68 | 32 | 0.011 | -34 | 0.907 | 180 |
| 800 | 0.940 | 178 | 0.62 | 30 | 0.010 | -33 | 0.914 | 179 |
| 850 | 0.946 | 178 | 0.57 | 27 | 0.010 | -30 | 0.913 | 179 |
| 900 | 0.944 | 177 | 0.52 | 24 | 0.009 | -27 | 0.921 | 178 |
| 950 | 0.946 | 177 | 0.48 | 22 | 0.008 | -28 | 0.928 | 177 |
| 1000 | 0.95 | 176 | 0.45 | 19 | 0.008 | -31 | 0.930 | 177 |
| 1050 | 0.949 | 176 | 0.42 | 17 | 0.006 | -26 | 0.933 | 177 |
| 1100 | 0.953 | 176 | 0.39 | 15 | 0.006 | -19 | 0.933 | 176 |
| 1150 | 0.954 | 175 | 0.36 | 13 | 0.005 | -16 | 0.937 | 176 |
| 1200 | 0.956 | 175 | 0.34 | 11 | 0.005 | -15 | 0.938 | 175 |
| 1250 | 0.957 | 174 | 0.32 | 9 | 0.004 | 3 | 0.934 | 175 |
| 1300 | 0.955 | 174 | 0.30 | 7 | 0.003 | 2 | 0.934 | 174 |
| 1350 | 0.955 | 173 | 0.28 | 6 | 0.005 | 25 | 0.937 | 174 |
| 1400 | 0.955 | 173 | 0.26 | 5 | 0.005 | 33 | 0.935 | 173 |
| 1450 | 0.957 | 172 | 0.25 | 4 | 0.005 | 31 | 0.943 | 172 |
| 1500 | 0.954 | 172 | 0.23 | 3 | 0.004 | 42 | 0.943 | 172 |

8 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

Table 15. PowerSO-10RF formed lead (Gull Wing) mechanical data

| Dim. | mm. | | | Inch | | |
|------|-------|--------|-------|-------|--------|--------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A1 | 0 | 0.05 | 0.1 | 0. | 0.0019 | 0.0038 |
| A2 | 3.4 | 3.5 | 3.6 | 0.134 | 0.137 | 0.142 |
| A3 | 1.2 | 1.3 | 1.4 | 0.046 | 0.05 | 0.054 |
| A4 | 0.15 | 0.2 | 0.25 | 0.005 | 0.007 | 0.009 |
| a | | 0.2 | | | 0.007 | |
| b | 5.4 | 5.53 | 5.65 | 0.212 | 0.217 | 0.221 |
| c | 0.23 | 0.27 | 0.32 | 0.008 | 0.01 | 0.012 |
| D | 9.4 | 9.5 | 9.6 | 0.370 | 0.374 | 0.377 |
| D1 | 7.4 | 7.5 | 7.6 | 0.290 | 0.295 | 0.298 |
| E | 13.85 | 14.1 | 14.35 | 0.544 | 0.555 | 0.565 |
| E1 | 9.3 | 9.4 | 9.5 | 0.365 | 0.37 | 0.375 |
| E2 | 7.3 | 7.4 | 7.5 | 0.286 | 0.292 | 0.294 |
| E3 | 5.9 | 6.1 | 6.3 | 0.231 | 0.24 | 0.247 |
| F | | 0.5 | | | 0.019 | |
| G | | 1.2 | | | 0.047 | |
| L | 0.8 | 1 | 1.1 | 0.030 | 0.039 | 0.042 |
| R1 | | | 0.25 | | | 0.01 |
| R2 | | 0.8 | | | 0.031 | |
| T | 2 deg | 5 deg | 8 deg | 2 deg | 5 deg | 8 deg |
| T1 | | 6 deg | | | 6 deg | |
| T2 | | 10 deg | | | 10 deg | |

Note: Resin protrusions not included (max value: 0.15 mm per side)

Figure 27. Package dimensions




Table 16. PowerSO-10RF straight lead mechanical data

| Dim. | mm. | | | Inch | | |
|------|-------|--------|-------|-------|--------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A1 | 1.62 | 1.67 | 1.72 | 0.064 | 0.065 | 0.068 |
| A2 | 3.4 | 3.5 | 3.6 | 0.134 | 0.137 | 0.142 |
| A3 | 1.2 | 1.3 | 1.4 | 0.046 | 0.05 | 0.054 |
| A4 | 0.15 | 0.2 | 0.25 | 0.005 | 0.007 | 0.009 |
| a | | 0.2 | | | 0.007 | |
| b | 5.4 | 5.53 | 5.65 | 0.212 | 0.217 | 0.221 |
| c | 0.23 | 0.27 | 0.32 | 0.008 | 0.01 | 0.012 |
| D | 9.4 | 9.5 | 9.6 | 0.370 | 0.374 | 0.377 |
| D1 | 7.4 | 7.5 | 7.6 | 0.290 | 0.295 | 0.298 |
| E | 15.15 | 15.4 | 15.65 | 0.595 | 0.606 | 0.615 |
| E1 | 9.3 | 9.4 | 9.5 | 0.365 | 0.37 | 0.375 |
| E2 | 7.3 | 7.4 | 7.5 | 0.286 | 0.292 | 0.294 |
| E3 | 5.9 | 6.1 | 6.3 | 0.231 | 0.24 | 0.247 |
| F | | 0.5 | | | 0.019 | |
| G | | 1.2 | | | 0.047 | |
| R1 | | | 0.25 | | | 0.01 |
| R2 | | 0.8 | | | 0.031 | |
| T1 | | 6 deg | | | 6 deg | |
| T2 | | 10 deg | | | 10 deg | |

Note: Resin protrusions not included (max value: 0.15 mm per side)


Figure 28. Package dimensions

Figure 29. Tube information





Figure 30. Reel information

9 Revision history

Table 17. Document revision history

| Date | Revision | Changes |
|-------------|----------|--|
| 21-Mar-2006 | 1 | Initial release. |
| 19-May-2010 | 2 | Added: <i>Table 6: Moisture sensitivity level.</i> |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2010 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

