



Features

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDA)
- Built-In Biasing Resistors
- **Lead Free/RoHS Compliant (Note 3)**
- **"Green" Device (Note 4 and 5)**


Mechanical Data

- Case: SOT-363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish - Matte Tin Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe)
- Terminal Connections: See Diagram
- Marking Information: See Diagrams & Page 3
- Ordering Information: See Page 3
- Weight: 0.006 grams (approximate)




| SOT-363 | | |
|-----------------------------|--------------|------|
| Dim | Min | Max |
| A | 0.10 | 0.30 |
| B | 1.15 | 1.35 |
| C | 2.00 | 2.20 |
| D | 0.65 Nominal | |
| F | 0.30 | 0.40 |
| H | 1.80 | 2.20 |
| J | — | 0.10 |
| K | 0.90 | 1.00 |
| L | 0.25 | 0.40 |
| M | 0.10 | 0.25 |
| α | 0° | 8° |
| All Dimensions in mm | | |

| P/N | R1 (NOM) | R2 (NOM) | MARKING |
|----------|----------|----------|---------|
| DDC122LU | 0.22K | 10K | N81 |
| DDC142JU | 0.47K | 10K | N82 |
| DDC122TU | 0.22K | OPEN | N83 |
| DDC142TU | 0.47K | OPEN | N84 |



R₁, R₂



R₁ Only

SCHEMATIC DIAGRAM

Maximum Ratings @T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|---|------------------------|----------|------|
| Supply Voltage (6) to (1) and (3) to (4) | V _{CC} | 50 | V |
| Input Voltage (2) to (1) and (5) to (4) | V _{IN} | -5 to +6 | V |
| Input Voltage (1) to (2) and (4) to (5) | V _{EBO (MAX)} | 5 | V |
| Output Current | I _C | 100 | mA |
| Power Dissipation | P _d | 200 | mW |
| Thermal Resistance, Junction to Ambient Air | R _{θJA} | 625 | °C/W |

- Notes:
1. 150mW per element must not be exceeded.
 2. Mounted on FR4 PC Board with recommended pad layout at <http://www.diodes.com/datasheets/ap02001.pdf>.
 3. No purposefully added lead.
 4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
 5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.

Electrical Characteristics

@T_A = 25°C unless otherwise specified

R1, R2 Types

| Characteristic | | Symbol | Min | Typ | Max | Unit | Test Condition |
|-------------------------|----------------------|---------------------|------------|-----|------------|------|--|
| Input Voltage | DDC122LU DDC142JU | V _{I(off)} | 0.3 0.3 | — | — | V | V _{CC} = 5V, I _O = 100μA |
| | DDC122LU DDC142JU | V _{I(on)} | — | — | 2.0 2.0 | V | V _O = 0.3V, I _O = 20mA V _O = 0.3V, I _O = 20mA |
| Output Voltage | | V _{O(on)} | — | — | 0.3V | V | I _O /I _I = 5mA/0.25mA |
| Input Current | DDC122LU DDC142JU | I _I | — | — | 28 13 | mA | V _I = 5V |
| Output Current | | I _{O(off)} | — | — | 0.5 | μA | V _{CC} = 50V, V _I = 0V |
| DC Current Gain | DDC122LU DDC142JU | G _I | 56 56 | — | — | — | V _O = 5V, I _O = 10mA |
| Gain-Bandwidth Product* | | f _T | — | 200 | — | MHZ | V _{CE} = 10V, I _E = 5mA, f = 100MHZ |

* Transistor - For Reference Only


Electrical Characteristics

@T_A = 25°C unless otherwise specified

R1- Only

| Characteristic | | Symbol | Min | Typ | Max | Unit | Test Condition |
|--------------------------------------|----------------------|----------------------|------------|------------|------------|------|--|
| Collector-Base Breakdown Voltage | | BV _{CBO} | 50 | — | — | V | I _C = 50μA |
| Collector-Emitter Breakdown Voltage | | BV _{CEO} | 40 | — | — | V | I _C = 1mA |
| Emitter-Base Breakdown Voltage | DDC122TU DDC142TU | BV _{EBO} | 5 | — | — | V | I _E = 50μA I _E = 50μA |
| Collector Cutoff Current | | I _{CBO} | — | — | 0.5 | μA | V _{CB} = 50V |
| Emitter Cutoff Current | DDC122TU DDC142TU | I _{EBO} | — — | — | 0.5 0.5 | μA | V _{EB} = 4V |
| Collector-Emitter Saturation Voltage | | V _{CE(sat)} | — | — | 0.3 | V | I _C = 5mA, I _B = 0.25mA |
| DC Current Transfer Ratio | DDC122TU DDC142TU | h _{FE} | 100 100 | 250 250 | 600 600 | — | I _C = 1mA, V _{CE} = 5V |
| Gain-Bandwidth Product* | | f _T | — | 200 | — | MHZ | V _{CE} = 10V, I _E = -5mA, f = 100MHZ |

* Transistor - For Reference Only




(150mW per element must not be exceeded).

Ordering Information (Note 6)

| Device | Packaging | Shipping |
|--------------|-----------|------------------|
| DDC122LU-7-F | SOT-363 | 3000/Tape & Reel |
| DDC142JU-7-F | SOT-363 | 3000/Tape & Reel |
| DDC122TU-7-F | SOT-363 | 3000/Tape & Reel |
| DDC142TU-7-F | SOT-363 | 3000/Tape & Reel |

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



NXX = Product Type Marking Code
 See Page 1 Diagrams
 YM = Date Code Marking
 Y = Year ex: T = 2006
 M = Month ex: 9 = September

Date Code Key

| Year | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | N | P | R | S | T | U | V | W | X | Y | Z |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.