

# FCX1053A


## SOT89 NPN medium power transistor

### Summary

$BV_{CEO} = 75V$

$R_{CE(sat)} = 78m\Omega$

$I_C = 3A$




### Description

This medium power NPN transistor, offered in the SOT89 package provides high current and low saturation voltage making it ideal for use in various driving and power management applications.


### Features

- Extremely low equivalent on-resistance;  $R_{CE(sat)} = 7.8m\Omega$  at 4.5A
- 3 Amps continuous current
- Up to 10 amps peak current
- Very low saturation voltages
- Excellent  $h_{FE}$  characteristics up to 10 amps



### Applications

- Emergency lighting circuits
- Motor driving (including DC fans)
- Solenoid, relay and actuator drivers
- DC-DC modules
- Backlight inverters
- Power switches
- MOSFET gate drivers



Pinout - top view

### Ordering information

Device	Reel size (inches)	Tape width (mm)	Quantity per reel
FCX1053ATA	7	12	1,000

### Device marking

053

# FCX1053A

## Absolute maximum ratings

Parameter	Symbol	Value	Unit
Collector-base voltage	$V_{CBO}$	150	V
Collector-emitter voltage	$V_{CEO}$	75	V
Emitter-base voltage	$V_{EBO}$	5	V
Continuous collector current <sup>(a)</sup>	$I_C$	3	A
Peak pulse current	$I_{CM}$	10	A
Power dissipation at $T_{amb} = 25^{\circ}C^{(a)}$	$P_D$	1.6	W
Linear derating factor		13	mW/ $^{\circ}C$
Power dissipation at $T_{amb} = 25^{\circ}C^{(b)}$	$P_D$	2.0	W
Linear derating factor		16	mW/ $^{\circ}C$
Operating and storage temperature range	$T_j; T_{stg}$	-55 to +150	$^{\circ}C$

## Thermal resistance

Parameter	Symbol	Value	Unit
Junction to ambient <sup>(a)</sup>	$R_{\theta JA}$	72	$^{\circ}C/W$
Junction to ambient <sup>(b)</sup>	$R_{\theta JA}$	62	$^{\circ}C/W$







### NOTES:

(a) For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.

(b) For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.

# FCX1053A

## Thermal characteristics



# FCX1053A

## Electrical characteristics (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)






Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$V_{(BR)CBO}$	150	250		V	$I_C = 100\mu\text{A}$
Collector-emitter breakdown voltage	$V_{CES}$	150	250		V	$I_C = 100\mu\text{A}$
Collector-emitter breakdown voltage	$V_{CEO}$	75	100		V	$I_C = 10\text{mA}$
Collector-emitter breakdown voltage	$V_{CEV}$	150	250		V	$I_C = 100\mu\text{A}, V_{EB} = 1\text{V}$
Emitter-base breakdown voltage	$V_{(BR)EBO}$	5	8.8		V	$I_E = 100\mu\text{A}$
Collector cut-off current	$I_{CBO}$		0.9	10	nA	$V_{CB} = 120\text{V}$
Emitter cut-off current	$I_{EBO}$		0.3	10	nA	$V_{EB} = 4\text{V}$
Collector-emitter cut-off current	$I_{CES}$		1.5	10	nA	$V_{CES} = 120\text{V}$
Collector-emitter saturation voltage	$V_{CE(sat)}$		21	30	mV	$I_C = 0.2\text{A}, I_B = 20\text{mA}^{(*)}$
			55	75	mV	$I_C = 0.5\text{A}, I_B = 20\text{mA}^{(*)}$
			150	200	mV	$I_C = 1\text{A}, I_B = 10\text{mA}^{(*)}$
			160	210	mV	$I_C = 2\text{A}, I_B = 100\text{mA}^{(*)}$
			350	440	mV	$I_C = 4.5\text{A}, I_B = 200\text{mA}^{(*)}$
Base-emitter saturation voltage	$V_{BE(sat)}$		900	1000	mV	$I_C = 3\text{A}, I_B = 100\text{mA}^{(*)}$
Base-emitter turn-on voltage	$V_{BE(on)}$		825	950	mV	$I_C = 3\text{A}, V_{CE} = 2\text{V}^{(*)}$
Static forward current transfer ratio	$h_{FE}$	270	440			$I_C = 10\text{mA}, V_{CE} = 2\text{V}^{(*)}$
		300	450	1200		$I_C = 0.5\text{A}, V_{CE} = 2\text{V}^{(*)}$
		300	450			$I_C = 1\text{A}, V_{CE} = 2\text{V}^{(*)}$
		40	60			$I_C = 4.5\text{A}, V_{CE} = 2\text{V}^{(*)}$
			20			$I_C = 10\text{A}, V_{CE} = 2\text{V}^{(*)}$
Switching times	$t_{on}$		162		ns	$I_C = 2\text{A}, I_{B1} = I_{B2} = \pm 20\text{mA}, V_{CC} = 50\text{V}$
	$t_{off}$		900		ns	$I_C = 2\text{A}, I_{B1} = I_{B2} = \pm 20\text{mA}, V_{CC} = 50\text{V}$
Transition frequency	$f_T$		140		MHz	$I_C = 50\text{mA}, V_{CE} = 10\text{V}, f = 100\text{MHz}$
Output capacitance	$C_{OBO}$		21	30	pF	$V_{CB} = 10\text{V}, f = 1\text{MHz}$

### NOTES:

(\*) Measured under pulsed conditions. Pulse width = 300 $\mu\text{s}$ . Duty  $\leq 2\%$ .


# FCX1053A

## Typical characteristics



# FCX1053A

## Package outline - SOT89



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	1.40	1.60	0.550	0.630	E1	2.13	2.29	0.084	0.090
B	0.44	0.56	0.017	0.022	e	1.50 BSC		0.059 BSC	
B1	0.36	0.48	0.014	0.019	e1	3.00 BSC		0.118 BSC	
C	0.35	0.44	0.014	0.019	H	3.94	4.25	0.155	0.167
D	4.40	4.60	0.173	0.181	L	0.89	1.20	0.155	0.167
E	2.29	2.60	0.090	0.102		-	-	-	-

**Note:** Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Streitfeldstraße 19 D-81673 München Germany	Zetex Inc 700 Veterans Memorial Highway Hauppauge, NY 11788 USA	Zetex (Asia Ltd) 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong	Zetex Semiconductors plc Zetex Technology Park, Chadderton Oldham, OL9 9LL United Kingdom
Telefon: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europe.sales@zetex.com	Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com	Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com	Telephone: (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com

For international sales offices visit [www.zetex.com/offices](http://www.zetex.com/offices)

Zetex products are distributed worldwide. For details, see [www.zetex.com/salesnetwork](http://www.zetex.com/salesnetwork)

This publication is issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contact or be regarded as a representation relating to the products or services concerned. The company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.