

# High-voltage Switching Transistor (Telephone power supply) (-400V, -0.5A)

2SA1812 / 2SA1727 / 2SA1776

**●Features**

- 1) High breakdown voltage,  $BV_{CEO} = -400V$ .
- 2) Low saturation voltage, typically  $V_{CE(sat)} = -0.3V$  at  $I_C / I_E = -100mA / -10mA$ .
- 3) High switching speed, typically  $t_f = 1\ \mu s$  at  $I_C = -100mA$ .
- 4) Wide SOA (safe operating area).

**●Packaging specifications and  $h_{FE}$** 

Type	2SA1812	2SA1727	2SA1776
Packaging	MPT3	CPT3	ATV
$h_{FE}$	PQ	PQ	PQ
Marking	AJ*	—	—
Code	T100	TL	TV2
Basic ordering unit (pieces)	3000	3000	2500

\* Denotes  $h_{FE}$ **●Electrical characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	$BV_{CBO}$	-400	—	—	V	$I_C = -50\ \mu A$
Collector-emitter breakdown voltage	$BV_{CEO}$	-400	—	—	V	$I_C = -1mA$
Emitter-base breakdown voltage	$BV_{EBO}$	-7	—	—	V	$I_E = -50\ \mu A$
Collector cutoff current	$I_{CBO}$	—	—	-1	$\mu A$	$V_{CB} = -400V$
Emitter cutoff current	$I_{EBO}$	—	—	-1	$\mu A$	$V_{EB} = -6V$
DC current transfer ratio	$h_{FE}$	82	150	270	—	$V_{CE} = -5V, I_C = -50mA$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	—	-1	V	$I_C/I_B = -100mA/-10mA$
Base-emitter saturation voltage	$V_{BE(sat)}$	—	—	-1.2	V	$I_C/I_B = -100mA/-10mA$
Transition frequency	$f_T$	—	12	—	MHz	$V_{CB} = -5V, I_E = 50mA, f = 5MHz$
Output capacitance	$C_{OB}$	—	18	—	pF	$V_{CE} = -10V, I_E = 0A, f = 1MHz$
Turn-on time	$t_{on}$	—	0.6	—	$\mu s$	$I_C = -100mA, R_L = 1.5k\Omega$
Storage time	$t_{stg}$	—	2.7	—	$\mu s$	$I_B = -I_E = -10mA$
Fall time	$t_f$	—	1	—	$\mu s$	$V_{CC} \approx -150V$

**●Absolute maximum ratings (Ta=25°C)**

Parameter	Symbol	Limits	Unit
Collector-base voltage	$V_{CBO}$	-400	V
Collector-emitter voltage	$V_{CEO}$	-400	V
Emitter-base voltage	$V_{EBO}$	-7	V
Collector current	$I_C$	-0.5 -1.0	A (DC) A (Pulse) *1
		0.5 2 1 10	W W *2 W W (Tc=25°C)
Collector power dissipation	2SA1812 2SA1727 2SA1776	$P_c$	1 1
Junction temperature	$T_J$	150	°C
Storage temperature	$T_{stg}$	-55~+150	°C

\*1 Single pulse \*2 When mounted on a 40×40×0.7mm ceramic board.

\*3 When  $t = 1.7mm$  and the foil collector area on the PC board is  $1cm^2$  or greater.

(96-609-A313)