



MJD50

HIGH VOLTAGE FAST-SWITCHING NPN POWER TRANSISTOR



- STMicroelectronics PREFERRED SALESTYPE
- HIGH VOLTAGE CAPABILITY
- SURFACE-MOUNTING TO-252 (DPAK) POWER PACKAGE IN TAPE & REEL (SUFFIX "T4")
- ELECTRICALLY SIMILAR TO TIP50

APPLICATIONS

- SWITCH MODE POWER SUPPLIES
- AUDIO AMPLIFIERS
- GENERAL PURPOSE SWITCHING AND AMPLIFIER

DESCRIPTION

The MJD50 is manufactured using Medium Voltage Epitaxial Planar technology, resulting in a rugged high performance cost-effective transistor.



ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|------------------|--|------------|------|
| V _{CB0} | Collector-Base Voltage (I _E = 0) | 500 | V |
| V _{CEO} | Collector-Emitter Voltage (I _B = 0) | 400 | V |
| V _{EBO} | Emitter-Base Voltage (I _C = 0) | 5 | V |
| I _C | Collector Current | 1 | A |
| I _{CM} | Collector Peak Current (t _p < 5 ms) | 2 | A |
| I _B | Base Current | 0.6 | A |
| I _{BM} | Base Peak Current (t _p < 5 ms) | 1.2 | A |
| P _{tot} | Total Dissipation at T _c = 25 °C | 15 | W |
| T _{stg} | Storage Temperature | -65 to 150 | °C |
| T _j | Max. Operating Junction Temperature | 150 | °C |

MJD50

THERMAL DATA


| | | | | |
|----------------|-------------------------------------|-----|------|---------------|
| $R_{thj-case}$ | Thermal Resistance Junction-case | Max | 8.33 | $^{\circ}C/W$ |
| $R_{thj-amb}$ | Thermal Resistance Junction-ambient | Max | 100 | $^{\circ}C/W$ |

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^{\circ}C$ unless otherwise specified)


| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|-----------------|--|--|----------|------|------|------|
| I_{CES} | Collector Cut-off Current ($V_{BE} = 0$) | $V_{CE} = 500 V$ | | | 0.1 | mA |
| I_{CEO} | Collector Cut-off Current ($I_B = 0$) | $V_{CE} = 300 V$ | | | 0.1 | mA |
| I_{EBO} | Emitter Cut-off Current ($I_C = 0$) | $V_{EB} = 5 V$ | | | 1 | mA |
| $V_{CEO(sus)*}$ | Collector-Emitter Sustaining Voltage ($I_B = 0$) | $I_C = 30 mA$ | 400 | | | V |
| $V_{CE(sat)*}$ | Collector-Emitter Saturation Voltage | $I_C = 1 A$ $I_B = 0.2 A$ | | | 1 | V |
| $V_{BE(on)*}$ | Base-Emitter On Voltage | $I_C = 1 A$ $V_{CE} = 10 V$ | | | 1.5 | V |
| h_{FE*} | DC Current Gain | $I_C = 0.3 A$ $V_{CE} = 10 V$ $I_C = 1 A$ $V_{CE} = 10 V$ | 30 10 | | 150 | |
| f_T | Transition Frequency | $I_C = 0.2 A$ $V_{CE} = 10 V$ $f=2MHz$ | 10 | | | MHz |
| h_{fe} | Small Signal Current Gain | $I_C = 0.2 A$ $V_{CE} = 10 V$ $f=1kHz$ | 25 | | | |

* Pulsed: Pulse duration = 300 μs , duty cycle 1.5 %


Safe Operating Area




Derating Curves




DC Current Gain




DC Current Gain




Collector-Emitter Saturation Voltage




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Collector-Base Capacitance




Switching Time Inductive Load




Switching Time Inductive Load



Switching Time Inductive Load




Switching Time Inductive Load



TO-252 (DPAK) MECHANICAL DATA

| DIM. | mm | | | inch | | |
|------|------|------|-------|-------|-------|-------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| A | 2.20 | | 2.40 | 0.087 | | 0.094 |
| A1 | 0.90 | | 1.10 | 0.035 | | 0.043 |
| A2 | 0.03 | | 0.23 | 0.001 | | 0.009 |
| B | 0.64 | | 0.90 | 0.025 | | 0.035 |
| B2 | 5.20 | | 5.40 | 0.204 | | 0.213 |
| C | 0.45 | | 0.60 | 0.018 | | 0.024 |
| C2 | 0.48 | | 0.60 | 0.019 | | 0.024 |
| D | 6.00 | | 6.20 | 0.236 | | 0.244 |
| E | 6.40 | | 6.60 | 0.252 | | 0.260 |
| G | 4.40 | | 4.60 | 0.173 | | 0.181 |
| H | 9.35 | | 10.10 | 0.368 | | 0.398 |
| L2 | | 0.8 | | | 0.031 | |
| L4 | 0.60 | | 1.00 | 0.024 | | 0.039 |
| V2 | 0° | | 8° | 0° | | 0° |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 2000 STMicroelectronics – Printed in Italy – All Rights Reserved
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco -
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>