


## VIP-3/SC/D25SUB/M

Order No.: 2315133

The illustration shows version VIP-3/SC/D50SUB/M




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2315133>

VARIOFACE module, with screw connection and male D-Subminiature pin strip, for mounting on NS 35/7.5 or NS 32, 25-pos.



### Commercial data

|                          |   |
|--------------------------|---|
| GTIN (EAN)               | <br>4 046356 312929 |
| sales group              | I501  |
| Pack                     | 1 pcs.  |
| Customs tariff           | 85369010  |
| Catalog page information | Page 307 (IF-2011)  |

### Product notes

WEEE/RoHS-compliant since:  
11/23/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

|   |             |
|---|-------------|
| Nominal voltage $U_N$                     | 125 V AC/DC |
| Max. current carrying capacity per branch | 2 A         |
| Number of positions                       | 25          |
| Width                                     | 57.4 mm     |

|   |                  |
|---|------------------|
| Height                                  | 69 mm            |
| Depth                                   | 62 mm            |
| Status display                          | No               |
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Mounting position                       | Any              |
| Standards/regulations                   | IEC 60664        |
|   | DIN EN 50178     |
|   | IEC 62103        |
| Pollution degree                        | 2                |
| Surge voltage category                  | II               |

#### Connection data

|  |                     |
|--|---------------------|
| Connection 1                           | PCB connection      |
| Connection in acc. with standard       | IEC / EN            |
| Connection method                      | Screw connection    |
| Conductor cross section solid min.     | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max.     | 4 mm <sup>2</sup>   |
| Conductor cross section stranded min.  | 0.2 mm <sup>2</sup> |
| Conductor cross section stranded max.  | 2.5 mm <sup>2</sup> |
| Conductor cross section AWG/kcmil min. | 24                  |
| Conductor cross section AWG/kcmil max  | 12                  |
| Stripping length                       | 8 mm                |
| Screw thread                           | M 3                 |
| Connection 2                           | D-SUB connection    |
| Number of positions                    | 25                  |

#### Certificates / Approvals



Certification

CSA, CUL, UL

**Accessories**

| Item                   | Designation                       | Description  |
|------------------------|-----------------------------------|--|
| <b>Cable/conductor</b> |                                   |  |
| 2302421                | CABLE D-SUB-B-B-S/.../.../...     | Shielded round cable, assembled with two D-SUB female connectors, variable cable length  |
| 2302340                | CABLE D-SUB-S/.../.../...         | Shielded round cable, assembled with one D-SUB male and one female connector, variable cable length  |
| 2305473                | CABLE-D25SUB/B/B/100/<br>KONFEK/S | Assembled, shielded circular cable, with D-SUB socket strip, 25-pos. from both sides, cable length: 1m   |
| 2305486                | CABLE-D25SUB/B/B/200/<br>KONFEK/S | Assembled, shielded circular cable, with D-SUB socket strip, 25-pos. from both sides, cable length: 2m   |
| 2305499                | CABLE-D25SUB/B/B/300/<br>KONFEK/S | Assembled, shielded circular cable, with D-SUB socket strip, 25-pos. from both sides, cable length: 3 m  |
| 2302120                | CABLE-D25SUB/B/S/ 50/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 0.5 m   |
| 2302133                | CABLE-D25SUB/B/S/100/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 1 m   |
| 2302146                | CABLE-D25SUB/B/S/150/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 1.5 m   |
| 2302159                | CABLE-D25SUB/B/S/200/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 2 m   |
| 2302162                | CABLE-D25SUB/B/S/300/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 3 m   |
| 2302175                | CABLE-D25SUB/B/S/400/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 4 m   |
| 2302188                | CABLE-D25SUB/B/S/600/<br>KONFEK/S | Round shielded cable set, with 25-pos. D-SUB female and male connectors, cable length: 6 m   |
| <b>General</b>         |                                   |  |
| 5147777                | BLUEMARK X1                       | Printers with UV technology for printing plastic labels in UniCard format.   |
| <b>Marking</b>         |                                   |  |
| 0818111                | UC-TM 4                           | UniCard materials for labeling terminal blocks using a marker groove, 120-section, can be labeled with BLUEMARK and CMS-P1-PLOTTER, color: white                                 |
| 0818085                | UC-TM 6                           | UniCard materials for labeling terminal blocks with a marker groove,80-section, can be labeled with BLUEMARK and CMS-P1-PLOTTER, color: white                                    |
| 0811862                | ZB 22:UNBEDRUCKT                  | Zack marker strip, unprinted: 4-section, for individual labeling with M-PEN, ZB-T or CMS system, sufficient for 100 terminal blocks, for a terminal width of 22 mm, color: White |

|         |                    |  |
|---------|--------------------|--|
| 0809793 | ZB 5,08:UNBEDRUCKT | Zack strip, unprinted: 10-section, for individual labeling with M-PEN, ZB-T or CMS system, sufficient for 100 terminal blocks per pack |
|---------|--------------------|--|

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;