

Current refinements (click to remove)

[Search Tips](#) 
 [Region](#) **USA** [Product Family](#) **Butt Splice, Nylon Insulated** [Text Search](#): 'BSN18-C'

Your search criteria matched only one product, shown below.


- Designed to splice two solid or stranded wires together to repair or lengthen wires
- Butted configuration provides low profile for limited space applications
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal wire stop assures proper length of insertion into terminal barrel
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486

Part Number:	BSN18-C
RoHS Compliance Status:	Compliant
Part Description:	Butt Splice 22 – 18 AWG, nylon insulated.
Product Type:	Splices
CSA Certified:	Yes
UL Listed:	Yes
Length (In.):	1.15
Angle:	straight
Max. Ins.:	.115
Panduit Color Code:	Red
Tool:	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
Wire Range:	22 – 18 AWG
Wire Range (mm ²):	0.5 – 1.0
Min. Order UOM:	PC
Min. Order Qty.:	100
BOM Qty. (# of Pkgs.)	
Add to My Catalog	

 Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.