

CRIMPSET 6

Order No.: 1202072



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1202072>

Assortment box, metal, filled with ferrules acc. to DIN 46228-4:
1990-09, 500 pces. AI 0.25-6 YE, AI 0,34-6 TQ, AI 0.5-8 WH, AI
0.75-8 GY, AI 1-8 RD, AI 1.5-8 BK, 300 pces. AI 2.5-8 BU, 200 pces.
AI 4-10 GY, 100 pces. AI 6-12 YE

Commercial data

GTIN (EAN)	4017918017699
sales group	C302
Pack	1 pcs.
Customs tariff	82060000
Weight/Piece	2.8823 KG
Catalog page information	Page 669 (CL-2009)

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data

General

Length (b)	206 mm
Height	48 mm
Width (a)	357 mm
Base element material	Metal

Certificates / Approvals

Certification

GOST

Article Sets

Item	Designation	Description
Allgemein		
3200014	AI 0,5 - 8 WH	Ferrule, Length: 14 mm, Color: white
3200519	AI 0,75- 8 GY	Ferrule, Length: 14 mm, Color: gray
3200030	AI 1 - 8 RD	Ferrule, Length: 14 mm, Color: red
3200043	AI 1,5 - 8 BK	Ferrule, Length: 14 mm, Color: black
3200522	AI 2,5 - 8 BU	Ferrule, Length: 14 mm, Color: blue
3200535	AI 4 -10 GY	Ferrule, Length: 17 mm, Color: gray
3200548	AI 6 -12 YE	Ferrule, Length: 20 mm, Color: yellow
1204436	CRIMPFOX UD 6	Crimping pliers, for ferrules in accordance with DIN 46228-1: 1992-08 and DIN 46228-4: 1990-10
1204384	QUICK WIREFOX 6	Stripping tool for cables with PVC insulation, stripping range: 0.08 to 6 mm ² , wire cutting up to 6 mm ² flexible or 4 mm ² rigid

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;