

Current refinements (click  to remove)

[Search Tips](#) 
 [Region](#) **USA**  [Product Family](#) **Code Conductor, One-Hole, Standard Barrel with Window Lug**  [Text Search](#): 'LCA4-14-L'

For Use with Stranded Copper Conductors

- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Inspection window to visually assure full conductor insertion
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV\*\* and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- UL Listed and CSA Certified for wide wire range-taking capability when crimped with *PANDUIT*® *Uni-Die*™ Dieless Crimping Tools‡
- **Tested by Telcordia – meets NEBS Level 3**
- American Bureau of Shipping Approved




**Related Products**

- [Contour Crimp™ Control...](#)
- [Die Type, Manual, Crimping Tool CD-720 Crimping Dies](#)
- [Die Type, Manual Hydraulic, 14 Ton,...](#)
- [Die Type, Remote Hydraulic, 14 Ton,...](#)
- [Die Type, Battery Powered Hydraulic...](#)
- [More...](#)

|                          |  |
|--------------------------|--|
| Part Number:             | LCA4-14-L  |
| RoHS Compliancy Status:  | Compliant  |
| Part Description:        | One-hole, standard barrel with window lug, #4 – #3 AWG STR, #2 AWG SOL wire, 1/4" stud hole. |
| Product Type:            | Compression Connectors - Lugs  |
| CSA Certified:           | Yes  |
| UL Listed:               | Yes  |
| Length (In.):            | 1.63   |
| Length (mm):             | 41.4   |
| Copper Conductor Size:   | #4 – #3 AWG STR, #2 AWG SOL  |
| Stud Hole Size (In.):    | 1/4  |
| Tongue Width (In.):      | .55  |
| Barrel Length (In.):     | .81  |
| Angle:                   | Straight   |
| Clearance:               | .37  |
| Figure No.:              | 1  |
| Panduit Color Code:      | Gray   |
| Panduit Die Index No.:   | P29  |
| Tongue Thickness:        | .09  |
| Tongue Type:             | Standard   |
| Tongue Width (mm):       | 14.0   |
| Wire Range (mm²):        | 25   |
| Wire Strip Length (In.): | 7/8  |
| Min. Order UOM:          | PC   |
| Min. Order Qty.:         | 1  |
| Burndy Die Index No.:    | 8  |
| T&B Die Index No.:       | 29   |
| BOM Qty. (# of Pkgs.)    |  |

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|  |  |
|--|--|
| Material                                       | High Conductivity Seamless Copper Tube   |
| Plating  | Electro-Tin  |
| Wire Size                                      | 4 AWG, 3 AWG & 2 SOL   |
| Wire Type                                      | Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric   |
| Wire Strip Length                              | 7/8 in.  |
| Stud Size                                      | 1/4 in.  |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C  |
| C.S.A Certified Wire Connector                 | Yes  |
| Panduit Color Code on Barrel                   | GRAY   |
| Panduit Die Index No. on Barrel                | P29  |
| Alternate Industry Die Index No. ( ) on Barrel | (8)  |



|     |      |     |     |   |   |  |
|-----|------|-----|-----|---|---|--|
|     |      |     |     |   | <b>PANDUIT CORP. TINLEY PARK, ILLINOIS</b>          |  |
|     |      |     |     |   | LCA4-14-L<br>Copper Lug - One-Hole, Standard Barrel |  |
| 01  | 2/03 | SAC | PWS | EXTENDED WIRE RANGE AND UPDATED STAMPS AND MARKINGS | 10543   |  |
| REV | DATE | BY  | CHK | DESCRIPTION   | ECN   | SCALE N/A DRAWING NO / CAD FILE LCA4-14-CUST |