



Datasheet
Quick Disconnects [Overview](#)

[[Home](#) > [Products](#) > [Disconnects](#) > [Datasheet](#)]

19007-0009



Flag InsulKrimp® Quick Disconnect, Female, for 18-22 (0.80-0.35) Wire, Box, Tab 4.75mm (.187") x 0.51mm (.020")

[View all parts in series 19007](#)
[Email this page](#)
[Samples](#)
[Distributor Stock](#)

Status	Active
Type	Quick Disconnect
Product Name	InsulKrimp™
Orientation	Flag
Gender	Female
Tab Width	4.75mm (.187")
Tab Thickness	0.51mm (.020")
Wire Size [AWG]	18, 20, 22
Wire Size [mm²]	0.35 - 0.80
Wire Insulation Diameter	4.44mm (.175") max.
Barrel	Closed

PHYSICAL

Insulation	Nylon (PA)
Insulation Color	Red
Flammability	UL 94V-2
Contact	Brass (CuZn)
Plating	Tin (Sn)
Lock to Mating Part	None
Polarized to Mating Part	No
Vibration Support	No
Voltage-max [volts]	600V
Temperature Range	-65°C to +105°C

REFERENCE

Packaging	Box
UL File Number	E79133
CSA File Number	LR61836

**This part is
ELV and RoHS
COMPLIANT**

ENVIRONMENT

RoHS Compliant	Yes
----------------	-----

Related Products

APPLICATION TOOLING		
Region	Description	Product Number
Europe, Americas	Hand Crimp Tool	64001-4100
Europe, Americas	Crimp Head for the AT-200 Pneumatic Hand Tool	64005-4100

990 Catalog Page	U-5
Molex Series	19007
Old Part Number	AA-2222

For all product dimensions, please refer to Drawing (PDF).

© Copyright 2005 Molex Incorporated