


VS-04-BUB-FK-F/IP67


Order No.: 1653867



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1653867>

USB socket insert, 4-pos., socket USB type B on flat-ribbon cable terminal strip, pitch 2.54, for the Freenet system in the panel mounting frame, IP20 terminal outlet, 19" patch panel and service interface

Commercial data

GTIN (EAN)	 4 017918 970192
Note	Made-to-order
sales group	D531
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 426 (PC-2011)

Product notes

WEEE/RoHS-compliant since:
09/20/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Mechanical characteristics

Number of positions	4
Insertion/withdrawal cycles	≥ 1000
Connection method	Flat-ribbon cable connection, pitch 2.54 mm
Ambient temperature (operation)	-15 °C ... 65 °C

Material data

Inflammability class acc. to UL 94	V0
Housing material	PC
Contact carrier material	Thermoplastic
Contact material	Copper alloy
Contact surface material	Gold over nickel
Degree of protection	IP20

Electrical characteristics

Rated voltage (III/3)	30 V
Rated current	1 A
Insulation resistance	≥ 1 GΩ
Transmission characteristics (category)	USB 2.0


Accessories

Item	Designation	Description
1653744	VS-A-F-IP67	Panel mounting frame, IP67, for Freenet system, for round panel cutout, with grommet, without mounting screws, color: gray


Diagrams/Drawings

Schematic diagram

Pin	USB B
1	GND
2	
3	Shield
4	
5	D+
6	D-
7	Shield
8	
9	VBUS
10	



Contact assignment



Pin assignment socket USB, type B

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;