



5	Molded PVC Gray-White	
4	Molded PVC Gray-White	
3	USB 2.0 Cable, UL Style, 1 Twisted Pair 28AWG and 2C 24AWG, Braid Shielding with Drain Wire, OD 4.5mm, Jacket Gray-White	
2	USB B Male, 2.0, Gold Plating 30u on contacts, white insulator, short A pierce type	1 set
1	USB A Male, 2.0, Gold Plating, 30 u on contacts, white insulator, short A pierce type	1 set
No.	Description	QTY

PIN ASSIGNMENT		
P1	P2	
1	1 RED	24#
2	2 WHITE	
3	3 GREEN	
4	4 BLACK	24#
SHIELD	SHIELD+BRAID	

TOLERANCES UNLESS OTHERWISE STATED		TITLE		EMERSON Network Power	
0.5 - 5	= ± 0.2	USB A-B Cable, Male -Male		CONNECTIVITY SOLUTIONS AIM-CAMBRIDGE	
5 - 30	= ± 0.4	PART NO	DRAWN	DATE	
30 - 120	= ± 0.6	30-3007-6		CHECKED	DATE
120 - 315	= ± 1.0	SCALE	REV	PRC	
315 - 1000	= ± 1.6	DIMENSIONS ARE IN INCHES		APPROVED	DATE
1000-2000	= ± 2.4				