



5	Molded PVC Gray-White	
4	Molded PVC Gray-White	
3	USB 2.0 Cable, UL Style, 1 Twisted Pair 28AWG and 2C 24AWG, Braid Shielding with Drain Wire, OD 4.5mm, Jacket Gray-White	
2	USB B Male, 2.0, Gold Plating 30u on contacts, white insulator, short A pierce type	1 set
1	USB A Male, 2.0, Gold Plating, 30 u on contacts, white insulator, short A pierce type	1 set
No.	Description	QTY

PIN ASSIGNMENT		
P1	P2	
1	1 RED	24#
2	2 WHITE	
3	3 GREEN	
4	4 BLACK	24#
	SHIELD	SHIELD+BRAID

TOLERANCES UNLESS OTHERWISE STATED		TITLE USB A-B Cable, Male -Male			
0.5 - 5 = ± 0.2		PART NO	DRAWN	DATE	CONNECTIVITY SOLUTIONS AIM-CAMBRIDGE
5 - 30 = ± 0.4		30-3007-6			
30 - 120 = ± 0.6		CHECKED	DATE		
120 - 315 = ± 1.0		SCALE	REV	PRC	
315 - 1000 = ± 1.6		DIMENSIONS ARE IN INCHES		APPROVED	DATE
1000-2000 = ± 2.4					