

This document was generated on 06/16/2010

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0015247040		
Status:	Active		
Overview:	minifit bmi		
Description:		Mini-Fit BMI™ Receptacle Header, Dual Row, Vertical, with	
Description.		Post 2.54µm (100µ") Tin (Sn), UL 94V-2, 4 Circuits	
	Shap-in Flastic Feys,	$r_{051} = 2.54 \mu m (100 \mu) r_{111} (51), OL 94 v - 2, 4 Circuits$	Photo I I
Deserverter			
Documents:		Draduct Or a silication DO EFEC 000 (DDE)	The first
<u>3D Model</u>		Product Specification PS-5556-002 (PDF)	010
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Series
Agonov Cortifi	iantian		image - Reference only
Agency Certification		LR19980	
UL			EU RoHS China RoHS
UL		E29179	ELV and RoHS
General			Compliant
		PCP Pacantacian	REACH SVHC
Product Family		PCB Receptacles	
Series		42385	Contains SVHC: No
Application		Board-to-Board	Halogen-Free
Comments		Solder Type With Pegs	Status
MolexKits		Yes	Not Reviewed
Overview		<u>minifit_bmi</u>	Need more information on product
Product Name		Mini-Fit BMI™	environmental compliance?
Physical			Email productcompliance@molex.com
		4	For a multiple part number RoHS Certificate
Circuits (Loaded)		4	Compliance, click here
Color - Resin		Natural	Compliance, <u>click here</u>
Durability (mating cycles max)		30	Please visit the Contact Us section for any
Flammability		94V-2	non-product compliance questions.
Glow-Wire Compliant		No	
Guide to Mating Part		Yes	1
Keying to Mating Part		None	
Lock to Mating Part		None	
Material - Metal		Brass	Search Parts in this Series
Material - Plating Mating		Tin	<u>42385</u> Series
Material - Resin		Nylon	
Number of Rows		2	Mates With
Orientation		Vertical	42475 Panel Mount Plug, 42404 Vertical
PCB Locator		Yes	Header, <u>42440</u> Vertical Header, <u>43879</u>
PCB Retention		Yes	Vertical Header, <u>44068</u> Vertical Header
PCB Thickness Recommended (in)		0.070 ln	
PCB Thickness Recommended (iii) PCB Thickness Recommended (iiii)		1.80 mm	
		Tray	
Packaging Type		0.165 ln	
Pitch - Mating Interface (in)			
Pitch - Mating Interface (mm)		4.20 mm	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Surface Mount Co		No	
Temperature Rang		-40°C to +105°C	
Termination Interfa	ace: Style	Through Hole	
Electrical			
Current - Maximum per Contact		9A	
Grounding to PCB		No	
Voltage - Maximum		600V	
-			
Solder Proces			
Duration at Max E	Dragona Tamparatura (agaa)		

Duration at Max. Process Temperature (seconds)

5

Lead-free Process Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	Wave Capable (TH only) 1 240			
Material Info Old Part Number	A-42385-04A1			
Reference - Drawing Numbers				
Packaging Specification	PK-42385-999			
Product Specification	PS-5556-002			
Sales Drawing	SDA-42385-*			
Test Summary	TS-5556-002			

## This document was generated on 06/16/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION