

Thermofit Molded Parts Specification Control Drawing

NOTES

- 1. All dimensions are in $\frac{\text{incres}}{[\text{millimeters}]}$
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- 3. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.

 4. Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.





202D211 thru 299

Boot, Straight With Lip

Part Number :

Description :

TABLE OF DIMENSIONS													
PART NUMBER	Н		J			P	JO	R	s	Т	U	HW	JW
	Min	Max	Min -3,-4,-25	Min -5-6-8	Max	±10%	±10%	Ref	Ref	Ref	±10%	±20%	±20%
	a	ь	-130 G	-568 -12100 CI	ь	b	ь	ь	ь	ь	b	ь	ь
202D211	.88	.45	.88	<u>.55</u>	.25	4.17	3.40	<u>.46</u>	. <u>12</u>	. <u>04</u>	.56	<u>.06</u>	. <u>045</u>
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[105,9]	[86,4]	[11,7]	[3,0]	[1,0]	[14,2]	[1,52]	[1,14]
202D221	1.01	.59	1.01	.63	.29	4.77	3.88	.48	.12	.04	.59	<u>.06</u>	. <u>045</u>
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[121,2]	[98,6]	[12,2]	[3,0]	[1,0]	[15,0]	[1,52]	[1,14]
202D232	1.16	.74	1.16	.72	.33	<u>5.46</u>	4.44	.48	.12	.04	.61	<u>.07</u>	. <u>045</u>
	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[138,7]	[112,8]	[12,2]	[3,0]	[1,0]	[15,5]	[1,78]	[1,14]
202D242	1.34	.90	1.34	.84	.38	6.28	<u>5.15</u>	<u>.48</u>	. <u>12</u>	.04	.62	<u>.07</u>	. <u>045</u>
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[159,5]	[130,8]	[12,2]	[3,0]	[1,0]	[15,7]	[1,78]	[1,14]
202D253	1.47	1.16	1.47	.91	<u>.41</u>	7.00	<u>5.60</u>	<u>.55</u>	. <u>12</u>	. <u>065</u>	<u>.71</u>	<u>.08</u>	. <u>045</u>
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[177,8]	[142,2]	[14,0]	[3,0]	[1,65]	[18,0]	[2,0]	[1,14]
202D263	1.72	1.34	1.72	1.07	<u>.48</u>	<u>8.00</u>	6.42	<u>.60</u>	.12	. <u>065</u>	.78	.08	. <u>045</u>
	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[203,2]	[163,1]	[15,2]	[3,0]	[1,65]	[19,8]	[2,0]	[1,14]
202D274	1.97	1.62	1.97	1.24	.56	8.00	6.21	<u>.60</u>	.12	. <u>065</u>	.82	.09	. <u>055</u>
	[50,0]	[41,2]	[50,0]	[31,5]	[14,2]	[203,2]	[157,7]	[15,2]	[3,0]	[1,65]	[20,8]	[2,3]	[1,40]
202D285	2.47	1.85	2.47	1.54	<u>.69</u>	<u>8.00</u>	6.03	<u>.63</u>	12	.08	.92	.10	. <u>055</u>
	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[203,2]	[153,2]	[16,0]	[3,0]	[2,0]	[23,4]	[2,5]	[1,40]
202D296	2.73	2.35	2.73	1.70	<u>.77</u>	8.00	5.64	<u>.63</u>	12	.08	.93	.10	. <u>055</u>
	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[203,2]	[143,3]	[16,0]	[3,0]	[2,0]	[23,6]	[2,5]	[1,40]
202D299	3.22	2.64	3.22	2.01	<u>.90</u>	<u>8.00</u>	5.45	<u>.63</u>	12	.08	1.23	.10	. <u>055</u>
	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[203,2]	[138,4]	[16,0]	[3,0]	[2,0]	[31,2]	[2,5]	[1,40]

300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: N1 Date: 29MAR11 Part Number :

202D211 thru 299


Part Number : 202D211 thru 299 Description: Boot, Straight With Lip

Description: Boot, Straight With Lip

Thermofit Molded Parts Specification Control Drawing

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-3	Polyolefin, Semi-rigid	RT-301	/42; /86; /180	S-1017; S-1048; S-1030	Adhesive				
-4	Polyolefin, Flexible	RT-1304	/42; /86; /180	S-1017; S-1048; S-1030	Adhesive				
-5	Neoprene	RT-501	/42	S-1017					
-6	Silicone	RT-602	N/A						
-8	Polyolefin, Space	RT-1308	N/A						
-12	*VITON, Flexible	RT-1312	N/A						
-25	Elastomer, Fluid Resistant	RT-1325	/42,/86	S-1017;S-1048	Adhesive				
-130	Polyolefin, Flexible	RW-2008	/42; /86	S-1017; S-1048	Adhesive				
-100	Polyolefin, Semi-flexible ZEROHAL™	RT-1323	/86; /184	S-1048; S-1030	Adhesive				

*VITON is a Registered Trademark of Dupont



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION



Revision: N1 Date: 29MAR11 Part Number : 202D211 thru 299 Description : Boot, Straight With Lip

CAD FILE MP97163

Downloaded from Elcodis.com electronic components distributor