




FSD75-8-DSL10



- Polypropylene insulation housing available in DIN standard colors in strips of 50
- Continuously molded design provides consistent placement of ferrules in tool to ensure fast, reliable terminations
- Available in #20 – #14 AWG featuring a seamless barrel design to contain loose wire strands for superior terminations
- Designed for use with the Semiautomatic Ferrule Crimping Tool CT-1000 for medium volume applications

▪ Part Number	FSD75-8-DSL10
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Insulated ferrules, on strip, single wire DIN end sleeve.
▪ Color	White
▪ Length (In.)	.60
▪ Length (mm)	15.2
▪ CE Compliant	No
▪ CE Marking	No
▪ Inside Diameter (In.)	.04
▪ Inside Diameter (mm)	1.0
▪ Max. Wire Insul. Dia. (In.)	.10
▪ Pin Length (In.)	.31
▪ Pin Length (mm)	8.0
▪ Pricing Description	Insulated Ferrules on Strips, single wire, 20 AWG (.50mm), .31"(8.0mm) pin length, white DIN end sleeve
▪ Tool	CT-1000
▪ Wire Range	20 AWG
▪ Wire Range (mm ²)	0.50
▪ Wire Strip Length (In.)	13/32
▪ Wire Strip Length (mm)	10