



PLT1.5M-M0



- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation

| | |
|-------------------------------------|---|
| ▪ Part Number | PLT1.5M-M0 |
| ▪ RoHS Compliancy Status | Compliant |
| ▪ Part Description | Cable Tie, 5.6", Miniature cross section |
| ▪ Product Type | Cable Ties |
| ▪ Material | Weather Resistant Nylon 6.6 |
| ▪ Color | Black |
| ▪ CSA Certified | Yes |
| ▪ UL Listed (File #E56854) | Yes |
| ▪ UL Recognized (File #E56854) | Yes |
| ▪ Length (In.) | 5.6 |
| ▪ Length (mm) | 142 |
| ▪ Width (In.) | .098 |
| ▪ Width (mm) | 2.5 |
| ▪ CE Compliant | Yes |
| ▪ Cross Section | Miniature |
| ▪ Head Height (In.) | .154 |
| ▪ Head Height (mm) | 3.9 |
| ▪ Head Width (In.) | .180 |
| ▪ Head Width (mm) | 4.6 |
| ▪ Locking Style | Locking |
| ▪ Material Flammability Rating | UL 94V-2 |
| ▪ Max. Bundle Diameter (In.) | 1.25 |
| ▪ Max. Bundle Diameter (mm) | 32 |
| ▪ Max. Continuous Use Temperature | 185°F (85°C) |
| ▪ Min. Loop Tensile Strength (Lbs.) | 18 |
| ▪ Min. Loop Tensile Strength (N) | 80 |
| ▪ Pricing Description | Cable Tie, 5.6"L (142mm), Miniature, Weather Resistant, Black |

| | |
|-------------------------|----------------------------------|
| ▪ Thickness (In.) | .043 |
| ▪ Thickness (mm) | 1.1 |
| ▪ Tool | GTS, GTSL, GS2B, PTS, PPTS, STS2 |
| ▪ Min. Order UOM | PC |
| ▪ Min. Order Qty. | 1000 |
| ▪ BOM Qty. (# of Pkgs.) | |

