



## PLT2M-M0



- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation

▪ Part Number	PLT2M-M0
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Cable Tie, 8.0", Miniature cross section
▪ Product Type	Cable Ties
▪ Material	Weather Resistant Nylon 6.6
▪ Color	Black
▪ CSA Certified	Yes
▪ UL Listed (File #E56854)	Yes
▪ UL Recognized (File #E56854)	Yes
▪ Length (In.)	8.0
▪ Length (mm)	203
▪ Width (In.)	.098
▪ Width (mm)	2.5
▪ CE Compliant	Yes
▪ Cross Section	Miniature
▪ Head Height (In.)	.154
▪ Head Height (mm)	3.9
▪ Head Width (In.)	.180
▪ Head Width (mm)	4.6
▪ Locking Style	Locking
▪ Material Flammability Rating	UL 94V-2
▪ Max. Bundle Diameter (In.)	2.00
▪ Max. Bundle Diameter (mm)	51
▪ Max. Continuous Use Temperature	185°F (85°C)
▪ Min. Loop Tensile Strength (Lbs.)	18
▪ Min. Loop Tensile Strength (N)	80
▪ Pricing Description	Cable Tie, 8.0"L (203mm), Miniature, Weather Resistant, Black

▪ Thickness (In.)	.043
▪ Thickness (mm)	1.1
▪ Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1000
▪ BOM Qty. (# of Pkgs.)	

