THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PROOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP. FEED DIRECTION **REEL** DIA. REF. .500 [12.7] DIA. $\pm .005 [\pm 0.15]$ **HOLE THRU** .157 [4.0] - .079 [2.0] $\pm .005 [\pm 0.15]$ $\pm .005 [\pm 0.15]$.059 [1.5] DIA. PITCH -.413 [10.5] HOLE (TYP.) REF. 00000 .787 $\pm .005$ [20.0] $[\pm 0.15]$ WIDTH 000000000000000000000 — .016 [0.4] FEED DIRECTION REF. NOTES: TAPE AND REEL SPECIFICATIONS: 1 TAPE: MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER ANSI/EIA-481 STANDARD 1.732 [44.0] WIDE; 1.260 [32.0] PITCH KEYSTONE ELECTRONICS CORP. 2. REEL: www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900 13.0 [330.2] DIA. 200 PIECES OF PART NAME PART NO. 1082 PER REEL. 20mm SM COIN CELL HOLDER ON TAPE MATERIAL AS NOTED FINISH DRN BY NT 3.19.09 AS NOTED APP'D

TOLERANCES

ANGULAR ± 1°

UNLESS OTHERWISE SPECIFIED

DECIMAL

REV.

INCH

 $\pm .015 [\pm 0.38]$

CODE

C/M

DWG NO.

1082TR

DESCRIPTION

DATE