


Seeloc® Washers





Vibration-Resistant, Self-Sealing Washers

Seeloc® Washers are self-sealing, vibration-resistant washers, each having a silicone rubber section, molded and bonded to a stainless steel formed washer. These washers are designed for use with regular screws or bolts for sealing panels and cases having large clearance holes or slots, and can also be used to seal openings of protrusions as shown above. Upon tightening, a seal is formed under the head of the screw or bolt as well as around the periphery of the washer face.

Part No.	For Thread Size	Washer O. D.
75601	#6	1/2"
75801	#8	1/2"
75101	#10	1/2"
75602	#6	1"
75802	#8	1"
75102	#10	1"
75082	1/4	1"
75107	5/16	1"
75122	3/8	1"
75142	7/16	1"
75162	1/2	1"
75603	#6	1-1/2"
75803	#8	1-1/2"
75103	#10	1-1/2"
75083	1/4	1-1/2"
75108	5/16	1-1/2"
75123	3/8	1-1/2"
75143	7/16	1-1/2"
75163	1/2	1-1/2"

Specifications

Material:	Standard Seeloc® washer is stainless steel, but can be made in carbon steel, nickel-plated brass, aluminum, etc. Silicone rubber is standard.
Temp. Range:	-160°F to +500°F
Pressure Range:	exceeds 100 psi internal and external
Shelf Life:	in excess of 25 years
Resistant to:	salt water, acids, weather, sunlight, ozone, etc.
Installation:	Seeloc® washers are installed on bolts or screws in the same manner as regular washers. The rubber section should always face the panel.



APM HEXSEAL® Sealing Specialists



44 Honeck Street, Englewood, NJ 07631-9917 • Tel (201) 569-5700 • E-mail: info@apmhexseal.com • www.apmhexseal.com

PRINTED IN U.S.A

Specifications

Material:	Standard Seeloc® washer is stainless steel, but can be made in carbon steel, nickel-plated brass, aluminum, etc. Silicone rubber is standard.
Temp. Range:	-160°F to 500°F
Pressure Range:	exceeds 100 psi internal and external
Shelf Life:	in excess of 25 years
Resistant to:	salt water, acids, weather, sunlight, ozone, etc.
Installation:	Seeloc® washers are installed on bolts or screws in the same manner as regular washers. The rubber section should always face the panel.

PART NO.	FOR THREAD SIZE	WASHER O.D.
75601	#6	1/2"
75801	#8	1/2"
75101	#10	1/2"
75602	#6	1"
75802	#8	1"
75102	#10	1"
75082	1/4	1"
75107	5/16	1"
75122	3/8	1"
75142	7/16	1"
75603	1/2	1"
75603	#6	1-1/2"
75803	#8	1-1/2"
75103	#10	1-1/2"
75083	1/4	1-1/2"
75108	5/16	1-1/2"
75123	3/8	1-1/2"
75143	7/16	1-1/2"
75163	1/2	1-1/2"



A	CAD COMPUTER GENERATED				12-23-02
REV.	DESCRIPTION				DATE
MAXIMUM AND MINIMUM MEASUREMENTS ARE STATED DIRECTLY ON EACH DIMENSION.		TITLE: SEELOC ® VIBRATION-RESISTANT, SELF-SEALING WASHERS	ENG.		
MAT'L:			DWN.		
AS NOTED			CHKD.		
FINISH:		APM-HEXSEAL CORPORATION	SCALE	DWG. NO.	SW-100
AS NOTED					

THIS DRAWING COVERS PROPRIETARY ITEM AND IS THE PROPERTY OF THE APM-HEXSEAL CORPORATION.
THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF THE APM-HEXSEAL CORPORATION.