

# M-5400 / M-5410 / M-5450

## WheelMouse optical



### Facts & Features

- Optical sensor for precise movement of the mouse pointer
- PC- and MAC-compatible due to USB interface
- Precise performance with 1000 dpi resolution
- Easy scrolling with the PowerWheel
- Elegant design, ideally suited for right- and left-handed users
- Connection and disconnection during operation with USB connector
- Adapter for PS/2 interface

### Delivery Volume

- 1 WheelMouse optical
- 1 Adapter for PS/2 interface
- 1 Printed manual

### Approvals

- FCC, cURus, GS, CE, GOST-R
- Microsoft Windows™ XP

### System requirements

- USB or PS/2 interface

### Technical data

- Number of buttons:  
3 buttons
- Cable length:  
approx. 1.80 m
- Weight:  
ca. 135 g (without packaging)  
ca. 155 g (with packaging)
- Dimensions in mm:  
approx. 121 x 63 x 38 mm (without packaging)  
approx. 136 x 89 x 48 mm (with packaging)
- Current consumption:  
typ. 30 mA
- Connection:  
USB (PS/2 via adapter)
- Resolution:  
1000 dpi
- Frame rate:  
1500 per second
- Storage temperature:  
-15 °C to 60 °C
- Operating temperature:  
0 °C to 40 °C
- Packaging Unit:  
40 mice per master carton  
27 master cartons per pallet

## Order description

<i>Order number</i>	<i>Housing colour</i>	<i>EAN-Code</i>
M-5400	light grey	4025112056789
M-5450	black	4025112056994
M-5410	silver / black	4025112069819

Cherry GmbH  
Cherrystraße  
91275 Auerbach/Opf.  
Germany

Phone: +49 9643 18-0  
Internet: [www.cherry.de](http://www.cherry.de)  
[www.cherrycorp.com](http://www.cherrycorp.com)

Sales: +49 1805 243779 (01805-Cherry)  
E-Mail: [sales@cherry.de](mailto:sales@cherry.de)  
Fax: +49 9643 18-1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 Cherry GmbH, Last update: 02.06.2008\_V14

