



MICRO SWITCH
 FREEPORT, ILLINOIS, U.S.A.
 A DIVISION OF HONEYWELL
 FED. MFG. CODE 91926

SWITCH-ENCLOSED

CATALOG LISTING
DTE6-2RN80

DTE6-2RN80

DRAWING NUMBER

ISSUE 6

BP 14FEB06

REVISED X86499-DTE6

REVISIONS

A	072861	DATE	8/25/82
B	73296	BY	7/23/84
C	77486	BY	7/23/84
D	001899	BY	10/18/85
E	001896	BY	11/18/85

APR 89

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS OPERATING FORCE ----- 20 - 48 OZ DIFFERENTIAL FORCE ----- RELEASE FORCE ----- 6 OZ MIN PRETRAVEL ----- DIFFERENTIAL TRAVEL ----- .060 MAX OVERTRAVEL ----- .125 MIN FREE POSITION ----- SWITCH - BASIC REPLACEMENT - DT-2R3-A7		ELECTRICAL DATA CONTACT ARRANGEMENT D P D T L59 10A 125 OR 250 VAC 0.3A 125 VDC, 0.15A 250 VDC RJ	SCALE FULL DO NOT SCALE PRINT UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (.0) ± .030 TWO PLACE (.00) ± .015 THREE PLACE (.000) ± .005 ANGLES ± THIRD ANGLE PROJECTION WEIGHT .56 LB
---	--	--	--

- NOTES**
- 1 - 4-40 UNC X .125 REF TERMINAL SCREW & LOCKWASHER (6)
 - 2 - ROLLER MAY BE SET AT ANY POSITION AROUND AXIS OF PLUNGER
 - 3 - SEAL RATING : NEMA 1,3 IP 54