

OP-AR62

ISSUE 2

REPLACES

OP-AR62

ISSUE 2

REVISIONS

A 20.9.1982

B 28.10.82

C 01.10.84

D 01.10.84

E 01.10.84

F 02.10.84

G 02.10.84

H 02.10.84

I 02.10.84

J 02.10.84

K 02.10.84

L 02.10.84

M 02.10.84

N 02.10.84

O 02.10.84

P 02.10.84

Q 02.10.84

R 02.10.84

S 02.10.84

T 02.10.84

U 02.10.84

V 02.10.84

W 02.10.84

X 02.10.84

Y 02.10.84

Z 02.10.84

CATALOG LISTING

MICRO SWITCH

SWITCH-ENCLOSED

OP-AR62

FED. MFR. CODE 91929

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

ROLLER LEVER ADJUSTABLE THRU 360°

ROLLER LEVER MAY BE POSITIVELY LOCKED AT INTERVALS OF APPROX. 0.2° (1980 POSITIONS)

RIGHT HAND CLOCKWISE ROTATION

(2) MOUNTING HOLE IN OPPOSITE WALL.

0.750 REF. DIA. X .250 REF. WIDE HARDENED STEEL ROLLER.

CHARACTERISTICS

OPERATING FORCE ----- 1/2-1 1/4 LBS

RELEASE FORCE ----- 1/4 LB. MIN.

PRETRAVEL ----- .219 MAX. 8°

DIFFERENTIAL TRAVEL ----- .007 MAX. 1/4°

OVERTRAVEL ----- DO NOT OVERTRAVEL MORE THAN 90°

BASIC SWITCH REPLACEMENT BZ-2R-P4

ELECTRICAL DATA

CONTACT ARRANGEMENT S. P. D. T.

-L96-

1/2 A-125, 250, OR 480 VAC

1/2 A-125 VDC; 1/4 A-250 VDC

1/8 HP-125 VAC; 1/4 HP-250 VAC

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.018
THREE PLACE	(.000)	±.008

WEIGHT

NOTE-

1-(6) MOUNTING SCREW HOLES, 10-32 NF-28 THREADS X .219 REF. DEEP.

2-8-32 NC X .219 REF. BINDER HEAD TERMINAL SCREWS AND CUPWASHERS

3-SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE.