

CABLE / Kabel

Flat cable LIYZ 2x0.14mm²
 colour white
 ends tinned
 Flachkabel LIYZ 2x0.14 mm²
 Farbe weiss
 Enden verzinkt




Abmessungen / Dimension (mm)
 Tolerances acc. to DIN ISO 2768-m

MARKING / Aufdruck

MEDER-Label, Type
 Production code EN60062/
 Factory code
 Circuit diagram
 MEDER-Logo, Typ
 Produktionscode
 EN60062/Fertigungsstätte
 Schaltbild

CIRCUIT DIAGRAM



Magnetical properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20°C	23		44	AT
Test equipment		KMS-14			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	VDC
operating ampere	DC or Peak AC			1,25	A
Switching current				0,5	A
Sensor-resistance	measured with 40% overdrive			320	mOhm
Housing material		PBT glass fibre reinforced			
Case color		white			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	Cable not moved	-30		70	°C
Operating temperature	cable moved	-5		70	°C
Storage temperature		-30		70	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		flat cable			
Cable material		PVC			
Cross section [mm ²]		0,14			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		from 5m cable, a pre-resistor is recommended.			
mounting advice 1		Decreased switching distances by mounting on iron			
mounting advice 2		Magnetically conductive screws must not be used			
tightening torque	Screw M3 ISO 1207 Disk ISO 7089			0,5	Nm

Modifications in the sense of technical progress are reserved