

# MINI-PS-100-240AC/ 5DC/3

Order No.: 2938714




DIN rail power supply unit 5 V DC/3 A, primary switched-mode, narrow design

Commercial data	
EAN	4017918900502
Pack	1 Pcs.
Customs tariff	85044040
Weight/Piece	0.1928 KG
Catalog page information	Page 504 (IF-2007)

**Product notes**

WEEE/RoHS-compliant since:  
08/17/2006



Technical data	
<b>Input data</b>	
Nominal input voltage	100 V AC ... 240 V AC
AC input voltage range	85 V AC ... 264 V AC
DC input voltage range	90 V DC ... 350 V DC
AC frequency range	45 Hz ... 65 Hz

DC frequency range	0 Hz
Current consumption	Approx. 0.4 A (120 V AC)
	0.2 A (230 V AC)
	Approx. 0.4 A (for 90 V DC)
	Approx. 0.2 A (for 350 V DC)
Nominal power consumption	15 W
Inrush surge current	< 15 A (typical)
Power failure bypass	> 30 ms (120 V AC)
	> 140 ms (230 V AC)
Input fuse	2 A (slow-blow, internal)
Recommended backup fuse	6 A
	10 A
	16 A (characteristic B)

**Output data**

Nominal output voltage	5 V DC $\pm$ 1%
Setting range of the output voltage	4.5 V DC ... 5.5 V DC (> 5 V constant capacity)
Output current	3 A (-25°C ... 70°C)
	5 A (with POWER BOOST, -25°C ... 40°C permanent)
Connection in parallel	Yes, for assembling redundant systems and increasing efficiency
Connection in series	No
Residual ripple	< 40 mVPP
Peak switching voltages nominal load	< 50 mVPP (20 MHz)
Maximum power dissipation idling	1 W
Power loss nominal load max.	5 W

**General data**

Width	22.5 mm
Height	99 mm
Depth	107 mm
Weight	0.17 kg
Operating voltage display	LED green
Efficiency	> 73 % (At 230 V AC and nominal values)
Insulation voltage input/output	3 kV (routine test)
	4 kV (type test)
Degree of protection	IP20

Class of protection	II (in an enclosed control cabinet)
MTBF	> 500 000 h in acc. with IEC 61709 (SN 29500)
Ambient temperature (operation)	-25 °C ... 70 °C (> 60°C derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (at 25°C, no condensation)
Mounting position	Horizontal DIN rail NS 35, EN 60715
Assembly instructions	Can be aligned: Horizontal 0 cm, vertical 5 cm
Electromagnetic compatibility	Conformance with EMC directive 89/336/EEC
Emitted interference	EN 50081-2
Immunity to interference	EN 61000-6-2
Standard – Safety transformers for switched-mode power supply units	EN 61558-2-17
Standard - Electrical safety	EN 60950/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Standard - Safe isolation	DIN VDE 0100-410 DIN VDE 0106-1010
Standard – Limitation of mains harmonic currents	EN 61000-3-2
Standard – Equipment safety	GS (tested safety)
UL approvals	UL/C-UL listed UL 508 UL/C-UL Recognized UL 60950 UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D

**Connection data, input**

Type of connection	Pluggable screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	7 mm
Screw thread	M3

**Connection data, output**

Type of connection	Pluggable screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>

Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	7 mm

### Signaling

Output name	DC OK active
Status display	"DC OK" LED green

### Certificates / Approvals



Certification CUL Listed, GOST, UL Listed

Certification Ex: CUL-EX LIS, UL-EX LIS

### Drawings

#### Block diagram

