

Model #: PS4816

Tripp Lite Power Strip - Multiple outlets wherever you need them

Highlights

16 outlets

Convenient and safe covered, on/off switch

15-amp circuit breaker

15-ft. cord

48" length

Description

Tripp Li□

horizontal

2.717 inch cen

Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 16 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 48 in. corded, mountable power strip

Applications

Offers vertical or horizontal multi-outlet power distribution in rack enclosures, raceways, desktops and more.

Package Includes

PS4816

Mounting hardware

Instruction manual

Features

Sturdy all-metal 48 inch corded strip format with 2.717 inch center-to-center outlet spacing

Included mounting hardware supports vertical or horizontal mounting in rack enclosures, raceways and more Includes 16 NEMA 5-15R output receptacles

Ideal f

Lighted power switch with locking transparent cover prevents accidental shutoff

15 amp electrical capacity with circuit breaker

120VAC, 50/60Hz electrical compatibility

Lifetime warranty

Specifications

Votage compatibility 120 VAC Frequency compatibility 5050 Hz OUTPUT VIDINATION Output voit amp capacity (amps) 15A Output voit amp capacity (amps) 18 Nema 5-15R Outlet quantity / type 18 Nema 5-15R Outlet capacing 2.71 in. INPUT Input connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (ft.) 15 Input cord length (ft.) 15 Input play features Black Block 15 Locks ALARMS & SWITCHES 1 Witchigs witch cover 12 Transparent onloff switch controls power to all outlets Lock on Switch cover 1.52 Unit weight (ft.) 4.52 Unit weight (ft.) 4.52 Unit weight (ft.) 4.52 Unit Dimensions (HWD/cm) 4.52 × 1.5 Unit Dimensions (HWD/cm) 4.52 × 2.5 Waterial of construction 4.52 × 1.5 Mounting accessories in cluded	SYSTEM OVERVIEW	
OUTPUT Cutput voit amp capacity (amps) 15A Output watts 1500 Outlet quantity / type 16 Nema 5-15R Outlet spacing 2.717 in. INPUT Input Cord Sauge, type 14/3 SUT Input cord length (ft.) 15 Input cord length (ft.) 15 Input put port delight (m) 4.572 Recommended Electrical 15A 120V Switches Lighted 2 position switch controls power to all outlets Lecking switch cover Transparent on/off switch cover prevents accidental tum-off PHYSICAL 4.3 Unit weight (ft.) 4.3 Unit weight (ft.) 4.3 Unit weight (ft.) 4.3 Unit Dimensions (HWD/rm) 4.2 x 3.8 x 3.8 Material of construction Auminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications included Mounting accessories Includes mounting clips Included Black Ac Incord color Black Ac Incord color Black LI	Voltage compatibility	120VAC
Output volt amp capacity (amps) 15A Output watts 1800 Outlet quantity / type 18 Nema 5-15R Outlet spacing 2.717 in. INPUT Input connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical 15A 120V Switches Lighted 2 position switch controls power to all outlets Lecking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (kg) Unit Dimensions (HWDf)n) 48 x 1.5 x 1.5 Unit Dimensions (HWDf)n) 48 x 1.5 x 1.5 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications included Receptacle Color Black LETH CALL (CALL) UL 1863 CUL / CSA (Canada) UL 1863 CUL / CSA (Canada) UL 1863	Frequency compatibility	50/60 Hz
(amps) 1800 Output watts 1800 Outlet quantity / type 16 Nema 5-15R Outlet spacing 2.717 in. INPUT The put connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical service Black LEDS ALARMS & SWITCHES Uighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental tum-off PHYSICAL Unit weight (kg) 4.3 Unit weight (kg) 4.9522 Unit Dimensions (HWD/m) 48 x 1.5 x 1.5 Unit Dimensions (HWD/m) 42 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications included Receptacle Color Black AC line cord color Black LT1353 (Power Tap) UL1363 CUL7 (SA (Canada) UL1363	OUTPUT	
Outlet quantity / type 16 Nema 5-15R Outlet spacing 2.717 in. INPUT Input connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical service Black Input plug features Black LEDS ALARMS & SWITCHES Ughted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (fts) 4.3 Unit plimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/im) 48 x 1.5 x 1.5 Unit Dimensions (HWD/im) 48 x 1.5 x 1.5 Wounting accessories included Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Black AC line cord color Black AC line cord color Black AC line cord color Black LI 1363 (Power Tap) UL 1363 UL 1363 (Power Tap) UL 1363		15A
Outlet spacing 2.717 in. INPUT Input connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electricals revices Black Input plug features Black LEDS ALARMS & SWITCHES Ughted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48.1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications included Mounting accessories included Black AC line cord color Black AC line cord color Black CERTIFICATIONS Unit 363 Unit 363 (Power Tap) UL 1363 CUL / CSA (Canada) UL 1	Output watts	1800
INPUT Input connection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical Service 15A 120V Input plug features Black LEDS ALARMS & SWITCHES Elighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit begint (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Receptacle Color Black Coline cord color Black	Outlet quantity / type	16 Nema 5-15R
Input cornection type Nema 5-15P Input cord gauge, type 14/3 SJT Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical Service 15A 120V Input plug features Black LEDS ALARMS & SWITCHES Variable of part on/off switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental tum-off PHYSICAL 4.3 Unit weight (fts) 4.3 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/in) 48 x 1.5 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Mounting accessories included Includes mounting clips CERTIFICATIONS Ut 1363 ULT 363 (Power Tap) UL 1363 CUL / CSA (Canada) UL	Outlet spacing	2.717 in.
Input cord gauge, type 14/3 SJT 15 15 15 15 15 15 15 15 15 15 15 15 15	INPUT	
Input cord length (ft.) 15 Input cord length (m) 4.572 Recommended Electrical 5tA 120V Input plug features Black LEDS ALARMS & SWITCHES Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/im) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Includes mounting clips Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Input connection type	Nema 5-15P
Input cord length (m) 4.572 Recommended Electrical Service 15A 120V Input plug features Black LEDS ALARMS & SWITCHES Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Input cord gauge, type	14/3 SJT
Recommended Electrical Service Input plug features Black LEDS ALARMS & SWITCHES Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/im) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included AC line cord color Black CERTIFICATIONS UL 1363 (Power Tap) UL 1363 CUL / CSA (Canada) UARRANTY	Input cord length (ft.)	15
Service Black LEDS ALARMS & SWITCHES Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/in) 42 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 UL1 363 (Power Tap) UL1363 CUL / CSA (Canada) CUL	Input cord length (m)	4.572
LEDS ALARMS & SWITCHES Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips includes mounting clips Receptacle Color Black AC line cord color Black CERTIFICATIONS UL 1363 (Power Tap) UL 1363 CUL / CSA (Canada) cul WARRANTY		15A 120V
Switches Lighted 2 position switch controls power to all outlets Locking switch cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 cUL / CSA (Canada) CUL WARRANTY	Input plug features	Black
Locking switch cover PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) WARRANTY	LEDS ALARMS & SWITCHES	
PHYSICAL Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Switches	Lighted 2 position switch controls power to all outlets
Unit weight (lbs) 4.3 Unit weight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories Includes mounting clips included Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 cUL / CSA (Canada) cUL WARRANTY	Locking switch cover	Transparent on/off switch cover prevents accidental turn-off
Unit veight (kg) 1.9522 Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips included Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	PHYSICAL	
Unit Dimensions (HWD/in) 48 x 1.5 x 1.5 Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Aluminum Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Includes mounting clips Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 cUL / CSA (Canada) cUL WARRANTY	Unit weight (lbs)	4.3
Unit Dimensions (HWD/cm) 122 x 3.8 x 3.8 Material of construction Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) ULC WARRANTY	Unit weight (kg)	1.9522
Material of construction Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) WARRANTY	Unit Dimensions (HWD/in)	48 x 1.5 x 1.5
Form factors supported Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) WARRANTY	Unit Dimensions (HWD/cm)	122 x 3.8 x 3.8
Mounting accessories included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Material of construction	Aluminum
included Receptacle Color Black AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Form factors supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications
AC line cord color Black CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY		Includes mounting clips
CERTIFICATIONS UL1363 (Power Tap) UL1363 CUL / CSA (Canada) CUL WARRANTY	Receptacle Color	Black
UL1363 (Power Tap) UL1363 cUL / CSA (Canada) cUL WARRANTY CUL	AC line cord color	Black
cUL / CSA (Canada) cUL WARRANTY	CERTIFICATIONS	
WARRANTY	UL1363 (Power Tap)	UL1363
	cUL / CSA (Canada)	cUL
Product warranty Lifetime	WARRANTY	
	Product warranty	Lifetime