Protect It! Surge Suppressor

State-of-the-art protection for every application



Model #: TLP808TELTV

- 8 outlets / 8-ft. cord
- 3500 joule rating
- Coaxial surge protection
- Modem/fax surge protection
- > \$150,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's TLP808TELTV surge suppressor has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 3500 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment. \$150,000 Ultimate Lifetime Insurance (USA & Canada only).

KEY BUYING POINTS

- 8 outlets with integrated child safety covers; charcoal gray housing
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment; 6-ft. coax cable included
- · Surge suppression rating: 3500 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$150,000 Ultimate Lifetime Insurance (USA & Canada only)
- Diagnostic LEDs indicate protection present & ground present
- Audible alarm notifies user when the unit is damaged and needs to be replaced
- Keyhole supports for wall mounting
- · Lighted power switch
- Lifetime product warranty

TYPICAL APPLICATIONS

Ideal for home computers, TV/VCR/DVD players, stereos and other important electrical equipment

PACKAGE INCLUDES

- TLP808TEL
- 6-ft. telephone cord
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

TLP808TELTV surge suppression strip includes 8 AC outlets, 8 foot AC cord, single line phone suppression, coax line surge suppression, 3500 joule protection level, diagnostic

LEDs, 3 dedicated transformer outlets, lifetime warranty and \$150,000 connected equipment

insurance

Voltage compatibility: 120 VAC
Frequency compatibility: 50/60 Hz

OUTPUT

Output volt amp capacity (amps): 15
Output watt capacity (watts): 1800

Outlet quantity / type: 8 NEMA 5-15R output receptacles

Outlet orientation: Single row of 5, plus a second row of 3 for transformer accommodation

Outlet safety covers: Includes built-in sliding outlet safety covers

Transformer accommodation: Supports 3 large transformer plug accessories without covering remaining outlets, accepts up

to 6 transformers total

INPUT

Input connection type: NEMA 5-15P

Input cord length (ft.): 8
Input cord length (m): 2.4

Input plug features: Space-saving right angle input plug

Input cord gauge, type: 14 gauge, SJT

Recommended electrical service: 120V 15A

LEDS ALARMS & SWITCHES

Diagnostic LEDs: Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status

Alarms: Audible alarm sounds to indicate damage to suppression components

Switches: Combination AC circuit breaker and 2 position red illuminated on/off power switch

AC SURGE / NOISE SUPPRESSION

Protection modes: Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression

AC suppression joule rating: 3500 joules

Clamping voltage (RMS): 150V
AC suppression response time: < 1 ns

UL1499 let through rating: 330V - UL Verified

EMI / RFI filtering: Up to 40 dB

DATALINE SURGE SUPPRESSION

TEL / Modem line protection: Includes single line phone suppression via built-in RJ11 connectors, includes cable (260V

clamping, 120 joules, center 2 wires protected. 1 input jack and 2 output jacks)

Coax line protection: Includes coax line surge suppression via built-in Type F coax jacks, includes coax cable

PHYSICAL

Shipping weight (lbs): 2.5
Shipping weight (kg): 1.1
Unit weight (lbs): 1.6
Unit weight (kg): 0.7

Unit Dimensions (HWD/in): $1.6 \times 9.25 \times 4.25$ Unit Dimensions (HWD/cm): $4.1 \times 23.5 \times 10.8$ Shipping Dimensions (HWD/in): $2.5 \times 14.75 \times 8.75$ Shipping Dimensions (HWD/cm): $6.4 \times 37.5 \times 22.2$

Material of construction: Plastic

Keyhole mounting tabs enable wall mounting Integrated keyhole mounting tabs:

Housing color: Attractive dark grey color scheme

AC line cord color: Gray

CERTIFICATIONS

UL1449 1998 Rev. (AC Suppression): UL1449 UL1363 (Power Tap): UL1363 **UL497A UL497A (Communications):**

FCC Part 68 FCC Part 68 (Communications):

cUL cUL / CSA (Canada):

Industry Canada (Communications): Industry Canada

Approvals: Exceeds IEEE 587 category A&B specifications

WARRANTY

Lifetime **Product warranty:** Connected equipment insurance (USA and

Canada Only):

\$150,000

Data recovery warranty: Included

SPECIAL FEATURES

Additional Information: Pair of phone line output jacks serve as a line splitter to enable the protection of two devices

sharing a single dialup phone line

When you order today, you will receive the updated new version of these surge suppressors, however, they may be in packaging that still reflects the old specifications for joule and insurance amounts. In some cases the packaging you receive may have a sticker indicating these upgrades. This is simply due to an excess supply of existing packaging. Tripp Lite's ongoing commitment to having large quantities of product in stock at all times requires us to maintain large quantities of packaging. We are using this supply up as quickly as possible and are in the process of transitioning to new packaging. The timing will vary by product.

Please bear with us during this period of transition and rest assured that Protect It! Surge Suppressors are among the finest surge protection products available. If you want to know if your Protect It! Surge Suppressor offers the latest joule ratings and/or insurance amounts, refer to the date code on the back of your unit. If it was manufactured after 1/7/02 it is an upgraded version. For additional guestions feel free to contact our Technical support hotline at (773) 869-1234 or email techsupport@tripplite.com.

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.