

PC Board Right Angle JacksX

These BNC jacks are manufactured to the highest standards to assure stability in maintaining impedance matching at 50 ohm and 75 ohm applications. The 50 ohm versions have been approved by most of the U.S. manufacturers of LAN cards, and the 75 ohm is in wide use in High Definition Video applications which require the use of a True 75 ohm connector. Contacts are phosphor bronze and will remain resilient even after hundreds of insertions.

(75Ω)

N/A



Fig. 28



Fig. 29



Fig. 30



Fig. 31



Fig. 32



Fig. 33



Fig. 34



Fig. 35



Fig. 36 (top) Fig. 37

Part Number		Body Material	Description	Imp.	Height F.M.S.	Contact Plating	Fig. No.
364M095	✓	Nickel /Zinc	4 Post Low Profile, Metal	50Ω	.453	Gold	38
364M0975	✓	Nickel /Zinc	4 Post Low Profile, Metal	75Ω	.453	Gold	38
364A595	✓	White Valox	Standard Profile W/ Posts	50Ω	.610	Gold	28
364A595T	✓	White Valox	Standard Profile W/ Posts (TPX)	50Ω	.610	Gold	28
364A595NP*	✓	White Valox	Standard Profile WO Posts	50Ω	.610	Gold	35
364A595NPPT*	✓	White Valox	Standard Profile WO Posts (TPX)	50Ω	.610	Gold	35
364A595B	✓	Black Valox	Standard Profile W/ Posts	50Ω	.610	Gold	30
364A595BT	✓	Black Valox	Standard Profile W/ Posts (TPX)	50Ω	.610	Gold	30
364A595BNP*	✓	Black Valox	Standard Profile WO Posts	50Ω	.610	Gold	35
364A595BNPT*	✓	Black Valox	Standard Profile WO Posts (TPX)	50Ω	.610	Gold	35
364A595BL	✓	White Valox	Lo-Profile W/ Posts	50Ω	.515	Gold	29
364A595BLT	✓	White Valox	Lo-Profile W/ Posts (TPX)	50Ω	.515	Gold	29
364A595BLNP*	✓	White Valox	Lo-Profile W/O Posts	50Ω	.515	Gold	34
364A595BLB	✓	Black Valox	Lo-Profile W/ Posts	50Ω	.515	Gold	31
364A595BLBT	✓	Black Valox	Lo-Profile W/ Posts (TPX)	50Ω	.515	Gold	31
364A595BLBNP*	✓	Black Valox	Lo-Profile W/O Posts	50Ω	.515	Gold	34
364M595	✓	Nickel /Zinc	Standard Profile W/ Posts	50Ω	.620	Gold	32
364M595T	✓	Nickel /Zinc	Standard Profile W/ Posts (TPX)	50Ω	.620	Gold	32
364M595M	✓	Nickel /Zinc	Super Lo-Profile W/ Clips	50Ω	.340	Gold	35A
364M595MT	✓	Nickel /Zinc	Super Lo-Profile W/ Clips (TPX)	50Ω	.340	Gold	35A
364M595L	✓	Nickel /Zinc	Lo-Profile W/ Posts	50Ω	.529	Gold	33
364M595LT	✓	Nickel /Zinc	Lo-Profile W/ Posts (TPX)	50Ω	.529	Gold	33
364A595NP	✓	White Valox	Standard Profile WO Posts	50Ω	.610	Gold	35
364A595NPPT	✓	White Valox	Standard Profile WO Posts (TPX)	50Ω	.610	Gold	35
364A595BNP*	✓	Black Valox	Standard Profile WO Posts	50Ω	.610	Gold	35
364A595BLNP*	✓	White Valox	Lo-Profile W/O Posts	50Ω	.515	Gold	-
364A595BLBNP*	✓	Black Valox	Lo-Profile W/O Posts	50Ω	.515	Gold	34
364A795	✓	White Valox	Standard Profile W/ Posts (TPX)	75Ω	.610	Gold	28
364A795T	✓	White Valox	Standard Profile W/ Posts	75Ω	.610	Gold	28
364A795B	✓	Black Valox	Standard Profile W/ Posts	75Ω	.610	Gold	30
364A795BT	✓	Black Valox	Standard Profile W/ Posts (TPX)	75Ω	.610	Gold	30
364A795BL	✓	White Valox	Lo-Profile W/ Posts	75Ω	.515	Gold	29
364A795BLT	✓	White Valox	Lo-Profile W/ Posts (TPX)	75Ω	.515	Gold	29
364A795BLB	✓	Black Valox	Lo-Profile W/ Posts	75Ω	.515	Gold	31
364A795BLBT	✓	Black Valox	Lo-Profile W/ Posts (TPX)	75Ω	.515	Gold	31
364M795	✓	Metal	Standard Profile W/ Posts	75Ω	.620	Gold	32
364M795T	✓	Metal	Standard Profile W/ Posts (TPX)	75Ω	.620	Gold	32
364M795L	✓	Metal	Lo-Profile W/ Posts	75Ω	.529	Gold	33
364M795LT	✓	Metal	Lo-Profile W/ Posts (TPX)	75Ω	.529	Gold	33
364F595BL	✓	White Valox	9400pF 500V Decoupled	50Ω	.515	Gold	36
364F595BLB	✓	Black Valox	9400 pF 500V Decoupled	50Ω	.515	Gold	37
364H595BL	✓	White Valox	9400 pF 1500V Decoupled	50Ω	.515	Gold	36
364H595BLB	✓	Black Valox	9400 pF 1500V Decoupled	50Ω	.515	Gold	37
364NT	✓	Zinc/Brass	Jam Nut (364 Series)	N/A	----	----	36N
364LW	✓	Zinc/Steel	Lock Washer (364Series)	N/A	----	----	37N
364 KNT	✓	Brass/Nickel	Knurled Nut (364 Series)	N/A	----	----	38N

✓ RoHS compliant reflow or wave solder ✓ RoHS compliant wave solder only

(TPX) insulator for re-flow solder