



V-Bite® PC Edge Mount

The V-Bite® is an industry award winning design PCB connector with all the advantages a designer could want. It edge mounts to the board which offers the lowest profile and utilizes very little PCB real estate. It lends itself to surface mount and through-hole soldering techniques. There are versions for IR and convection reflow soldering. Because the connector locks into place both above and below the PCB it disperses rotational torque relief to the board and not the solder points. The V-Bite® design offers the lowest VSWR ratings due to the straight through-put contact design. No right angles for reflection. Available in 50 and 75 ohm, threaded and non-threaded. Other options for PCB thickness available. Other interfaces available. See "F", BNC Twin, TNC and N sections.

Part Number	RoHS	Description	Imp	Contact	Fig. No.
361V504ER	<input checked="" type="checkbox"/>	BNC Jack W/ Teflon For Reflow Solder	50W	Phos./Gold	39A
361V504ET	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Teflon For Reflow Solder	50W	Phos./Gold	39
361V504EFT	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Teflon Insulator/Flange	50W	Phos./Gold	39B
361V509E	<input checked="" type="checkbox"/>	BNC Jack W/ Polyethylene Insulator	50W	Phos./Tin	39A
361V509ET	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Polyethylene Insulator	50W	Phos./Tin	39
361V704ER	<input checked="" type="checkbox"/>	BNC Jack W/ Teflon For Reflow Solder	75W	Phos./Gold	39A
361V704ET	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Teflon For Reflow Solder	75W	Phos./Gold	39
361V704EFT	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Teflon Insulator/Flange	75W	Phos./Gold	39B
361VH704EFT	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Teflon Insulator/Flange 4GHZ	75W	Phos./Gold	—
361V709E	<input checked="" type="checkbox"/>	BNC Jack W/ Polyethylene Insulator	75W	Phos./Gold	39A
361V709ET	<input checked="" type="checkbox"/>	BNC Threaded Jack W/ Polyethylene Insulator	75W	Phos./Gold	39
361E704ER	<input checked="" type="checkbox"/>	BNC End launch W/Teflon for Reflow Solder, gold plated	75W	Phos./Gold	39H
361KNT	<input checked="" type="checkbox"/>	Knurled nut (361 series)	NA	—	—
3M61V704	<input checked="" type="checkbox"/>	Mini-BNC Jack W/Teflon for Reflow	75W	Phos./Gold	—
461V504E	<input checked="" type="checkbox"/>	Twin-BNC Jack W/ Teflon For Reflow Solder	75W	Phos./Gold	***
561V504E	<input checked="" type="checkbox"/>	TNC Jack W/ Teflon For Reflow Solder	50W	Phos./Gold	***
861V509E	<input checked="" type="checkbox"/>	F type Edge Mount Jack (RG59)	*NCI	Phos./Gold	39C
861V509ER	<input checked="" type="checkbox"/>	F type Edge Mount Jack w/ TFE Insul. for Reflow (RG59)	*NCI	Brass/Gold	39C
861V509ER6	<input checked="" type="checkbox"/>	F type Edge Mount Jack w/ TFE Insul. for Reflow (RG6, RG59)	75W	Brass/Gold	39C
861VH509ER6	<input checked="" type="checkbox"/>	F type Edge Mount Jack w/ TFE Ins. for Reflow (RG6.59) 5GHZ	75W	Brass/Gold	39C
862V509ER6	<input checked="" type="checkbox"/>	F type Edge Mount Plug w/TFE insul for reflow	75W	Brass/Gold	—
161V504E	<input checked="" type="checkbox"/>	N type Edge Mount Jack w/ TFE Insul for reflow	50W	Brass/Gold	39D
161V504EFT	<input checked="" type="checkbox"/>	N type Edge Mount Jack w/ Flange TFE Insul for reflow	50W	Brass/Gold	39E
162V504E	<input checked="" type="checkbox"/>	N Type Edge Mount Plug (TFE Insul for reflow)	50W	Brass/Gold	39F
R061V704ER	<input checked="" type="checkbox"/>	RCA Type Edge Mount Jack w/TFE for reflow	75W	Brass/Gold	39G

RoHS compliant reflow or wave solder RoHS compliant wave solder only

*NCI (non constant impedance)



Patented V-Bite®
SnapsIntoPCB
SurfaceMountCenterContact
Pick&PlaceVersionAvailable



Fig. 39



Fig. 39A



Fig. 39B



Fig. 39C



Fig. 39D



Fig. 39E



Fig. 39F



Fig. 39G



Fig. 39H

