

Power Transformer Chassis Mount: Quick Pack

FD4-120

Description:

The FD4-120 Quick Pack small power transformer offers a significant reduction in size and weight over a standard transformer. This transformer can be used for a wide variety of applications. It is bobbin wound for reduced size and small operating space.

Electrical Specifications (@25C); Maximum Power: 6.0VA Input Voltage: Series: 230VAC@50/60Hz Parallel: 115VAC@50/60Hz

Output Voltage: 120VCT@0.05A

Construction:

Split bobbing non concentric winding eliminates costly electrostatic shielding. Termination is suitable for quick connects or soldering.

Safety:

UL Class B E53148



Dimensions:

А	В	С	D	Е	F	G
1.375	2.0±.03	2.375	1.250	1.687	.187 Dia	.687


Notes: 1. Units: inches.

2. Terminal size: .187" X 0.021".

Connect 2 & 3

3. Weight: .44 lbs

Schematic:




Output: 5 to8

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2002/95/EC, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757	22520B Temescal Canyon Road Corona, California 92883	Publish Date: February 4, 2010
---	--	--------------------------------





С