

EcoLine™ Contact Cleaner

General Purpose Contact Cleaner 1622

Introduction

EcoLine[™] Contact Cleaner is a hexane mixture that cleans electrical contacts and connections. Ideal for switches, relays, contact pads and other electrical connections. Safe on most plastics, the solvent will not damage switch housing.

Features / Benefits

EPA SNAP Approved Non-Ozone Depleting Safe on Most Plastics Zero Residue Rapidly Evaporating

Physical Properties		
Boiling Point	80°C / 176°F	
Flash Point (TCC)	-15°F	
Evaporation Rate	NIF	
Surface Tension		
Kauri-Butanol (KB Value)		

Chemical Components

Isopropanol	(67-63-0)	8-12%-Aerosol 10-15%-Bulk
Denatured Alcohol 2-Methyl-2-Propanol		18-25% <<1%-Aerosol 3.4%-Bulk
Carbon Dioxide (Aerosol Propellant) Hexane Isomers Consisting of:	. (124-38-9)	1-4%
n-Hexane	. (110-54-3)	39-43%
Methylcycle pentane	.(96-37-7)	8-10%
Methyl pentane	varies	12-18%
Acetic Acid, Propyl Ester		< 3%-Aerosol 5-10%-Bulk

Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Excellent	PMMA	Excellent
Nylon	Excellent	POM	Excellent
Lexan	Excellent	PP	Excellent
HDPE	Excellent	PS	Excellent
CDPE	Excellent	PTFE	Excellent
C. E. Phenolic	Excellent	PVC	Excellent

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

EcoLine[™] Contact Cleaner may be ordered in the following container sizes:

1622-10S	10 Ounce Aerosol
1622-13S	13 Ounce Aerosol
1622-54G	340 pounds in metal drum



MSDS No: 1622-A CARB Compliant

Ecoline Contact Cleaner

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Ecoline Contact Cleaner PRODUCT DESCRIPTION: Contact Cleaner PRODUCT CODE: 1622-10S,-13S ACTIVE INGREDIENT(S): 2-Propanol; Ethanol

MANUFACTURER

Techspray, L.P.

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"F" - Highly flammable R11 - Highly flammable.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Transparent, colorless liquid.

IMMEDIATE CONCERNS: Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. Causes skin irritation. Harmful if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

SKIN: Prolonged or repeated skin contact may cause irritation.

INGESTION: This material may be harmful or fatal if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Liquid splashed in the eye may cause redness, irritation and conjunctivitis.

SKIN: Prolonged or exposure may cause skin irritation.

INGESTION: Swallowing of this material may result in nausea, vomiting and weakness followed by central nervous system depression.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: Contains Methanol which has been established as a teratogen by inhalation. See Sec.11 for details.



MSDS No: 1622-A CARB Compliant

Ecoline Contact Cleaner

TARGET ORGAN STATEMENT: Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS	EINECS
n-Heptane	50 - 6	5 142-82-5	
2-Propanol	7 - 15	67-63-0	200-661-0
Ethanol	10 - 20	64-17-5	200-578-6
Methanol	1 - 3	67-56-1	200-659-6
n-Propyl acetate	< 1	109-60-4	2036861
1,1-difluoroethane (HFC-152a)	20 - 30) 75-37-6	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but do not induce. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (22°F) TAG CC **Notes:** Non-propellant material ("cold fill") only.

FLAMMABLE LIMITS: 1.1 (Heptane) to 6.7 (Heptane)

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressuredemand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain spill with dike to prevent entry into sewers.

LARGE SPILL: Clean up spills immediately, observing precautions in Protective Equipment section.

GENERAL PROCEDURES: Dike area to contain spill. Take precautions as necessary to prevent



MSDS No: 1622-A CARB Compliant

Ecoline Contact Cleaner

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: For prolonged or repeated use, wear nitrile, neoprene, or natural rubber gloves.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

WORK HYGIENIC PRACTICES: Wash hands before eating and wash before reuse.

OTHER USE PRECAUTIONS: Emergency shower and eyewash facility should be in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point	Boiling Point (°C)	Specific Gravity
2-Propanol	53.6	82.4	0.785

ODOR: Characteristic odor.

APPEARANCE: Clear, Colorless liquid

pH: Not Applicable

PERCENT VOLATILE: 100 at 20°C (68°F)

VAPOR PRESSURE: 55.49 mmHg@20C (VOC Composite Vapor Pressure)

BOILING POINT: Not Determined

FREEZING POINT: Not Applicable

MELTING POINT: Not Applicable

FLASHPOINT AND METHOD: (22°F) TAG CC **Notes:** Non-propellant material ("cold fill") only.

SOLUBILITY IN WATER: to 32 at 20°C (68°F)

EVAPORATION RATE: > 1 (TCE=1)

DENSITY: 0.713g/mL at 25°C

VISCOSITY: Not Applicable

(VOC): 75.000 % by weight Notes: Meets VOC requirements for CARB Category: Electronic Cleaner

10. STABILITY AND REACTIVITY



MSDS No: 1622-A CARB Compliant

Ecoline Contact Cleaner

STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Stable. However, may decompose if heated.

INCOMPATIBLE MATERIALS: Incompatible with alkali or alkaline earth metals - powdered Al, Zn, Be, etc.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Methanol	6.2 to 12.98 mg/kg	16 g/kg	64000 ppm
n-Propyl acetate	9370 mg/kg	> 20 ml/kg	8000 ppm

DERMAL LD₅₀: Slight to very low toxicity.

ORAL LD₅₀: Practically non-toxic to animals. However, based on reports of human exposure to Methanol, a small amount (usually two or more ounces) can cause mental sluggishness, nausea and vomiting leading to severe illness, blindness or death if treatment is not received.

INHALATION LC₅₀**:** Slight to very low toxicity.

EYE EFFECTS: Mixture is a moderate eye irritant.

SKIN EFFECTS: Based on human exposure reports, prolonged and repeated skin contact with Methanol has produced toxic effects including vision effects and death.

CARCINOGENICITY

Chemical Name	NTP	IARC	OSHA
	Status	Status	Status
2-Propanol	NOT	NOT	NOT
	LISTED	LISTED	LISTED
Ethanol	NOT	NOT	NOT
	LISTED	LISTED	LISTED
Methanol	NOT	NOT	NOT
	LISTED	LISTED	LISTED
n-Propyl acetate	NOT	NOT	NOT
	LISTED	LISTED	LISTED

TERATOGENIC EFFECTS: Information for Methanol: In an inhalation developmental toxicity study, rats were exposed 6hrs./day to 5000 - 20000 ppm vapors. A significant teratogenic response was seen at 20000 ppm. Fetotoxicity was noted at 10000 ppm, but not at 5000 ppm.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial



MSDS No: 1622-A CARB Compliant

Ecoline Contact Cleaner

311/312 HAZARD CATEGORIES: IMMEDIATE / DELAYED

FIRE: Yes PRESSURE GENERATING: Yes ACUTE: Yes CHRONIC: Yes

313 REPORTABLE INGREDIENTS: 2-propanol (CAS #67-63-0)

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
2-Propanol	7 - 15	67-63-0
Methanol	1 - 3	67-56-1

TITLE III NOTES: Not listed as an Extremely Hazardous Substance.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Methanol (#67-56-1)

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Methanol (#67-56-1)

Chemical Name	Wt.%	CERCLA RQ
Methanol	1 - 3	1* lbs.

CERCLA RQ: Methanol has an RQ of 5000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-Propanol	67-63-0
Ethanol	64-17-5
Methanol	67-56-1
n-Propyl acetate	109-60-4
1,1-difluoroethane (HFC-152a)	75-37-6

TSCA REGULATORY: This product is listed on the TSCA Inventory.

CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Methanol (CAS# 67-56-1)

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS

CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals known to the State of California to cause cancer.

RCRA STATUS: D001

OSHA HAZARD COMM. RULE: Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.